



SX302

PROMOTION



Promotion from 1st Oct to 31st Dec 2023 via Tremco approved distribution partners.



PROMOTION

**BUY 10 UNITS
GET 1 FREE UNIT**

Contact your local Tremco Area Sales Manager to take advantage of this deal.



SX302 MOISTURE TOLERANT LATEX UNDERLAYMENT

SX302 is a moisture tolerant cement based latex underlayment and has been developed for use in domestic, light commercial and light industrial environments prior to application of carpet, wood and vinyl flooring. SX302 is not suitable for use in areas that may be subject to high point loading. The product is moisture tolerant for use under surface damp proof membranes.

- Protein free - suitable for use in biologically sensitive areas
- Moisture tolerant – can be used under a DPM
- Extremely low odour with no unpleasant ammonia smell

TECHNICAL DATA

PROPERTY	RESULT
Composition	Cementitious powder and liquid latex dispersion
Pot Life (at 20 °C)	20 minutes
Compressive Strength	After 28 days approx. 25 N/mm ²
Coverage	Approx. 5 m ² per unit @ 3 mm thickness
	Thicknesses of 6 mm to feather edge can be applied dependant on surface profile. An average thickness of 3 mm will provide a coverage rate of 5 m ² per mix
	Thicknesses of 8 mm to 30 mm can be achieved by incorporating an equal volume of 3 mm granite chippings
	This will depend on the condition of the substrate and method of preparation (please refer to Tremco CPG UK Limited Technical Department)
Cure Time (at 20 °C)	Foot Traffic: 90 minutes
Storage	Store in dry, shaded conditions between +5 °C and +25 °C
Shelf Life	6 months when stored as recommended in original unopened packaging
	High temperatures and humidity will lead to a reduced shelf life

Tremco CPG UK Limited, Coupland Road,
Hindley Green, Wigan, WN2 4HT UK

+44 (0) 1942 251400

hello@tremcocpg.com

www.tremco-europe.com