

**MIND THE GAP**

# **IMPREGNATED EXPANDING FOAM TAPES**



## **TP600 NG COMPRIBAND - IMPREGNATED SEALING TAPE**

Tape reference	Suitable joint depth options (mm)	Suitable joint width for 600 Pa (Hurricane) (mm)	Suitable joint width for 450 Pa (Storm) (mm)	Roll length (m)
2	10,15,20	2	2	10,0
3	12,15,20	3	3	8,0
3 to 7	15,25	3 to 4	3 to 7	7,0
4 to 10	15,20	4 to 5	4 to 10	5,6
5 to 12	15,20	5 to 7	5 to 12	4,3
6 to 14	20,25	6 to 10	6 to 14	3,6
7 to 15	20,25	7 to 11	7 to 15	3,3
9 to 18	20	9 to 14	9 to 18	6,5
9 to 18	22,25,30	9 to 18	9 to 18	6,5
11 to 24	28,30	11 to 24	11 to 24	5,2
13 to 32	32,35,40	13 to 32	13 to 32	4,0
18 to 40	35,40	18 to 40	18 to 40	2,7
26 to 54	55	26 to 54	26 to 54	2,2
30 to 67	70	30 to 67	30 to 67	2,2


**MIND THE GAP**

# SIZE COMPARISON CHART



## PREVIOUS TP600

Previous Size Reference	Available Widths (mm)	Weather Performance to 600 Pa (mm)
2	10	2
3	10	3
3-7	10,15,20	3-7
5-10	10,15,20	5-10
7-12	15,20	7-12
8-15	15,20,25,30	8-15
10-18	20,25,30	10-18
13-24	20,25,30	13-24
17-32	30,35	17-32
22-40	40	22-40
39-54	55	39-54
52-67	70	52-67

## NEW TP600 NG

Tape reference	Suitable joint depth options (mm)	Suitable joint width for 600 Pa (Hurricane) (mm)	Suitable joint width for 450 Pa (Storm) (mm)
2	10,15,20	2	2
3	12,15,20	3	3
3 to 7	15,25	3 to 4	3 to 7
4 to 10	15,20	4 to 5	4 to 10
5 to 12	15,20	5 to 7	5 to 12
6 to 14	20,25	6 to 10	6 to 14
7 to 15	20,25	7 to 11	7 to 15
9 to 18	20	9 to 14	9 to 18
9 to 18	22,25,30	9 to 18	9 to 18
11 to 24	28,30	11 to 24	11 to 24
13 to 32	32,35,40	13 to 32	13 to 32
18 to 40	35,40	18 to 40	18 to 40
26 to 54	55	26 to 54	26 to 54
30 to 67	70	30 to 67	30 to 67