

# RW120

## TREMDRAIN DUO VERTICAL OUTLET



Lasting Performance

### KEY BENEFITS SUMMARY



- Excellent flow rates
- Two part outlet sealed at AVCL
- Allows immediate temporary waterproofing once the AVCL has been applied
- Robust stainless steel construction
- Integrated membrane flange allows for flush detailing
- Outlet to internal downpipe connection options

### PRODUCT INFORMATION

#### Description

RW120 is a prefabricated 2-part, gravity fed, vertical drainage outlet manufactured from stainless steel and includes an integral membrane flange.

#### Usage / Purpose

RW120 outlets are designed to effectively drain rainwater from Tremco flat roof systems and robustly connect to an internal downpipe infrastructure. RW120 outlets have two parts enabling the lower section to be sealed during AVCL installation providing immediate temporary waterproofing.

#### Packaging

Units are boxed. Quantity and design subject to project.

#### Availability

Direct from Tremco CPG UK Limited (see bottom of leaflet for address and telephone details).

#### Application Instructions

RW120 consists of 2 components:

Stainless steel outlet spigot with pre-drilled fixing holes.

Factory laminated integral membrane flange.

Firstly locate the pre-drilled holes in the stainless steel base plate and secure with substrate specific screws into solid grounds. Once the thermal insulation has been applied, the top section of the 2-part outlet can be inserted through the system to engage the bottom base plate. The integral membrane flange should be dressed into the proposed membrane system as per Tremco specification guidelines. Avoid prominent laps where possible.

### Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

### Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

# RW120

## TREMDRAIN DUO VERTICAL OUTLET



Outlet size	Flow rate including leafguard type l/sec	To suit pipe size (mm) where outlet is inserted into existing pipe in refurbishment situations	O-ring seal diameter (mm)	Membrane attachment
75mm	2.98	82-97	8	500 x 500
110mm	3.94	120-128	10	500 x 500
125mm	5.30	135-143	10	500 x 500
160mm	6.76	170-178	10	500 x 500