

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

No. FO100 – 20170702

P1/3

- 1. Unique identification code of the product-type:** FO100
- 2. Intended use/es:** Is a flexible pad or cord used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of pipes into socket boxes, on both sides of the wall.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** EAD 350454-00-1104, September 2017
European Technical Assessment: ETA 18/0579
Technical Assessment Body: CPR Notified Body UL International (UK) Ltd, NB 0843
Notified Body: CPR Notified Body UL International (UK) Ltd, NB 0843
- 7. Declared performance/s:**

Basic Work Requirement	Performance
Safety in case of fire	
Reaction to fire (EN 13501-1)	NPD
Resistance to fire (EN 13501-2)	See ETA18/0579 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	NPD
Water Permeability (ETAG 026-3 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	NPD
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₂

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Business Unit Director Sealants & Coatings



At Wigan on 24 November 2017

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

No. FP302 – 20170630

DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

Nullifire
Smart Protection

P2/3

CE	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 18 0843-CPR-0457 FO100 – 20170702 www.nullifire.com/FO100/	
EN 1366-3: 2009 ETA 18-0579 ETAG 26, Part 2	
Is a flexible pad or cord used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of pipes into socket boxes, on both sides of the wall.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	NPD
Resistance to fire	See ETA17/0579 Annex A
Hygiene, Health and Environment	
Air Permeability (EN 1026:2000)	NPD
Release of dangerous substances	Declaration of manufacturer
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	NPD
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₂