

# **Declaration of Performance**

According Annex III of the Regulation (EU) No 305/2011 Amended by Commisions delegated Regulation (EU) No 574/2014

No: FL-02019

For the system build-up: Peran ESD SL consisting of:		
Primer:	Flowprime or Flowprime LW or Protop 1000 or Hydraseal DPM	
Anti-Static Primer:	Peran ESD Primer WB	
Main layer:	Peran ESD SL	

as described in our technical datasheets and application instruction guide.

1. Unique identification code of the product type:

## Peran ESD SL

2. Intended use/es:

### Synthetic resin screed for indoor use

3. Manufacturer:

Tremco CPG Poland Sp. z o.o. Ul. Marywilska 34, 03-288 Warszawa Poland

4. System/s of AVCP

System 4 System 3 (for reaction to fire)





5. A) Harmonised standard

## EN13813:2002

B) Notified body

### not applicable

6. Declared performance/s for Peran ESD SL

Essential characteristics	Performance	Harmonized technical specification
Release of corrosive	SR	
substances		
Wear resistance	AR0.5	EN 13813:2002
Impact resistance	IR4	EN 13013.2002
Bond strength	B2.0	
Reaction to fire	B <sub>fl</sub> -s1	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued in accordance with Regulation (Eu) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed on behalf of the manufacturer by:

Bartosz Mysior, Operations Director

At Warsaw, Poland on 10.06.2024

(authorised signature)





# **CE-marking**

CE			
Tremco CPG Poland Sp. z o.o.			
UI. Marywilska 34, 03-288 Warszawa, Poland			
Peran ESD SL			
08			
DoP no FL-02019			
EN 13813: 2002			
Synthetic resin screed for indoor use			
Release of corrosive substances	SR		
Abrasion resistance (BCA test)	AR0.5		
Impact resistance	IR4		
Bond strength	B2.0		
Reaction to fire	B <sub>fl-S1</sub>		

# **UKCA-marking**

UK CA			
Tremco CPG Poland Sp. z o.o.			
UI. Marywilska 34, 03-288 Warszawa, Poland			
Peran ESD SL			
22			
DoP no FL-02019			
EN 13813: 2002			
Synthetic resin screed for indoor use			
Release of corrosive substances	SR		
Abrasion resistance (BCA test)	AR0.5		
Impact resistance	IR4		
Bond strength	B2.0		
Reaction to fire	B <sub>fl-S1</sub>		

