



INDUSTRIAL FLOORING

- Durable workhorse surfaces suited to use in a wide range of demanding industrial plants and process environments.

Industrial Flooring Range



Flowcrete’s Industrial Flooring range has been developed to deliver the ultimate in durability and resistance for hard-wearing surfaces that stand the test of time.

Reliable formulations stand up to heavy forklift, pallet truck and pedestrian traffic, whilst boasting impressive resistance levels against aggressive chemicals, cleaning agents and spillages across a number of production areas. For areas subject to extreme temperature change or chemical attack, Flowcrete has developed Flowchem VE.

What’s more, Flowcrete’s Industrial flooring range offers everything from textured finishes for slip resistance to UV stability to maintain colour vibrancy. Some ranges are even available in an antistatic grade for the protection of sensitive electronic equipment, resulting in a range of flooring solutions perfect for a variety of heavy duty industrial environments.



Flowcrete’s range of industrial resin flooring systems are classified by FeRFA resin types. For more information, visit www.ferfa.org.uk

Application Suitability



Manufacturing



Aerospace



Automotive



Electronic



Pharmaceutical



Food and Drink Processing

Industrial Flooring Product Selector



Hygienic Finish

Slip Resistant

Temperature Resistant

Chemical Resistant

Fast Cure

Durable Finish

Antistatic Properties

FeRFA Type 1 - Light Duty Floor & Wall Seal Coats

Flowseal EPW	✓						✓
--------------	---	--	--	--	--	--	---

FeRFA Type 3 - Medium Duty, High Build Floor Coatings

Flowcoat SK		✓		✓			
Flowcoat SF41		✓					
Flowcoat LXP		✓					

FeRFA Type 5 - Medium to Heavy Duty, Self-smoothing Floor Finishes

Flowfresh SL	✓			✓		✓	
Flowshield SL						✓	
Flowshield LXP	✓		✓				
Flowshield LXP HD						✓	

FeRFA Type 6 - Medium to Heavy Duty, Trowel-applied Resin Flooring

Peran STB		✓				✓	✓
Flowfast Quartz		✓	✓	✓	✓	✓	

FeRFA Type 7 - Heavy Duty, Flowable Flooring

Flowfresh MF	✓		✓	✓		✓	
--------------	---	--	---	---	--	---	--

FeRFA Type 8 - Very Heavy Duty Resin Flooring

Flowfresh HF	✓	✓	✓	✓		✓	✓
Flowfresh RT	✓	✓	✓	✓		✓	✓
Mondéco Earth						✓	✓
Mondéco TZ	✓		✓	✓		✓	✓

Contains Polygiene®, a silver-ion based antimicrobial agent for superior hygiene.

Low slip potential in accordance with OSHA and ADA guidelines.

Demonstrates superior resistances to sustained high temperatures.

Excellent resistance to acids, alkalis, fats, oils and other substances.

Fast track installation and cure times in order to minimise downtime.

With correct maintenance, offers 10 year life expectancy or greater.

ESD grade available to safely dissipate the build-up of electrostatic charge.

WHERE YOU SEE THIS SYMBOL, AN ESD GRADE IS AVAILABLE

Standard Colours

		
Light Grey 232	Beige 326	Goosewing Grey 222
		
Tile Red 637	Mid Grey 280	Forest Green 754
		
Dark Grey 281	Traffic Blue 466	

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.






Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	6 Nm
BOND STRENGTH	
EN 1542	> 3 N/mm ²
WEAR RESISTANCE	
EN ISO 5470-1 Taber Abrader (H22 wheels, 1000 cycles, 1 kg load)	Weight loss <100mg
CAPILLARY ABSORPTION & PERMEABILITY TO WATER	
EN 1062-3	0.005 kg/m ² × h ^{0.5}
VAPOUR PERMEABILITY	
ASTM:E96:90	20g / m ² / mm / 24hr

Flowseal EPW (0.12 mm)

Flowseal EPW provides a coloured, gloss or matte finish at ground level in areas of light traffic.

The seamless floor sealer is vapour permeable, allowing floors in light processing areas, storerooms and garages to breathe.

-  Seamless hygienic finish
-  Can be applied to damp substrates
-  Solvent free and low odour
-  Temperature resistant up to 70°C
-  Cost effective solution



Standard Flowcoat SF41 Colours



Light Grey
232



Beige
326



Goosewing Grey
222



Tile Red
637



Mid Grey
280



Forest Green
754



Dark Grey
281



Traffic Blue
466

Standard Flowcoat LXP Colours



Goosewing Grey
222



Beige
326



Mid Grey
280



Forest Green
754



Dark Grey
281







Tile Red
637

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

Flowcoat SF41 (0.35 mm)

A high performance, solvent free, epoxy resin coating that can deliver an anti-slip profile.

Flowcoat SF41 is also hard wearing against sustained vehicle traffic, as well as chemical and abrasion resistant. A SKYDROL Aviation Fluid grade is also available as Flowcoat SK.

-  Hard wearing and abrasion resistant
-  Aesthetically attractive with demarcation
-  Solvent free and low odour
-  Tailored anti-slip profile

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	10 Nm
BOND STRENGTH	
EN 1542	> 2.5 N/mm ²
WEAR RESISTANCE	
EN 13892-5	Abrasion quantity <1cm ²
CAPILLARY ABSORPTION & PERMEABILITY TO WATER	
EN 1062-3	0.001 kg/m ² × h ^{0.5}
COMPRESSIVE STRENGTH	
EN 13892-2	>80 N/mm ²




Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	13 Nm
BOND STRENGTH	
EN 1542	> 2.0 N/mm ²
CAPILLARY ABSORPTION & PERMEABILITY TO WATER	
EN 1062-3	0.001 kg/m ² × h ^{0.5}
FLEXURAL STRENGTH	
EN 13892-2	>15 N/mm ²
SURFACE HARDNESS	
ASTM D2240	65 (Shore D)

Flowcoat LXP (0.7 mm)

Flowcoat LXP is a two-pack, solvent free, flexible polyurethane coating applied in a thin layer.

Typically applied in light duty processing, manufacturing and warehousing areas, the seamless system provides a chemical and abrasion resistant solution.

-  Flexible coating
-  Excellent chemical resistance
-  Solvent free and low odour
-  Tailored anti-slip profile

Standard Flowfresh SL/MF Colours



The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



Standard Flowshield SL Colours



The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	15 Nm
TEMPERATURE RESISTANCE	
Intermittent Spills: Up to 60°C (SL) / 70°C (MF) Sustained Heat: -20°C to 50°C (SL) / 60°C (MF)	
BOND STRENGTH	
EN 1542	> 2.5 N/mm²
WEAR RESISTANCE	
EN 13892-8	Abrasion quantity <1cm²
COMPRESSIVE STRENGTH	
EN 13892-2	>50 N/mm² (SL) 55 N/mm² (MF)

Flowfresh SL/MF (2, 4–6 mm)

Flowfresh SL and MF are medium duty chemically resistant, antimicrobial treated polyurethane resin finishes.

The non-tainting, non-dusting surface provides an easy-to-clean surface with impressive durability under traffic and heavy plant machinery.

- Contains Polygiene® for superior hygiene
- Easy to clean and sterilise
- Resistant to a range of chemicals
- Durable and abrasion resistant
- Smooth, matte, coloured finish

Flowshield SL (2 mm)

Flowshield SL is a self smoothing resin finish for dry process areas subject to medium to heavy traffic.

The seamless finish provides a durable surface well suited to use in areas subject to foot, trolley and pallet truck and rubber wheeled traffic.

- Seamless, joint-free application
- Hard wearing finish
- Antistatic grade available
- Easy to clean and maintain
- SKYDROL grade available

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	15 Nm
BOND STRENGTH	
EN 13892-8	> 2.5 N/mm²
WEAR RESISTANCE	
EN 13892-5	Abrasion quantity <0.5cm²
COMPRESSIVE STRENGTH	
EN 13892-2	55 N/mm²
SURFACE HARDNESS	
EN 13892-6	>400 N/mm²





Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	13 Nm (LXP) 11 Nm (LXP HD)
ELONGATION AT BREAK	
BS 6319	60% (LXP) 30% (LXP HD)
WEAR RESISTANCE	
EN ISO 5470-1 Taber Abrader (H22 wheels, 1000 cycles, 1 kg load)	Weight loss <100mg (LXP)
EN 13892-5	Abrasion quantity <1cm ² (LXP HD)
FLEXURAL STRENGTH	
EN 13892-2	>15 N/mm ²

Flowshield LXP/LXP HD
(1.5 – 3 mm)

Solvent free, flexible polyurethane toppings typically applied in manufacturing, warehousing and packaging environments.

Flowshield LXP and its heavy duty counterpart deliver superior resistance to traffic and chemicals.

-  Resistant to chemicals, sugars and acids
-  Easy-to-clean for low maintenance
-  Flexible application on various substrates
-  Optional anti-slip profile available

Standard Industrial Colours

		
Red 301	Grey 704	Green 602
		
Cream 103	Blue 502	Yellow 104

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

System: Peran STB Classic

Standard Colours





		
Goosewing Grey 222	Beige 326	Mid Grey 280
		
Forest Green 754	Dark Grey 281	Tile Red 637

The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

Peran STB (2–5 mm)

Comprising colour stable quartz beads in a clear resin binder, Peran STB delivers an attractive, slip resistant and durable floor finish.

The hard wearing topping is typically applied in wet and dry processing areas where the floor is subject to heavy traffic and chemical spillage.

-  Attractive, decorative finish
-  Impressive durability
-  Scratch, impact and chemical resistance
-  Superior slip resistance

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	C _{FL} - s1
BOND STRENGTH	
EN 13892-8	> 1.5 N/mm ² *
COMPRESSIVE STRENGTH	
EN 6319	>40 N/mm ²
FLEXURAL STRENGTH	
EN 6319	15 N/mm ²
TENSILE STRENGTH	
EN 6319	10 N/mm ²
WATER PERMEABILITY	
Karsten Test	Nil (Impermeable)

*Assumes concrete compressive strength is greater than 25 N/mm²



System: Flowshield LXP

Standard Industrial Colours



The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



System: Flowfast Quartz

Technical Profile

SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	20 Nm (HF), 21 Nm (RT)
TEMPERATURE RESISTANCE	
Intermittent Spills: Up to 120°C Sustained Heat: -40°C to 105°C	
BOND STRENGTH	
EN 13892-8	> 2.5 N/mm ²
WEAR RESISTANCE	
EN 13892-5	Abrasion quantity <1cm ²
COMPRESSIVE STRENGTH	
EN 13892-2	>50 N/mm ²

Flowfresh HF/RT (6–9 mm)

Hard wearing, low odour, seamless cementitious floor screed with an antimicrobial additive for hygiene sensitive industries.

Flowfresh HF and RT feature a steam-cleanable, finely textured anti-slip profile to ensure safety underfoot, even in wet processing environments.

- Contains Polygiene® for superior hygiene
- Durable to withstand very heavy traffic
- Good alternative to acid resistant tiles
- Superior chemical resistance



Technical Profile


SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	10 Nm
BOND STRENGTH	
EN 1542	> 2.5 N/mm ²
WEAR RESISTANCE	
EN 13892-5	Max wear depth <50µm
COMPRESSIVE STRENGTH	
EN 13892-2	60 N/mm ²
FLEXURAL STRENGTH	
EN 13892-2	20 N/mm ²
TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 70°C	

Flowfast Quartz (4 mm)

Flowfast Quartz is a methyl methacrylate (MMA), hard wearing, decorative resin floor topping.

Ideally suited to dry and wet process areas subject to heavy traffic, the fast-cure system is designed to enable fast track applications, with full system cure times of as little as two hours.

- Rapid installation and cure times
- Decorative colour stable quartz finish
- Impressive resistance to heavy traffic
- In-built anti-slip profile



Standard Colours







The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.

System: Flowfresh HF

Mondéco Earth (7 mm)

A hygienic, epoxy resin terrazzo comprising granite and flint aggregates for superior strength.

Mondéco Earth has been developed to provide a seamless alternative to terrazzo tiles, with a highly chemical resistant finish and impressive durability underfoot.

-  Extremely durable
-  Seamless, hygienic finish
-  Highly chemical resistant
-  Taint-free to sensitive foodstuffs

Technical Profile





SLIP RESISTANCE	
BS 7976-2 (typical values for 4-S rubber slider)	Dry >40
REACTION TO FIRE	
EN 13501-1	B _{FL} - s1
IMPACT RESISTANCE	
EN ISO 6272	16 Nm
EN BS 8204-1	Cat A (<0.5mm)
TEMPERATURE RESISTANCE	
Tolerant of sustained temperatures up to 60°C	
BOND STRENGTH	
EN 13892-8w	> 2.0 N/mm ²
WEAR RESISTANCE	
EN 13892-4	Max wear depth <50µm
BS 8204	Performance Class: Special



Mondéco TZ (7 mm)


Mondéco TZ is a highly temperature resistant polyurethane resin terrazzo with an antimicrobial treatment.

The durable floor covering provides excellent thermal shock resistance to allow for steam cleaning, while offering an abrasion, impact and chemical resistant finish.

-  Contains Polygiene® for superior hygiene
-  Impressive chemical & impact resistance
-  Steam cleanable
-  Excellent thermal shock resistance

System: Mondéco TZ

Standard Mondéco Earth Colours



Standard Mondéco TZ Colours



The applied colours may differ from the examples shown. For a full colour chart and samples, contact your local Flowcrete office.



Flowcrete

World leader in seamless resin flooring solutions and other specialist coatings.

Africa

South Africa	+27 31 701 0017	southafrica@flowcrete.com
--------------	-----------------	---------------------------

Asia Pacific (APAC)

Australia	+61 7 3205 7115	australia@flowcrete.com
Bangladesh	+603 6277 9575	bangladesh@flowcrete.com
Hong Kong	+852 2795 0478	hongkong@flowcrete.com
Indonesia	+62 21 252 3201	indonesia@flowcrete.com
Korea	+60 3 6277 9575	korea@flowcrete.com
Malaysia	+60 3 6277 9575	asia@flowcrete.com
New Zealand	+64 7 541 1221	newzealand@flowcrete.com
Pakistan	+60 3 6277 9575	pakistan@flowcrete.com
Philippines	+63 2 834 6506	philippines@flowcrete.com
Singapore	+65 6848 7166	singapore@flowcrete.com
Taiwan	+60 3 6277 9575	taiwan@flowcrete.com
Thailand	+66 2539 3424	thailand@flowcrete.com
Vietnam	+84 28 6287 0846	vietnam@flowcrete.com

Europe & Middle East (EME)

Bulgaria	+359 898 61 58 31	bulgaria@flowcrete.com
Denmark	+46 435 40 01 10	denmark@flowcrete.com
France	+33 1 60 61 74 42	france@flowcrete.com
Italy	+39 339 4853258	italy@flowcrete.com
Norway	+47 6486 0830	norway@flowcrete.com
Poland	+48 22 879 8907	poland@flowcrete.com
Romania	+40 766 596 991	romania@flowcrete.com
Russia	+7 916 931 3513	russia@flowcrete.com
Spain	+34 937 07 0872	spain@flowcrete.com
Sweden	+46 435 40 01 10	sweden@flowcrete.com
Turkey	+90 212 2946570	turkey@flowcrete.com
UAE	+971 4 347 0460	uae@flowcrete.com
UK	+44 (0) 1270 753 000	uk@flowcrete.com

India

India	+91 44 40176600	india@flowcrete.com
-------	-----------------	---------------------

North America

Canada	+1 877-210-2444	canada@flowcrete.com
Mexico	+55 44 40 94 00	mexico@flowcrete.com
USA	+1 513-943-4225	americas@flowcrete.com