

## Technical Data Sheet

# ME006

## FR AVCL

### Class B Air and Vapour Control Membrane

24-01-2025 / V 8

#### Description

ME006 FR AVCL is a aluminium foil faced glass fibre reinforced, air and vapour control membrane with a reaction to fire Class B-s1, d0 to EN 13501-1. ME006 FR AVCL is used on the interior side of lightweight steel and timber frame constructions to provide an air and vapour tight layer to control the passage of air and moisture.

ME006 FR AVCL is highly suited to construction projects designated as "relevant buildings" as defined in Approved Document B of the Building Regulations for England and Wales.



#### Features and Benefits

- Class B-s1, d0 to EN 13501-1
- Air and vapour tight, can be used to comply with Passiv Haus standards.
- Lightweight material making it quick and easy to install.
- Suitable for use with ME355 FR Sealing Tape to achieve a full interior membrane system.
- High mechanical performance.

#### Packaging

ME006 is supplied in two sizes:

1020 mm x 50 m

1500 mm x 50 m

#### Technical Characteristics

Grammage	EN 1849-2	Nominal 90g/m <sup>2</sup>
Fire Classification	EN 13501-1	Class B-s1, d0
Water Vapour Resistance	EN 1931	> 7,500 MNs/g
Water Vapour Transmission	EN 1931	Sd > 1,500 m
Air Permeability	EN 12114	≤ 0.1 m <sup>3</sup> /m <sup>2</sup> .h@50 Pa
Application Temperature		+5°C to +30°C
Service Temperature		-40°C to +100°C
Storage		Store in shaded dry conditions between +10°C and 25°C, away from direct exposure to weather. Avoid stacking pallets.
Shelf Life		24 months when stored as recommended in original unopened packaging.

#### Application

The instructions below are not intended to be comprehensive and should be read in conjunction with Tremco CPG UK method statements and FR AVCL installation guide available from our website.

## Technical Data Sheet

**ME006**  
**FR AVCL**

ME006 should be installed in accordance with 'BS 5250: 2021 Management of moisture in buildings. Code of practice'. ME006 should be situated on the warm side of the insulation layer. The following assumes the installation of ME006 to an SFS framed wall installed between concrete floor slabs and columns.

Apply ME006 from the roll, allowing a 50 mm overlap at the top and bottom onto the soffit and floor slab. All horizontal and vertical overlaps should be a minimum 100 mm and sealed using ME355 FR Sealing Tape (Alu).

For sealing window and door interfaces, the ME006 should be turned and bonded into the reveal. The complete perimeter interface with the window (or door) should then be sealed using a compatible illbruck tape or membrane ensuring a minimum 20 mm bond to window frame and 50 mm overlap back onto the ME006.

**Guarantee / Warranty**

Tremco CPG UK Ltd products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Ltd written instructions and (b) in any application recommended by Tremco CPG UK Ltd, but which is proved to be defective, will be replaced free of charge. No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

**Health And Safety Precautions**

Safety data sheet must be read and understood before use.

**Technical Service**

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.



Tremco CPG UK Limited  
Coupland Road, Hindley  
Green  
Wigan, WN2 4HT  
United Kingdom  
+44 (0)1942 251400  
hello@tremcocpg.com