Safety Data Sheet according to Regulation (EC) 'No. 2015/830

















SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

FLOWFRESH MULTIPACK SR 1.1 Product Identifier COATING FILLER C

Revision Date:

01/02/2022

Product Name:

Flowfresh SR Coating Filler C

Supersedes Date:

04/02/2021

EAV0-V0U8-C001-5KJ0 **UFI Code:**

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Coatings and paints, thinners, paint removers. Manual activities involving hand contact. Widespread use leading to inclusion into/onto article (indoor). For use by appropriately trained applicators. This component contains an antimicrobial agent. Roller application or brushing. Low energy spreading of coatings. Advised against:

Any other use.

Details of the supplier of the safety data sheet 1.3

> Manufacturer: Flowcrete Polska Sp. z o. o.

UI. Marywilska 34 03-228 Warszawa

Polska

Tel: +48 22 879 8907 Fax: +48 22 879 8918 ehs.uk@flowcrete.com www.flowcrete.com.pl/

Datasheet Produced by:

ehs.uk@flowcrete.com

1.4 Emergency telephone number: CHEMTREC +1 703 5273887 (Outside US)

Giftinformasjonen: +47 22 59 13 00

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin Irritation, category 2

H315

Skin Sensitizer, category 1 Serious Eye Damage, category 1 STOT, single exposure, category 3, RTI H317 H318 H335

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Cement, portland, chemicals

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection/
	face protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or
	doctor/physician.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a
	position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes.
	Remove contact lenses, if present and easy to do so.
	Continue rinsing.

If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

P333+313

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients

Name According to EEC	EINEC NO.	<u>CAS-NO.</u>	<u>70</u>	<u>Classifications</u>

Cement, portland, 266-043-4 65997-15-1 75-100 H315-317-318-335 Eye Dam. 1, Skin Irrit. chemicals 2, Skin Sens. 1, STOT SE 3 RTI

<u>CAS-No.</u> <u>M-Factors</u> <u>REACH Reg No.</u>

65997-15-1 exempt

EINIEG Na

Additional Information: The text for CLP Hazard Statements shown above (if any) is given in Section 16.

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off with soap and plenty of water.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water. Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Wear personal protective equipment. Avoid dust formation. Protect from moisture.

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Wash hands before breaks and at the end of workday. Do not breathe dust. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid moisture.

STORAGE CONDITIONS: Keep tightly closed in a dry and cool place.

7.3 Specific end use(s)

Part of the Flowfresh/Flowcrete Multipack system. Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

NameCAS-No.LTEL ppmSTEL ppmSTEL mg/m3LTEL mg/m3Cement, portland, chemicals65997-15-110 4

Name CAS-No. OEL Note

Cement, portland, chemicals 65997-15-1 Respirable Dust, Total Inhalable

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Effective dust mask.

EYE PROTECTION: Eye wash bottle with pure water. Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Protective gloves. Long sleeved clothing. Remove contaminated clothing and protective equipment

before entering eating areas.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

Chemical Name:

EC No.: CAS-No.:

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required				· •			
Inhalation								
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Gray / white powder

Physical State Solid
Odor odorless

Odor threshold Not determined

pH ca. 12

Melting point / freezing point (°C)

Boiling point/range (°C)

Flash Point, (°C)

Evaporation rate

Not determined

Not determined

Not determined

Upper/lower flammability or explosive

limits

Not determined

Vapour Pressure Not determined
Vapour density Not determined

Relative density ca. 3.0

Solubility in / Miscibility with water insoluble

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Decomposition temperature (°C)

Not determined

Viscosity

Not determined

Explosive properties

Not Applicable

Oxidising properties

Not Applicable

9.2 Other information

VOC Content g/l: <20
Specific Gravity (g/cm3) 0.120

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Avoid moisture.

10.5 Incompatible materials

Do not store near acids.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No Information Inhalation LC50: No Information

Irritation: No information available.

Cement and hydrated lime powder, especially in a water mix, may cause irritant contact

Date Printed: 01/02/2022

dermatitis and/or burns.

Sensitization: Prolonged or repeated skin contact may result in allergic eczema.

No information available. Repeated dose toxicity:

No information available. Carcinogenicity:

Mutagenicity: No information available.

No information available. Toxicity for reproduction:

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

No information available. Aspiration hazard:

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

Additional Information:

Corrosivity:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Social Dialogue on Respirable Crystalline Silica and Good Practices Guide A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

Literature References

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk... (SCOEL SUM Doc 94-final, June 2003).

So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required.

`Health & Safety Executive (specific for UK):

Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis". In addition to silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

SECTION 12: Ecological Information

12.1 Toxicity:

Date Printed: 01/02/2022

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information

No information

No information

12.2 Persistence and degradability: Mostly nonbiodegradable. The hydrated lime will react with atmospheric and

dissolved carbon dioxide to form calcium carbonate (e.g. chalk).

12.3 Bioaccumulative potential: The product is not volatile and insoluble in water, will accumulate in the ground.

12.4 Mobility in soil:No information

12.5 Results of PBT and vPvB The

assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: The addition of cement and hydrated lime to water will raise pH and may therefore be

toxic to aquatic life in some circumstances.

CAS-No. Name According to EEC EC50 48hr IC50 72hr LC50 96hr

65997-15-1 Cement, portland, chemicals No information No information

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code: 101304 **Packaging Waste Code:** 150101

SECTION 14: Transport Information

14.1 UN number Not applicable

14.2 UN proper shipping name Not regulated for transport according to ADR/RID, IMDG, and IATA

regulations.

Technical name Not applicable Not applicable 14.3 Transport hazard class(es) Not applicable Subsidiary shipping hazard 14.4 Packing group Not applicable 14.5 Environmental hazards Not applicable 14.6 Special precautions for user Not applicable EmS-No.: Not applicable 14.7 Transport in bulk according to Annex II of Not applicable MARPOL 73/78 and the IBC code

SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:

Denmark Product Registration Number:

Not available

Danish MAL Code:

Not available

Not available

Sweden Product Registration Number:

Not available

Norway Product Registration Number:

Not available

Germany WGK Class:

Not available

Directive 2004/42/CE:

<20

Covered by Directive 2012/18/EC (Seveso III):

Not applicable

Restrictions to product or to substances according

to Annex XVII, Regulation (CE) 1907/2006:

Not applicable

Annex XIV - Authorisation List:

CAS-No.

Date Printed: 01/02/2022

Name According to EEC

Not Applicable

SVHC - Substances of very high concern (Candidate List):

CAS-No. Name According to EEC

Not Applicable

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

Reasons for revision

Substance and/or Product Properties Changed in Section(s):

01 - Identification

 ${\tt 08}$ - Exposure Controls/Personal Protection

15 - Regulatory Information

Composition Information Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter
TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.