

Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: illbruck AT160

· MSDS code: T-I-AT160

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Priming

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck GmbH

Zweigniederlassung Traunreut

Traunring 65, D - 83301 Traunreut

Tel: +49 (0) 8669 34100, Fax: +49 (0) 8669 9784

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Contains: propan-2-ol

(Contd. on page 2)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 1)

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with non-hazardous additions.

Dangerous components:		
CAS: 67-63-0	propan-2-ol	75-<100%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
Reg.nr.: 01-2119457558-25-xxxx	•	

- · SVHC -
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove from the skin using a cloth or paper. Then clean with water and soap.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing:

Rinse out mouth and then drink plenty of water.

(Contd. on page 3)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 2)

Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Store in cool, dry place in tightly closed receptacles.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

(Contd. on page 4)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 3)

Protect against electrostatic charges.

- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

CAS: 67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm Long-term value: 999 mg/m³, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Filter A

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

Solvent resistant gloves

(Contd. on page 5)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 4)

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information	n on	hasic	nhysical	and	chemical	nronerties
J. I IIIIOIIIIauc		vasii.	ULIVAILA	anu	CHEHICA	. Di Obei lies

Fluid

· General Information

· Appearance: Form:

Colour:
Odour:
Odour threshold:
Colourless
Alcohol-like
Not determined.

PH-value:
Not determined.

• Melting point/freezing point: -89.5 °C

· Initial boiling point and boiling range: 82 °C

· Flash point: 13 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 425 °C

Decomposition temperature: Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

(Contd. on page 6)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

	(Contd. of page 5	;)
· Explosion limits:]
Lower:	2 Vol %	
Upper:	12 Vol %	
· Vapour pressure at 20 °C:	43 hPa	
· Density at 20 °C:	0.8 g/cm³	
· Solubility in / Miscibility with		1
water:	Immiscible / difficult to mix.	
· Partition coefficient: n-octanol/water	: Not determined.]
· Solvent content:		1
VOC (EU)	99.3 %	
	794.1 g/l	
VOC (EC)	99.30 %	
9.2 Other information	No further relevant information available.	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: None if stored according to specifications.

SECTION 11: Toxicological information

- 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	LD/LC50 values relevant for classification:		
CAS: 67-6	3-0 propa	n-2-ol	
Oral	LD50	5,045 mg/kg (rat)	
Dermal	LD50	12,800 mg/kg (rabbit)	
Inhalative	LC50/4 h	30 mg/L (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: Repeated exposure may cause skin dryness or cracking.

(Contd. on page 7)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 6)

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic to	· Aquatic toxicity:		
CAS: 67-63	3-0 propan-2-ol		
LC50/96 h	9,640 mg/L (pimephales promelas)		
LC50/48 h	>100 mg/L (leuciscus idus)		
EC50/48 h	13,299 mg/L (daphnia magna)		
EC50/72 h	>1,000 mg/L (desmodesmus subspicatus)		

- 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europea	n waste catalogue
08 04 99	wastes not otherwise specified
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 8)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 7)

- Uncleaned packaging:
- Recommendation:

Empty packages totally (without drops or grains, cleaned with a spatula). Under observation of the relevant local respectively national regulations re-use or recycling is preferred.

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information
--

· 14.1 UN-Number · ADR, IMDG, IATA	UN1219
· 14.2 UN proper shipping name · ADR	1219 ISOPROPANOL (ISOPROPYL ALCOHOL) 1219 ISOPROPANOL, Lösung
· IMDG, IATA	ISOPROPANOL (ISOPROPYL ALCOHOL)

· 14.3 Transport hazard class(es)

Marpol and the IBC Code

· ADR



· Class	3 (F1) Flammable liquids.
· Label	3

· IMDG, IATA



· Class	3 Flammable liquids.
· Label	3
14.4 Packing group	
· ADR, IMDG, IATA	II
14.5 Environmental hazards:	
· Marine pollutant:	No
14.6 Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E,S-D
· Stowage Category	В
· 14.7 Transport in bulk according to Ann	ex II of

Not applicable.

(Contd. on page 9)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 8)

Transport/Additional information:

· ADR

· Limited quantities (LQ)

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

· Transport category 2 · Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN "Model Regulation": UN 1219 ISOPROPANOL (ISOPROPYL ALCOHOL),

3, II

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) 2001/118/EC as regards the list of wastes

2008/98/EC on waste

- · Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

(Contd. on page 10)



Printing date 13.09.2019 Version number 5 Revision: 13.09.2019

Trade name: illbruck AT160

(Contd. of page 9)

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

GB