

NUDURA 12"
(305mm) STANDARD
FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

V-CLIP WALL PANEL
ANCHOR

FORM PANELS c/w
INSERT WEBS—CUT TO
SUIT FLOOR
CONNECTION—ADDITIONAL
FORM SUPPORT AS
REQUIRED

THROUGH WALL
FLASHING AS PER CODE
OR AS SPECIFIED

NUDURA 12" (305mm)
SITE ASSEMBLED BRICK
LEDGE FORM UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE
COAT

NUDURA WATERPROOF
MEMBRANE

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

FINISHED CONCRETE
TOPPING

HOLLOW CORE
PRECAST SLAB

FINISH AS SPECIFIED

DOWELS FIELD BENT
INTO SHEAR KEY JOINT
BETWEEN PANELS AS
SPECIFIED

MASONITE BEARING
PAD

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm)
BRICK LEDGE FORM UNIT
HOLLOW CORE PRECAST SLAB
BEARING WALL DETAIL
BRICK VENEER FINISH

REV. NO.
003 KS

REV. DATE:
FEB 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

D12A02

SCALE:
1 : 8