## **DECLARATION OF PERFORMANCE**

According to ANNEX III of the regulation (EU) N° 305/2011



**No.** SC902 – 20210105 P1/2

1. Unique identification code of the product-type: Nullifire SC902

2. Intended use/es: Reactive coating for the fire protection of structural steel members to obtain

load-bearing capacity for a specific period of time.

3. Manufacturer: TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT

5. System/s of AVCP: System 1

**6b. European Assessment Document:** EAD 350402-00-1106

**European Technical Assessment:** Document ETA 20/1216

**Technical Assessment Body:** Element Materials Technology Rotterdam B.V. Element

Notified Body: Materials Technology Rotterdam B.V. 2812

## 7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification				
Safety in Case of Fire						
Reaction to fire	Class B-s2, d0 (without topcoat)	EN13501-1				
	Class C-s2, d0 (with topcoat)					
Resistance to fire	Up to R120 Resistance to fire performance & field of	EN13501-2				
	application in accordance with EN13051-2 See ETA	EN13381-8: 2013				
	20/1216 clause 3.2 - Annex A					
Hygiene, Health and Environment						
Dangerous Substances	Does not contain dangerous substances					
	See ETA 20/1216 Clause 3.3					
Energy, Economy and Heat Retention						
Service & Durability	Compatible with generic primer types:					
	2 pack epoxy primer					
	And directly to substrates:					
	Blasted steel SA2.5, Galvanised steel, Brush cleaned					
	rusty steel	EAD 350402-00-1106				
	Conditions Z <sub>1</sub> , Z <sub>2</sub> , Y (with or without topcoat)					
	External Condition X (with approved topcoat)					
	Compatible with a range of topcoats. See ETA					
	20/1216 clause 3.4					

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

(Illa)

Signed for	and on	behalf o	f the	manu	facturer	by:
------------	--------	----------	-------	------	----------	-----

M. Liptrot, Operations Director At Wigan on 05 January 2021

## Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

## **DECLARATION OF PERFORMANCE**

According to ANNEX III of the regulation (EU) N° 305/2011



**No.** SC902 – 20210105

P2/2

C€					
TREMCO CPG UK Limited,					
Coupland Road, Hindley (	Green, Wigan. WN2 4HT UK				
, , , , ,	21				
2812-C	PR-GA5018				
	- 20210105				
	re.com/SC902/				
EN 133	381-8 2013				
ETA	20/1216				
EAD 350402-00-1106					
Reactive coating for the fire protection of structural steel members to obtain load-bearing capacity up to R120 for design temperatures in the range 350°C to 750°C.					
Essential Characteristic	Performance				
Safety in Case of Fire					
Reaction to fire	Class B-s2, d0 (without topcoat)				
Reaction to lire	Class C-s2, d0 (with topcoat)				
	Up to R120 Resistance to fire performance &				
Resistance to fire	field of application in accordance with				
Resistance to fire	EN13051-2 See ETA 20/1216 clause 3.2 -				
	Annex A				
Hygiene, Health and Environment					
Dangaraus Substances	Does not contain dangerous substances				
Dangerous Substances	See ETA 20/1216 Clause 3.3				
Energy, Economy and Heat Retention					
	Compatible with generic primer types:				
	2 pack epoxy primer				
	And directly to substrates:				
	Blasted steel SA2.5				
Sarvice & Durability	Galvanised steel				
Service & Durability	Brush cleaned rusty steel				
	Conditions Z <sub>1</sub> , Z <sub>2</sub> , Y (with/without topcoat)				
	External Condition X (with approved topcoat)				
	Compatible with a range of topcoats. See				
	ETA 20/1216 clause 3.4				
Other	NPD				