

Safety Data Sheet according to Regulation (EC) No. 2015/830

SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	FLOWFRESH MULTIPACK RT FILLER C	Revision Date:	19/01/2017
	Product Name:	Flowfresh Multipack RT Filler C	Supercedes Date:	28/05/2015

1.2 Relevant identified uses of the substance or mixture and uses advised against
Coatings and paints, thinners, paint removers. Hand-mixing with intimate contact and only PPE available. Wide dispersive indoor use resulting in inclusion into or onto a matrix. For use by appropriately trained applicators. This component contains an antimicrobial agent. Roller application or brushing. Low energy spreading of coatings. Advised against: Any other use.

1.3 Details of the supplier of the safety data sheet

	Supplier:	Flowcrete UK Ltd. The Flooring Technology Centre Booth Lane Moston, Sandbach, Cheshire. UK CW11 3QF
		Tel: +44 (0)1270 753000 Fax: +44 (0)1270 753333 ehs.uk@flowcrete.com http://www.flowcrete.co.uk
	Datasheet Produced by:	ehs.uk@flowcrete.com
1.4	Emergency telephone number:	CHEMTREC +001 703 5273887 (Outside US) CHEMTREC 1-800-424-9300 (Inside US)

SECTION 2: Hazard Identification

2.1 Classification of the substance or mixture

Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

HAZARD STATEMENTS

Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Serious Eye Damage, category 1	H318
STOT, single exposure, category 3, RTI	H335

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

Calcium dihydroxide, Cement, portland, chemicals

HAZARD STATEMENTS

Skin Irritation, category 2 Skin Sensitizer, category 1 Serious Eye Damage, category 1 STOT, single exposure, category 3, RTI PRECAUTION PHRASES	H315 H317 H318 H335	Causes skin irritation. May cause an allergic skin reaction. Causes serious eye damage. May cause respiratory irritation.
	P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

SECTION 3: Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.	EINEC No.	Name According to EEC	<u>%</u>	
65997-15-1	266-043-4	Cement, portland, chemicals	10-25	
1305-62-0	215-137-3 Calcium dihydroxide		2.5-10	
CAS-No.	REACH Reg No	<u>CLP Symbols</u>	CLP Hazard Statements	M-Factors
65997-15-1		GHS05-GHS07	H315-317-318-335	
1305-62-0	01-2119475151-	45 GHS05-GHS07	H315-318-335	
Additional Ir	formation:	The text for CLP Hazard S	Statements shown above (if any) is given in Section 16.	

SECTION 4: First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off with soap and plenty of water.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

SECTION 5: Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture No Information

5.3 Advice for firefighters

Not combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Pick up and transfer to properly labelled containers. No special environmental precautions required. After cleaning, flush away traces with water. Refer to protective measures listed in sections 7 and 8.

6.4 Reference to other sections

FURTHER INSTRUCTIONS: Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling

Wear personal protective equipment. Avoid dust formation. Protect from moisture.

7.2

Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid moisture. **STORAGE CONDITIONS:** Keep tightly closed in a dry and cool place.

7.3 Specific end use(s)

Part of the Flowfresh/Flowcrete Multipack system. Component of a resin flooring product. The mixing and application to be in accordance with the technical data sheets.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (UK WELS)

<u>Name</u>	CAS-No.	LTEL ppm	STEL ppm	<u>STEL mg/m3</u>	LTEL mg/m3
Cement, portland, chemicals	65997-15-1				4 10
Calcium dihydroxide	1305-62-0				5
Name	CAS-No.	OEL Note			
Hame	<u>040-110.</u>				
Cement, portland, chemicals	65997-15-1	Respirable Dust,			
		Total Inhalable			
Calcium dihydroxide	1305-62-0				

FURTHER ADVICE: Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Effective dust mask.

EYE PROTECTION: Eye wash bottle with pure water. Safety glasses with side-shields conforming to EN166. **HAND PROTECTION:** Protective gloves. Long sleeved clothing. Remove contaminated clothing and protective equipment before entering eating areas.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Ensure adequate ventilation, especially in confined areas.

Chemical Name:

EC No.: CAS-No.:

DNELs - Derived no effect level

	Workers			Consumers				
Route of	Acute effect	Acute effects	Chronic	Chronic effects	Acute effect	Acute effects	Chronic	Chronic effects
Exposure	local	systemic	effects local	systemic	local	systemic	effects local	systemic
Oral	Not required							
Inhalation					_			
Dermal								

PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties Appearance: granules/powder mix

· + F	granalee period
Physical State	Solid
Odor	odorless
Odor threshold	Not determined
рН	ca. 11.5
Melting point / freezing point (°C)	Not determined
Boiling point/range (°C)	N.D N.D.
Flash Point, (°C)	Not Applicable
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	Not determined
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	ca. 2.5
Solubility in / Miscibility with water	slight
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	Not determined
Explosive properties	Not Applicable
Oxidising properties	

Not Applicable

9.2 Other information

VOC Content g/l:

<20

This is a calculated maximum VOC content for the mixed ready to use product (to Directive 2004/42/EC).

SECTION 10: Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

- **10.3 Possibility of hazardous reactions** Hazardous polymerisation does not occur.
- **10.4 Conditions to avoid** Avoid moisture.

10.5 Incompatible materials Do not store near acids.

10.6 Hazardous decomposition products No hazardous decomposition products are known.

SECTION 11: Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:		
Oral LD50:	No Information	
Inhalation LC50:	No Information	
Irritation:	No information available.	
Corrosivity:	Cement and hydrated lime powder, especially in a water mix, may cause irritant contact dermatitis and/or burns.	
Sensitization:	Prolonged or repeated skin contact may result in allergic eczema.	
Repeated dose toxicity:	No information available.	
Carcinogenicity:	No information available.	
Mutagenicity:	No information available.	
Toxicity for reproduction:	No information available.	
STOT-single exposure:	No information available.	
STOT-repeated exposure:	No information available.	
Aspiration hazard:	No information available.	

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.

Data on individual components are tabulated below:

CAS-No.	Name According to EEC	Oral LD50	Dermal LD50	Vapor LC50
1305-62-0	Calcium dihydroxide	7340 mg/kg (rat)	>2500 mg/kg (rabbit)	

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. This product may contain Quartz (silicon dioxide), which is listed by IARC as a known carcinogenic to humans (Group 1). This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities. Social Dialogue on Respirable Crystalline Silica and Good Practices Guide A multi-sectoral social dialogue agreement on Workers Health Protection through the Good Handling and Use of Crystalline Silica and Products Containing it was signed on 25 April 2006. This autonomous agreement, which receives the European Commission's financial support, is based on a Good Practices Guide. The requirements of the Agreement came into force on 25 October 2006. The Agreement was published in the Official Journal of the European Union (2006/C 279/02). The text of the Agreement and its annexes, including the Good Practices Guide, are available from http://www.nepsi.eu and provide useful information and guidance for the handling of products containing respirable crystalline silica. Literature references are available on request from EUROSIL, the European Association of Industrial Silica Producers.

Literature References

Prolonged and/or massive exposure to respirable crystalline silica-containing dust may cause silicosis, a nodular pulmonary fibrosis caused by deposition in the lungs of fine respirable particles of crystalline silica.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However it pointed out that not all industrial circumstances, nor all crystalline silica types, were to be incriminated. (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.)

In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003).

So there is a body of evidence supporting the fact that increased cancer risk would be limited to people already suffering from silicosis. Worker protection against silicosis should be assured by respecting the existing regulatory occupational exposure limits and implementing additional risk management measures where required.

'Health & Safety Executive (specific for UK):

Detailed reviews of the scientific evidence on the health effects of crystalline silica have been published by HSE (Health and Safety Executive, UK) in the Hazard Assessment Documents EH75/4 (2002) and EH75/5 (2003). The HSE points out on its website that "Workers exposed to fine dust containing quartz are at risk of developing a chronic and possibly severely disabling lung disease known as "silicosis". In addition to silicosis, there is now evidence that heavy and prolonged workplace exposure to dust containing crystalline silica can lead to an increased risk of lung cancer. The evidence suggests that an increased risk of lung cancer is likely to occur only in those workers who have developed silicosis.

SECTION 12: Ecological Information

12.1	Toxicity:	
	EC50 48hr (Daphnia):	No information
	IC50 72hr (Algae):	No information
	LC50 96hr (fish):	No information
12.2	Persistence and degradability:	Mostly nonbiodegradable. The hydrated lime will react with atmospheric and dissolved carbon dioxide to form calcium carbonate (e.g. chalk).
12.3	Bioaccumulative potential:	The product is not volatile and insoluble in water, will accumulate in the ground.
12.4	Mobility in soil:	No information
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects:		The addition of cement and hydrated lime to water will raise pH and may therefore be toxic to aquatic life in some circumstances.		
CAS-No.	Name According to EEC	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
65997-15-1	Cement, portland, chemicals	No information	No information	
1305-62-0	Calcium dihydroxide	49.1 mg/l	No information	50.6 mg/l

SECTION 13: Disposal Considerations

13.1 WASTE TREATMENT METHODS: If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

European Waste Code:	101304
Packaging Waste Code:	150101

l.1	UN number	Not applicable
1.2	UN proper shipping name	Not regulated for transport according to ADR/RID, IMDG, and IATA regulations.
	Technical name	Not applicable
4.3	Transport hazard class(es)	Not applicable
	Subsidiary shipping hazard	Not applicable
4.4	Packing group	Not applicable
4.5	Environmental hazards	Not applicable
4.6	Special precautions for user	Not applicable
	EmS-No.:	Not applicable
4.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

SECTION 15: Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

National Regulations:		
Denmark Product Registration Number:	Not available	
Danish MAL Code:	Not available	
Danish MAL Code - Mixture:	Not available	
Sweden Product Registration Number:	Not available	
Norway Product Registration Number:	Not available	
WGK Class:	1	

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other Information

Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 08 - Exposure Controls/Personal Protection Statement(s) Changed

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes.

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation EC European Commission	
EU European Union	
US United States	
CAS Chemical Abstract Service	
EINECS European Inventory of Existing Chemical Substances	
REACH Registration, Evaluation, Authorization of Chemicals F	Regulation
GHS Globally Harmonized System of Classification and Label	ling of Chemicals
LTEL Long term exposure limit	
STEL Short term exposure limit	
OEL Occupational exposure limit	
ppm Parts per million	
mg/m3 Milligrams per cubic meter	
TLV Threshold Limit Value	
ACGIH American Conference of Governmental Industrial Hygieni	ists
OSHA Occupational Safety & Health Administration	
PEL Permissible Exposure Limits	
VOC Volatile organic compounds	
g/l Grams per liter	
mg/kg Milligrams per kilogram	
N/A Not applicable	
LD50 Lethal dose at 50%	
LC50 Lethal concentration at 50%	
EC50 Half maximal effective concentration	
IC50 Half maximal inhibitory concentration	
PBT Persistent bioaccumulative toxic chemical	
vPvB Very persistent and very bioaccumulative	
EEC European Economic Community	

Date Printed: 19/01/2017

ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
modified by the Pr	cotocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.