



1213



2538

Tremco CPG Netherlands B.V  
Vlietskade 1032  
NL-4241 Arkel

14

22

FS500-20140426  
illbruck.com/dop/FS500

**EN 15651-1, -2: 2012**

Non-structural sealant for joints for interior and exterior application  
(intended for use in cold climates)

Non-structural sealant for sealing glazing applications (intended for  
use in cold climates)

- Type F-EXT-INT-CC 25LM, Type G-CC 25LM

- Conditioning: Method A

- Substrate: Aluminium

**REACTION TO FIRE**

Class E

**RELEASE OF CHEMICALS DANGEROUS TO  
THE ENVIRONMENT AND HEALTH**

NPD

**WATER TIGHTNESS AND AIR TIGHTNESS**

- Resistance to flow

 $\leq 3\text{mm}$ 

- Loss of volume

 $\leq 10\%$ 

- adhesion/cohesion properties at maintained  
extension after water immersion (23°C)

NF

- elastic recovery

 $\geq 60\%$ 

- adhesion/cohesion properties after exposure to  
heat, water and artificial light

NF

- adhesion/cohesion properties (-30°C)

 $\leq 0,9\text{ N/mm}^2$ 

- adhesion/cohesion properties at maintained  
extension (-30°C)

NF

**DURABILITY**

Passed

NF = no failure according to ISO 11600

NPD = No performance declared