DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011



No. FS703 - 20210105

1. Unique identification code of the product-type: Nullifire FS703

2. Intended use/es: A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.

3. Manufacturer: TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, UK. WN2 4HT

5. System/s of AVCP: System 1

6. European Assessment Document: EAD 350141-00-1106 Linear Joint and Gap Seals

European Technical Assessment: ETA 20/1215

Technical Assessment Body: Warrington Certification Limited 1121, Warrington

Notified Body: Certification Limited

7. Declared performance/s:

Essential Characteristic	Performance	Harmonised Technical Specification	
Safety in Case of Fire			
Reaction to fire	Class E	EN13501-1	
Resistance to fire	Up to El240 Resistance to fire performance, in	EN13501-2	
	accordance with EN13501-2 See ETA 20/1215	EN1366-4: 2006	
	Clause 3.1.2 - Annex C		
Hygiene, Health and Environment			
Dangerous Substances	Does not contain dangerous substances See		
	ETA 20/1215 Clause 3.2.2		
Air Permeability	Test Pressure Differential 600 Pa See	EN 1026	
	ETA 20/1215 Clause 3.2.1		
Energy, Economy and Heat Retention			
Service & Durability	X intended for use in conditions exposed to	EAD 350141-00-1106 Linear Joint and Gap Seals	
	weathering in accordance with EOTA Technical		
	Report TR024 – Edition November 2006		
	Clause 3.3.1		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Operations Director

At Wigan on 05 January 2021

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

1/2

DECLARATION OF PERFORMANCE



No. FS703 – 20210105

C€			
TREMCO CPG UK Limited,			
Coupland Road, Hindley Green, Wigan. WN2 4HT UK			
21			
2812-CPR-JA5052			
FS703 – 20210105			

EN 1366-4: 2006 ETA 20/1215

www.nullifire.com/FS703/

EAD 350141-00-1106 Linear Joint and Gap Seals

A fire resistant, one part silicone based sealant used to form linear gap seals where gaps are present in wall and floor constructions.

Essential Characteristic	Performance		
Safety in Case of Fire			
Reaction to fire	Class E		
	Up to El240 Resistance to fire		
Resistance to fire	performance, in accordance with		
Resistance to me	EN13501-2 See ETA 20/1215 Clause 3.1.2		
	- Annex C		
Hygiene, Health and Environment			
Dangaraya Subatanasa	Does not contain dangerous substances		
Dangerous Substances	See ETA 20/1215 Clause 3.2.2		
Air Permeability	Test Pressure Differential 600 Pa		
	See ETA 20/1215 Clause 3.2.1		
Energy, Economy and Heat Retention			
	X intended for use in conditions exposed to		
	weathering in accordance with EOTA		
Service & Durability	Technical Report TR024 – Edition		
	November 2006		
	Clause 3.3.1		