

Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- Trade name: illbruck CY340 Activator
- · MSDS code: A-I-CY340ACT
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Activator
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

tremco illbruck Productie B.V. Vlietskade 1032, 4241 WC Arkel

T: +31 (0) 183568000, F: +31 (0) 183568100

msds@tremco-illbruck.com

#### · Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

## 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229 Extremely	flammable aerosol.	Pressurised	container: May	burst if
	heated.				

Acute Tox. 4 H332 Harmful if inhaled.
Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

Aguatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

#### · 2.2 Label elements

## Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS09

(Contd. on page 2)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 1)

## · Signal word Danger

## · Contains:

Naphtha (petroleum), hydrotreated light

N,N-dimethyl-p-toluidine

## · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H332 Harmful if inhaled. H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

## · Precautionary statements

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smokina.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P261 Avoid breathing vapours/spray.
P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P312 Call a doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

## **SECTION 3: Composition/information on ingredients**

#### · 3.2 Mixtures

· Description: Active substance with propellant

· Dangerous components:		
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220	30-<50%
CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light Flam. Liq. 2, H225; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H336	30-<50%
CAS: 106-97-8 EINECS: 203-448-7 Reg.nr.: 01-2119474691-32-xxxx	butane, pure Flam. Gas 1, H220	10-<20%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220	1-<5%

(Contd. on page 3)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

CAS: 99-97-8
EINECS: 202-805-4

Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H312

Acute Tox. 3, H373; Aquatic Chronic 3, H412

· SVHC -

· Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- · General information:

Take affected persons out of danger area and lay down.

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

## · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Headache

Dizziness

Nausea

Coughing

Irritant to skin and mucous membranes.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Fumes can combine with air to form an explosive mixture.

- 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

(Contd. on page 4)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 3)

· Additional information Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

## · 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep away from ignition sources.

- · **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Pick up mechanically.

or

Absorb liquid components with liquid-binding material.

Dispose of contaminated material as waste according to Section 13.

Clean the affected area carefully; suitable cleaners are:

Warm water

## · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **SECTION 7: Handling and storage**

## · 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Do not breathe vapour.

Avoid contact with the eyes and skin.

## · Information about fire - and explosion protection:

Extremely flammable.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

Do not spray onto a naked flame or any incandescent material.

## · 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

## · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

## Information about storage in one common storage facility:

Protect from heat and direct sunlight.

Store away from foodstuffs.

## Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

(Contd. on page 5)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

## **SECTION 8: Exposure controls/personal protection**

## · 8.1 Control parameters

## Ingredients with limit values that require monitoring at the workplace:

**CAS: 106-97-8 butane, pure** 

WEL Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

#### · Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

## · 8.2 Exposure controls

## · Personal protective equipment:

## General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Self-contained respiratory protective device.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

## Material of gloves

**PVC** gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

## **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol Colour: Colourless · Odour: Characteristic Melting point/freezing point: Undetermined. · Initial boiling point and boiling range: -44.5 °C

-40 °C · Flash point:

450 - 580 °C · Ignition temperature:

· Explosive properties: Product is not explosive. However, formation of explosive air/

vapour mixtures are possible.

· Explosion limits:

Lower: 1.8 Vol % Upper: 9.5 Vol %

Density at 20 °C: 0.79 g/cm<sup>3</sup>

· Solubility in / Miscibility with

Insoluble. water:

· Viscosity:

Dynamic at 25 °C: < 1 cps

· 9.2 Other information No further relevant information available.

## **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

(Contd. on page 7)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 6)

- 10.3 Possibility of hazardous reactions Reacts with oxidising agents.
- · 10.4 Conditions to avoid

Keep away from heat.

Keep away from sources of ignition - No smoking.

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

## **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- Acute toxicity

Harmful if inhaled.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
CAS: 6474	CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>5 mg/L (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Irritating effect.

Repeated exposure may cause skin dryness or cracking.

Causes skin irritation.

- · Serious eye damage/irritation Direct contact may cause temporary redness and discomfort.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Harmful if inhaled.

Irritating to respiratory system.

- CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause drowsiness or dizziness.

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

- GI

(Contd. on page 8)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 7)

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:

CAS: 64742-49-0 Naphtha (petroleum), hydrotreated light

EC50/48 h 36 mg/L (fish)

EC50/72 h 30 mg/L (pseudokirchneriella subcapit.)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

- · Additional ecological information:
- · General notes:

Toxic for aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

· European	· European waste catalogue	
14 06 03*	14 06 03* other solvents and solvent mixtures	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP14	Ecotoxic	

- Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

(Contd. on page 9)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

Non contaminated packagings may be recycled.

(Contd. of page 8)

## **SECTION 14: Transport information**

· 14.1 UN-Number	
· ADR. IMDG. IATA	UN1950

· 14.2 UN proper shipping name

4441111111

· ADR 1950 AEROSOLS, ENVIRONMENTALLY

HAZARDOUS 1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR





· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 · Label 2.1

.abei

· 14.4 Packing group

· ADR, IMDG, IATA Void

· 14.5 Environmental hazards:

· Marine pollutant: No

· Special marking (ADR): Symbol (fish and tree)

• 14.6 Special precautions for user Warning: Gases.

Hazard identification number (Kemler code):

EMS Number: F-D.S-U

• Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS:

Category C, Clear of living quarters.

Segregation Code SG69 For AEROSOLS with a maximum capacity of 1

litre:

(Contd. on page 10)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

	(Contd. of page
	• • • • • • • • • • • • • • • • • • • •
	Segregation as for class 9. Stow "separated from
	class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of clas
	2.
14.7 Transport in bulk according to A	nnex II of
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
,	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
Remarks:	- Special provisions: 190, 327, 344, 625 (3.3)
	- Special provisions for carriage: V14 (7.2.4); CV
	CV12 (7.5.11); S2 (8.5)
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0
. ,	Not permitted as Excepted Quantity
Remarks:	- Special provisions: 63, 190, 277, 327, 344, 959 (3.3
IATA	
Remarks:	- Special provisions: A145, A167, A802 (4.4)
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1, ENVIRONMENTALI
-	HAZARDOUS

## **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)
Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)
2001/118/EC as regards the list of wastes

2008/98/EC on waste

· REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

(Contd. on page 11)



Printing date 27.04.2020 Version number 5 Revision: 27.04.2020

Trade name: illbruck CY340 Activator

(Contd. of page 10)

- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

#### Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases - Category 1

Aerosol 1: Aerosols - Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity - oral - Category 3

Acute Tox. 4: Acute toxicity - inhalation - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.