# Technical Data Sheet

# **RW270** TREMSTIK CLEANER

# KEY BENEFITS SUMMARY

- Effective cleaner of PU products
- Helps to maintain braided hoses and applicator guns
- Compatible with all TremStik products

# PRODUCT INFORMATION

# Description

RW270 is an acetone cleaner for use with TremStik braided canister hoses and applicator guns.

#### **Usage/Purpose**

Developed specifically for use as a cleaner to flush and clear braided hoses and canister spray guns following application of TremStik PU Adhesive or TremStik Spray Primer.

Colour Clear

### Packaging

500ml aerosol

#### **Availability**

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details).

#### **Protective Equipment**

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

#### **Application Instructions**

- Shake canister well before use.
- When the spray primer / PU adhesive has been used and the hose is ready to be cleaned, turn valve on canister into off position, spray out remaining primer / PU adhesive left in the hose, and disconnect the braided hose and applicator gun from the canister.
- Attach and secure braided hose tightly to a canister of RW270 TremStik Cleaner, making sure the hose-valve connections are tight. Open valve on canister slowly and fully, check for leaks during this process. Unlock trigger on the applicator gun to start spraying.
- Spray out until liquid is clear, this indicates that the hose and gun is clean.
- Do not close valve until ready to connect to a new canister.

#### **Health & Safety Precautions**

Safety data sheet must be read and

**TREMCO** 

Lasting Performance

#### **Availability**

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details), or via local and national distributors.

#### **Technical Service**

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

#### **Guarantee/Warranty**

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and and deemed accurate at the time of issue.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



Tremco CPG UK Limited Coupland Road, Hindley Green Wigan WN2 4HT +44 (0) 1942 251400 roofing.uk@tremcocpg.com





TECHNICAL DATA	
PROPERTY	RESULT
Composition	Solvent cleaner
Specific gravity	0.72 + 0.02g/l (6.0 + .02 lg/gal)
Storage	Store between +5°C and +25°C Do not store at temperatures over 50°C Avoid exposure to direct sunlight Do not store directly on concrete floor
Shelf Life	18 months from date of manufacture





Tremco CPG UK Limited Coupland Road, Hindley Green Wigan WN2 4HT +44 (0) 1942 251400 roofing.uk@tremcocpg.com

2

Find Us @ in 

www.tremco-europe.com