



1213



Tremco CPG Netherlands B.V
Vlietskade 1032
NL-4241 Arkel

14

SP540-20140621
illbruck.com/dop/SP540

EN 15651-1, -4: 2012

Non-structural sealant for joints for interior and exterior application
(intended for use in cold climates)

Sealant for movement joints in floors for interior and exterior
application (intended for use in cold climates)

- Type F-EXT-INT-CC 25HM, Type PW-EXT-INT-CC 25HM

- Conditioning: Method A

- Substrate: Mortar M1 and Primer AT140, Aluminium with Primer
AT150

REACTION TO FIRE (EN 13501)

Class E

**RELEASE OF CHEMICALS DANGEROUS TO THE
ENVIRONMENT AND HEALTH**

NPD

WATER TIGHTNESS AND AIR TIGHTNESS

- Resistance to flow

 $\leq 3\text{mm}$

- Loss of volume

 $\leq 10\%$

- tear resistance

NF

- adhesion/cohesion properties at maintained
extension after water immersion (28 days/23°C)

NF

- adhesion/cohesion properties at maintained
extension after salt water immersion (28 days/23°C)

NF

- tensile properties at maintained extension (-30°C)

NF

- tensile properties, maintained extension after water
immersion at 23°C

Pass

DURABILITY

Pass

NF = no failure according to ISO 11600

NPD = No performance declared