Technical Data Sheet

RW141

TremClip

19-11-2026 / V 5

Description

RW141 is a self-adhesive or heat applied lightning conductor clip that has an integral membrane pad for no penetrative securement.
TremClip SA is a semi rigid PVC plastic disk with a self-adhesive backing.
TremClip HA is a heat applied SBS reinforced bitumen membrane pad.



Features and Benefits

- No mechanical fixing required
- Aids in the protection of buildings from lightning strikes
- Reliable attachment of lightning conductor tapes
- Self-adhesive & heat applied versions

Usage Purpose

RW141 is designed for securing lightning conductor tapes up to 25mm wide and 5mm thick.

Packaging

250 units per box

Application

Clips should be secured at a frequency the coincides with the specialist lightning conductor contractor's design or 500 mm centres.
Heat applied clips: Compatible with reinforced bitumen membranes only and typically applied by hot air gun or gas torch (if safe to do so). Heat the exposed bitumen surface of the pad until the bitumen begins to flow and press in place ensuring a visible bead of bitumen is exuded from all sides.
Self-adhesive clips: Compatible with liquid applied membranes only. Prepare the bonding area with an appropriate cleaner before application and allow to dry. Peel the release film away from the clip and firmly press in place with even pressure around the entire circumference
of the clip.

Size options: TremClip SA: 70mm diameter and TremClip HA: 100mm x 100mm SBS pad

Please Note

Heat applied clips have SBS reinforced bitumen membrane base 100 mm x 100 mm.
Self-adhesive clips have circular rigid plastic base 50 mm in diameter.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in

Technical Data Sheet

RW141

TremClip

accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.
Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Tremco CPG UK Limited
Coupland Road, Hindley Green
Wigan, WN2 4HT
United Kingdom
+44 (0)1942 251400
hello@tremcocpg.com