



1213



2538

Tremco CPG Netherlands B.V
Vlietskade 1032
NL-4241 Arkel

14

22

FS125-20140408
illbruck.com/dop/FS125

EN 15651-1, -2: 2012

Non-structural sealant for joints for interior and exterior application
(intended for use in cold climates)

Non-structural sealant for sealing glazing applications (intended for
use in cold climates)

- Type F-EXT-INT-CC 25LM, Type G-CC 25LM

- Conditioning: Method A

- Substrate: Aluminium

REACTION TO FIRE

Class E

RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH

NPD

WATER TIGHTNESS AND AIR TIGHTNESS

- Resistance to flow

 $\leq 3\text{mm}$

- Loss of volume

 $\leq 10\%$

- adhesion/cohesion properties at maintained
extension after water immersion (23°C)

NF

- elastic recovery

 $\geq 60\%$

- adhesion/cohesion properties after exposure to heat,
water and artificial light

NF

- adhesion/cohesion properties (-30°C)

 $\leq 0,9\text{ N/mm}^2$

- adhesion/cohesion properties at maintained
extension (-30°C)

NF

DURABILITY

Passed

NF = no failure according to ISO 11600

NPD = No performance declared