

RW110

TREMDRAIN VERTICAL OUTLET



RW110 is a prefabricated, gravity fed, vertical drainage outlet manufactured from stainless steel and includes an integral membrane flange.

With 400mm spigot

| Outlet size | Flow rate including leafguard type l/sec | To suit pipe size (mm) where outlet is inserted into existing pipe in refurbishment situations | O-ring seal diameter (mm) | Membrane attachment |
|-------------|--|--|---------------------------|---------------------|
| 40mm | 0.92 | 45-50 | 5 | 500 x 500 |
| 50mm | 0.90 | 58-64 | 8 | 500 x 500 |
| 62mm | 1.65 | 70-76 | 8 | 500 x 500 |
| 70mm | 2.55 | 75-78 | 5 | 500 x 500 |
| 75mm | 2.98 | 82-97 | 8 | 500 x 500 |
| 90mm | 3.48 | 98-108 | 10 | 500 x 500 |
| 95mm | 4.08 | 102-109 | 8 | 500 x 500 |
| 110mm | 3.94 | 120-128 | 10 | 500 x 500 |
| 125mm | 5.30 | 135-143 | 10 | 500 x 500 |
| 145mm | 5.48 | 150-153 | 5 | 500 x 500 |
| 160mm | 6.76 | 170-178 | 10 | 500 x 500 |

With 600mm spigot

| Outlet size | Flow rate including leafguard type l/sec | To suit pipe size (mm) where outlet is inserted into existing pipe in refurbishment situations | O-ring seal diameter (mm) | Membrane attachment |
|-------------|--|--|---------------------------|---------------------|
| 50mm | 0.90 | 58-64 | 8 | 500 x 500 |
| 62mm | 1.65 | 70-76 | 8 | 500 x 500 |
| 75mm | 2.98 | 82-97 | 8 | 500 x 500 |
| 95mm | 4.08 | 102-109 | 8 | 500 x 500 |
| 110mm | 3.94 | 120-128 | 10 | 500 x 500 |

