

FORM PANELS c/w INSERT
WEBS-CUT TO SUIT FLOOR
CONNECTION- ADDITIONAL
FORM SUPPORT AS
REQUIRED

WET SET DOWELS FIELD
BENT INTO SLAB AS
SPECIFIED

U BRACKET ANCHOR
INSERT

EXTERIOR FINISH AS
SPECIFIED

WET SET DOWELS
TO MATCH VERTICAL
REINFORCEMENT
BETWEEN POUR OR
AS SPECIFIED

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

GYPSUM BOARD
FINISHED/FIRE STOP
INSTALLED AT JOISTS
AS PER CODE

COMPOSITE STEEL
DECK-SLAB AND
REINFORCEMENT AS
SPECIFIED

OWSJ

INTERIOR INSULATION
REMOVED AT JOIST
LOCATIONS

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

NUDURA 12" (305mm)
STANDARD FORM UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 12" (305mm) FORM UNIT
COMPOSITE STEEL DECK-SLAB
STEEL JOIST ON EXT. BEARING WALL
INTERMEDIATE FLOOR CONNECTION
EXTERIOR FINISH AS SPECIFIED

REV. NO.
004 KS

DATE:
MARCH 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

D12C06

SCALE:
1 : 8