

NUDURA 8" (203mm)
STANDARD FORM UNIT

BRICK VENEER c/w 1"
(25mm) AIR SPACE
AND BRICK TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL AS
SPECIFIED PER CODE

CONTINUOUS
CAULKING AROUND
FRAME AT CONTACT
TO MASONRY

EXTENDED DOOR
FRAME SCREWED
DIRECTLY INTO NUDURA
CONCRETE CORE

DOOR THRESHOLD

OPENING
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

EXTERIOR CONCRETE
SLAB AND SLOPE AS
PER CODE

$\frac{3}{16}$ " (5mm) ACRYLIC
PARGE COAT

NUDURA 8"
(203mm) BRICK
LEDGE FORM UNIT

NUDURA WATERPROOFING
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

LINTEL REINFORCEMENT
AS PER CODE OR AS
SPECIFIED

VAPOUR BARRIER
SEALED TO FRAME

1 $\frac{1}{2}$ "
(38mm) MIN.
COVER

BLOCKING BETWEEN
JOISTS

FLOOR FINISH
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

LAP VAPOR
BARRIER TO
CONTACT DOOR
THRESHOLD

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

HORIZ/VERT
REINFORCEMENT AS PER
CODE OR AS SPECIFIED

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 8" (203mm) FORM UNIT
DOOR HEAD/THRESHOLD DETAIL
BRICK VENEER FINISH

REV. NO.
000

DATE:
SEPT 2010

DRAWN BY:
K. STILL

DWG NO.

E8E07

SCALE:

1 : 8