



1213



2538

Tremco CPG Netherlands B.V
Vlietskade 1032
NL-4241 Arkel

14

22

GS300-20140516
illbruck.com/dop/GS300

EN 15651-1, -2, -3: 2012

Non-structural sealant for joints for interior and exterior application (intended for use in cold climates)

Non-structural sealant for sealing glazing applications (intended for use in cold climates)

Non-structural sealant for sanitary joints

- Type F-EXT-INT-CC 25LM, Type G-CC 25LM, Type S XS1

- Conditioning: Method A

- Substrate: Glass, Aluminium w/o Primer, Mortar M1 with Primer WACKER GRUND G783

| | |
|---|-------------------------|
| REACTION TO FIRE | Class E |
| RELEASE OF CHEMICALS DANGEROUS TO THE ENVIRONMENT AND HEALTH | NPD |
| WATER TIGHTNESS AND AIR TIGHTNESS | |
| - Resistance to flow | ≤ 3mm |
| - Loss of volume | ≤ 10% |
| - adhesion/cohesion properties at maintained extension after water immersion (23°C) | NF |
| - elastic recovery | ≥60 % |
| - adhesion/cohesion properties after exposure to heat, water and artificial light | NF |
| - adhesion/cohesion properties (-30°C) | ≤ 0,9 N/mm ² |
| - adhesion/cohesion properties at maintained extension (-30°C) | NF |
| MICROBIOLOGICAL GROWTH | 1 |
| DURABILITY | Passed |

NF = no failure according to ISO 11600

NPD = No performance declared