

Flowchem VE Accelerator

Product description

Flowchem VE Accelerator is a cobalt-based formulation.

Features and Key Benefits

- Accelerates the Flowchem VE resin in combination with the Flowchem VE Curing Agent

Product Information

Applications

Flowchem VE Accelerator is (pre-)mixed with the Flowchem VE Resin and Flowchem VE Curing Agent to start the curing process that will result in a full cure of the Flowchem VE system.

Note: Flowchem VE Accelerator must never come into direct contact with Flowchem VE Curing Agent

Certificates/approvals

CE according EN 13813 (when used as part of complete system)

Environment and Health

Follow the appropriate Occupational Health and Safety Guidelines applicable to the location where the application is undertaken.

For more information, please refer to the safety datasheets for the individual components.

Technical Information

Technical Characteristics (liquid state)

Appearance	violet liquid
Density at +23°C (EN ISO 1183)	1.0 kg/dm ³
Solids content	~ 100%

Packaging

The Flowchem VE Accelerator is supplied in the following pack size:

- in metal cans of 1 kg

Storage

Store in dry area, in unopened, original containers in temperatures +5 °C to +25 °C. Protected from freezing, out of direct sunlight, moisture or contaminant ingress.

Shelf-life

9 months from manufacture day when stored correctly in the original, unopened packaging as supplied.

Usage Guidelines

Application conditions of the Flowchem VE systems

Ambient temperature range:	+5°C - +30°C
Substrate temperature range:	+5°C - +30°C
Ambient relative humidity:	< 95 %
Substrate relative humidity	<4.5 % (Tramex scale or 75% RH BS8203)

Application

Flowchem VE Accelerator shall always be added to the Flowchem VE Resin prior to mixing in the Flowchem VE Curing Agent.



Coverage

The amount of Flowchem VE Accelerator in ml that must be used for 25 kg of Flowchem VE Resin:

- 1°C: 160 ml (0.64%)
- 5°C: 130 ml (0.52%)
- 10°C: 110 ml (0.44%)
- 15°C: 90 ml (0.36%)
- 20°C: 80 ml (0.32%)
- 25°C: 70 ml (0.28%)

For temperatures higher than 30°C, please take contact with our Technical Department.

Cleaning

Clean using Flowchem VE Equipment Cleaner.

Technical Service

Contact Tremco CPG "Country"

Guarantee

Tremco CPG "Country" warrants all goods to be free from defects and will replace materials proven to be defective but makes no warranty as to appearance of colour. The information and recommendations herein are believed by Tremco CPG "Country" to be accurate and reliable.