

Declaration of Performance

According to ANNEX III of the regulation (EU) N. 305/2011

Nullifire
Smart Protection



No. FB750 – 20220202

1. **Unique identification code of the product-type:** Nullifire FB750 Intubatt

2. **Intended use/es:** A coated mineral wool board used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.

3. **Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan. WN24HT

4. **Authorized representative:** Tremco CPG Netherlands B.V., Vlietskade 1032, NL-4241 WC Arkel

5. **System/s of AVCP:** System 1

6. **European Assessment Document:** EAD 350454-00-1104

European Technical Assessment: ETA 21/0412

Technical Assessment Body: CSTB Centre Scientifique et Technique du Batiment

Notified body/ies: UL International (NL) B.V. No. 2821

7. European Assessment Document

Basic work requirement	Performance
Mechanical resistance and stability	
None	Not relevant
Safety in case of fire	
Reaction to fire (EN 13501-1)	Class E
Resistance to fire (EN 13501-2)	See ETA 21/0412 Annex A
Hygiene, Health and the Environment	
Air Permeability (EN 1026:2000)	See ETA 21/0412 Annex B
Water Permeability (EAD 350454-00-1104 Annex C)	NPD
Release of dangerous substances	Declaration of manufacturer – Uses categories IA3, S/W3
Safety in Use	
Mechanical Resistance and stability (EOTA TR001:2003)	NPD
Resistance to Impact / movement (EOTA TR001:2003)	NPD
Adhesion (EOTA TR001:2003)	NPD
Protection against noise	
Airborne Sound Insulation (EN10140-2 / EN ISO 717-1)	See ETA 21/0412 Annex C
Energy, Economy and Heat Retention	
Thermal Properties (EN 12664, EN 12667 or EN 12939)	NPD
Water vapour permeability (EN ISO 12572 / EN 12086)	NPD
General Aspects Relating to fitness for use	
Durability and Serviceability (EOTA TR 024:2009)	Z ₁

Declaration of Performance

According to ANNEX III of the regulation (EU) N. 305/2011

Nullifire
Smart Protection



8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Operations Director

At Wigan on 02 February 2022

Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according to Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.



2.

CE	
TREMCO CPG UK Limited Coupland Road, Hindley Green, Wigan, WN2 4HT 22 2821-CPR-0200 FB750 – 20220202 www.nullifire.com/FB750	
EN 1366 Part 3 ETA 21/0412 EAD 350454-00-1104	
A coated mineral wool board used to reinstate the fire resistance performance of wall and floor constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class E
Resistance to fire	ETA 21/0412 Annex A
Hygiene, Health and Environment	
Air Permeability	ETA 21/0412 Annex B
Water Permeability	NPD
Dangerous Substances	Uses categories IA3, S/W3
Safety in use	
Mechanical resistance and stability	NPD
Resistance to impact/movement	NPD
Adhesion	NPD
Protection against noise	
Airborne sound insulation	ETA 21/0412 Annex C
Energy, Economy and Heat Retention	
Thermal properties	NPD
Water vapour permeability	NPD
General aspects relating to fitness for use	
Service & Durability	Z ₁