

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** illbruck AT120
- **MSDS code:** T-I-AT120
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Priming
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
tremco illbruck Ltd
Coupland Road, Hindley Green, WIGAN, WN2 4HT
T: +44 (0) 1942251400, F: +44 (0) 1942251410
msds@tremco-illbruck.com
- **Further information obtainable from:**
tremco illbruck Ltd
Coupland Road, Hindley Green, Wigan, WN2 4HT
T: +44 (0) 1942251400, F: +44 (0) 1942251410
www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com
- **1.4 Emergency telephone number:**
During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**

| | |
|-------------------|---|
| Flam. Liq. 2 | H225 Highly flammable liquid and vapour. |
| Skin Irrit. 2 | H315 Causes skin irritation. |
| Eye Dam. 1 | H318 Causes serious eye damage. |
| STOT SE 3 | H336 May cause drowsiness or dizziness. |
| Asp. Tox. 1 | H304 May be fatal if swallowed and enters airways. |
| Aquatic Chronic 2 | H411 Toxic to aquatic life with long lasting effects. |

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08 GHS09

- **Signal word** Danger
- **Contains:**
Alkanes, C7-10-iso-tetra-n-butoxytitanium

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 1)

ethylbenzene

toluene

Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with non-hazardous additions.**Dangerous components:**

| | | |
|--|---|----------|
| CAS: 90622-56-3 EINECS: 292-458-5 Reg.nr.: 01-2119471305-42-xxxx | Alkanes, C7-10-iso- Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336 | 75-<100% |
| CAS: 1330-20-7 EC number: 918-167-1 Reg.nr.: 01-2119488216-32-xxxx | xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315 | 5-<10% |
| CAS: 5593-70-4 EINECS: 227-006-8 Reg.nr.: 01-2119967423-33-xxxx | tetra-n-butoxytitanium Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336 | 1-<5% |
| CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx | ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332 | 1-<5% |
| CAS: 108-88-3 EINECS: 203-625-9 Reg.nr.: 01-2119471310-51-xxxx | toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336 | 1-<5% |

SVHC -**Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· After skin contact:

Remove from the skin using a cloth or paper. Then clean with water and soap.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· **Information for doctor:** No further relevant information available.

· **Hazards** No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** Can form explosive gas-air mixtures.

· 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Fumes can combine with air to form an explosive mixture.
Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

| | |
|--|--|
| · Ingredients with limit values that require monitoring at the workplace: | |
|--|--|

CAS: 1330-20-7 xylene (mix)

| | |
|-----|--|
| WEL | Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV |
|-----|--|

CAS: 100-41-4 ethylbenzene

| | |
|-----|---|
| WEL | Short-term value: 552 mg/m ³ , 125 ppm Long-term value: 441 mg/m ³ , 100 ppm Sk |
|-----|---|

CAS: 108-88-3 toluene

| | |
|-----|--|
| WEL | Short-term value: 384 mg/m ³ , 100 ppm Long-term value: 191 mg/m ³ , 50 ppm Sk |
|-----|--|

| | |
|--|--|
| · Ingredients with biological limit values: | |
|--|--|

CAS: 1330-20-7 xylene (mix)

| | |
|------|--|
| BMGV | 650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid |
|------|--|

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 4)

Keep away from foodstuffs, beverages and feed.
 Do not eat, drink, smoke or sniff while working.
 Avoid contact with the eyes and skin.
 Do not inhale gases / fumes / aerosols.
 Immediately remove all soiled and contaminated clothing
 Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
 Not necessary if room is well-ventilated.

Filter AX

For further guidance,
 please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· **Protection of hands:**



Protective gloves

Solvent resistant gloves

· **Material of gloves**

Nitrile rubber, NBR

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:**



Protective work clothing

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

| | |
|----------------|-------------|
| Form: | Fluid |
| Colour: | Colourless |
| Odour: | Petrol-like |

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 5)

| | |
|---|---|
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Initial boiling point and boiling range: | 110 °C |
| · Flash point: | 6 °C |
| · Flammability (solid, gas): | Not applicable. |
| · Ignition temperature: | > 200 °C |
| · Decomposition temperature: | Not determined. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 0.7 Vol % |
| Upper: | 8.3 Vol % |
| · Vapour pressure at 20 °C: | 16.3 hPa |
| · Density at 20 °C: | 0.75 g/cm ³ |
| · Solubility in / Miscibility with water: | Immiscible / difficult to mix. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| · Solvent content: | |
| VOC (EU) | 706.0 g/l |
| VOC (EC) | 94.13 % |
| · 9.2 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** Forms explosive gas mixture with air.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None if stored according to specifications.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 6)

LD/LC50 values relevant for classification:
CAS: 90622-56-3 Alkanes, C7-10-iso-

| | | |
|------------|----------|---------------------|
| Oral | LD50 | >10,000 mg/kg (rat) |
| Dermal | LD50 | >3,000 mg/kg (rat) |
| Inhalative | LC50/4 h | 21 mg/L (rat) |

CAS: 1330-20-7 xylene (mix)

| | | |
|------------|----------|----------------------|
| Oral | LD50 | 4,300 mg/kg (rat) |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 27.6 mg/L (rat) |

CAS: 5593-70-4 tetra-n-butoxytitanium

| | | |
|------|------|-------------------|
| Oral | LD50 | 3,122 mg/kg (rat) |
|------|------|-------------------|

CAS: 100-41-4 ethylbenzene

| | | |
|--------|------|-----------------------|
| Oral | LD50 | 3,500 mg/kg (rat) |
| Dermal | LD50 | 17,800 mg/kg (rabbit) |

CAS: 108-88-3 toluene

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | 5,000 mg/kg (rat) |
| Dermal | LD50 | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5,320 mg/L (mouse) |

Primary irritant effect:
Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Additional toxicological information: Repeated exposure may cause skin dryness or cracking.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1 Toxicity
Aquatic toxicity:
CAS: 1330-20-7 xylene (mix)

| | |
|-----------|--------------------------------|
| LC50/96 h | 3.77 mg/L (fish) |
| EC50/48 h | 7.4 mg/L (daphnia magna) |
| EC50/72 h | 10 mg/L (skeletonema costatum) |

12.2 Persistence and degradability No further relevant information available.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 7)

- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Disposal must be made according to official regulations.

· **European waste catalogue**

| | |
|----------|---|
| 08 04 99 | wastes not otherwise specified |
| HP3 | Flammable |
| HP4 | Irritant - skin irritation and eye damage |
| HP5 | Specific Target Organ Toxicity (STOT)/Aspiration Toxicity |
| HP14 | Ecotoxic |

- **Uncleaned packaging:**
- **Recommendation:**
Empty packages totally (without drops or grains, cleaned with a spatula). Under observation of the relevant local respectively national regulations re-use or recycling is preferred.

SECTION 14: Transport information

- | | |
|---------------------------------------|--|
| · 14.1 UN-Number | |
| · ADR, IMDG, IATA | UN1993 |
| · 14.2 UN proper shipping name | |
| · ADR | 1993 FLAMMABLE LIQUID, N.O.S. (Alkanes, C7-10-iso-), ENVIRONMENTALLY HAZARDOUS |
| · IMDG | FLAMMABLE LIQUID, N.O.S. (Alkanes, C7-10-iso-), MARINE POLLUTANT |
| · IATA | FLAMMABLE LIQUID, N.O.S. (Alkanes, C7-10-iso-) |

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR



· Class

3 (F1) Flammable liquids.

· Label

3

· IMDG



· Class

3 Flammable liquids.

· Label

3

· IATA



· Class

3 Flammable liquids.

· Label

3

· 14.4 Packing group

· ADR, IMDG, IATA

II

· 14.5 Environmental hazards:

Product contains environmentally hazardous substances: Alkanes, C7-10-iso-

· Marine pollutant:

Yes

· Special marking (ADR):

Symbol (fish and tree)

Symbol (fish and tree)

· 14.6 Special precautions for user

Warning: Flammable liquids.

· Danger code (Kemler):

33

· EMS Number:

F-E, S-E

· Stowage Category

B

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ)

1L

· Excepted quantities (EQ)

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· Transport category

2

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 9)

| | |
|-----------------------------------|---|
| · Tunnel restriction code | D/E |
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| · UN "Model Regulation": | UN 1993 FLAMMABLE LIQUID, N.O.S. (ALKANES, C7-10-ISO-), 3, II, ENVIRONMENTALLY HAZARDOUS |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).

COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)

2001/118/EC as regards the list of wastes

2008/98/EC on waste

· Directive 2012/18/EU

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3, 48

· National regulations:

· Information about limitation of use:

Observe employment restrictions.

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

· Other regulations, limitations and prohibitive regulations

· **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

(Contd. on page 11)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 21.08.2019

Version number 18

Revision: 20.08.2019

Trade name: illbruck AT120

(Contd. of page 10)

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to the hearing organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· * Data compared to the previous version altered.

GB