

Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Nullifire SC900 A
- · MSDS code: W-N-SC900A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Coating compound/ Surface coating/ paint
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410 msds@cpg-europe.com

· Further information obtainable from:

See above-mentioned address

Tremco CPG UK Ltd Coupland Road, Hindley Green, Wigan, WN2 4HT T: +44 (0) 1942251400, F: +44 (0) 1942251410 www.cpg-europe.com, info.uk@cpg-europe.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008
- Carc. 2 H351 Suspected of causing cancer.
- Repr. 2 H361f Suspected of damaging fertility.

STOT RE 2 H373 May cause damage to the urinary tract through prolonged or repeated exposure.

- · Additional information: (EC) 1272/2008 & UK SI 2019 No. 720 "GB- CLP": 2.6.4.5 (Flam. Liq. 3)
- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 1)

· Hazard pictograms



- · Signal word Warning
- · Contains:

melamine

Hazard statements

H351 Suspected of causing cancer.

H361f Suspected of damaging fertility.

H373 May cause damage to the urinary tract through prolonged or repeated exposure.

Precautionary statements

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 Wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

· Supplemental information:

EUH208 Contains maleic anhydride. May produce an allergic reaction.

 Directive 2004/42/CE on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC

VOC 2004/42/CE & UK SI 2012/1715 (A / j) = <500 g/l

Nullifire SC900 A

- = 139 g/I
- 2.3 Other hazards No further relevant information available.
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)

GB



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 2			
· Dangerous components:			
CAS: 108-78-1 EINECS: 203-615-4 Reg.nr.: 01-2119485947-16-xxxx	melamine Carc. 2, H351; Repr. 2, H361f; STOT RE 2, H373	10-<20%	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	5-<10%	
CAS: 28553-12-0 EINECS: 249-079-5 Reg.nr.: 01-2119430798-28-xxxx	1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (DINP; di-"isononyl" phthalate) substance with a Community workplace exposure limit	1-<5%	
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	1-<5%	
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31-xxxx	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	<0.001%	

- · EU SVHC see Section 15
- · GB SVHC see Section 15
- · Additional information:

For the wording of the listed hazard phrases refer to section 16.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

Sensitising effect by skin contact is possible by prolonged exposure.

Suspected of damaging fertility.

Suspected of causing cancer.

(Contd. on page 4)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 3)

Causes damage to organs through prolonged or repeated exposure.

- · Hazards No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Avoid contact with the eyes and skin.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

· Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

(Contd. on page 5)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 4)

Provide ventilation for receptacles.

- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- · Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: 0°C to +35°C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with	limit values tha	t require m	onitorina a	at the workplace:
			• • • • • • • • • • • • • • • • • • • •	

CAS: 1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

CAS: 28553-12-0 1,2-Benzenedicarboxylic acid, di-C8-10-branched alkyl esters, C9-rich (DINP; di-

"isononyl" phthalate)

WEL Long-term value: 5 mg/m³

CAS: 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

CAS: 108-31-6 maleic anhydride

WEL | Short-term value: 3 mg/m³

Long-term value: 1 mg/m³

Sen

· DNELs

CAS: 108-78-1 melamine

Inhalative DNEL 8.3 mg/m3 (workers) (systemic effects)

· Ingredients with biological limit values:

CAS: 1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· Additional Occupational Exposure Limit Values for possible hazards during processing:

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

· Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

(Contd. on page 6)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 5)

- · 8.2 Exposure controls
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Ensure good ventilation/exhaustion at the workplace.

Do not breathe spray.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Wash thoroughly after handling.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Wear respiratory protection.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. Filter A/P2

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Fluorocarbon rubber (Viton)

PVA gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

(Contd. on page 7)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 6)

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Colour: White

Odour: CharacteristicMelting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range

range 137-143 °C (CAS: 1330-20-7 xylene (mix))

· Flash point: 39 °C · Ignition temperature: 500 °C

Solubility

• water: Immiscible / difficult to mix.

· **Vapour pressure:** Not determined.

· Density and/or relative density

Density at 20 °C: 1.55 g/cm³

• 9.2 Other information

· Appearance:

· Form: Viscous

· Important information on protection of health

and environment, and on safety.

Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· VOC (EU) 139.0 g/l · VOC (EC) 139 g/l 8.96 %

Information with regard to physical hazard

classes

· Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void Self-reactive substances and mixtures Void

(Contd. on page 8)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 7) Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void Oxidising liquids Void · Oxidising solids Void Organic peroxides Void · Corrosive to metals Void Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Nitrogen oxides

Carbon monoxide and carbon dioxide

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50	values rele	evant for classification:
CAS: 108	-78-1 mela	mine
Oral	Oral LD50 3,161 mg/kg (rat)	
CAS: 133	0-20-7 xyle	ene (mix)
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	27.124 mg/L (rat)
	LC50/4 h	5,000 ppmV (rat)
CAS: 100	-41-4 ethyl	benzene
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
		(Contd. on page 9

(Contd. on page 9)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 8)

CAS: 108-	-31-6 male	eic anhydride
Oral	LD50	400 mg/kg (rat)
Dermal	LD50	2,620 mg/kg (rabbit)

- Skin corrosion/irritation Slight irritation possible.
- · Serious eye damage/irritation Slight irritation possible.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity

Suspected of causing cancer.

· Reproductive toxicity

Suspected of damaging fertility.

- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

May cause damage to the urinary tract through prolonged or repeated exposure.

- Aspiration hazard Based on available data, the classification criteria are not met.
- · Additional toxicological information:

Repeated exposure may cause skin dryness or cracking.

Fillers are encapsulated within the liquid and therefore not expected to be released from the product under normal conditions of use.

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 1330-20-7 xylene (mix)

LC50/96 h 4.2 mg/L (rainbow trout)

EC50/48 h | 2.93-4.4 mg/L (daphnia magna)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

(Contd. on page 10)

- GB



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

(Contd. of page 9)

Trade name: Nullifire SC900 A

· 12.7 Other adverse effects

Ecotoxical effects:

CAS: 1330-20-7 xylene (mix)

IC50/72 h 2.2 mg/L (algae)

- Additional ecological information:
- · General notes:

Overall evaluation

Avoid transfer into the environment.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

	· European waste catalogue		
	08 01 11* waste paint and varnish containing organic solvents or other hazardous substances		
Γ	HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity		
	HP7	Carcinogenic	
Ī	HP10	Toxic for reproduction	

- Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, ADN, IMDG, IATA	Void
· 14.2 UN proper shipping name	
ADR	Void
	Void
· ADN, IMDG, IATA	Void
· 14 3 Transport hazard class(es)	

14.3 Transport hazard class(es)

· ADR, ADN, IMDG, IATA

· Class Void

(Contd. on page 11)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

	(Contd. of page
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user	Not applicable.
· 14.7 Maritime transport in bulk according	ng to IMO Not applicable.
· Transport/Additional information:	
· ADR	2.2.3.1.1 (note 1)
·IMDG	2.3.1.3
·IATA	3.3.1.3
· UN "Model Regulation":	Void

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) STATUTORY INSTRUMENTS 2012 No. 1715 ENVIRONMENTAL PROTECTION | The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012, and any subsequent amendments

- "GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019
- "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019 The Endocrine Disruptor Lists I, II, III (www.edlists.org)
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 52a
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

(Contd. on page 12)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 11)

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- · Substances of very high concern (SVHC) according to EU REACH, Article 57

CAS: 108-78-1 melamine

- · Substances of very high concern (SVHC) according to UK REACH Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H361f Suspected of damaging fertility.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 13)



Revision: 13.02.2023

Printing date 14.02.2023

Version number 11 (replaces version 10)

Trade name: Nullifire SC900 A

(Contd. of page 12)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.

GB