

Flowchem VE Curing Agent

Product description

Flowchem VE Curing Agent is a transparent formulation which, among other things, consists of a peroxide.

Features and Key Benefits

Assists in the full cure of the Flowchem VE systems

Product Information

Applications

Flowchem VE Curing Agent is used as a curing agent for all Flowchem VE systems.

Note: Flowchem VE Curing Agent must never come into direct contact with Flowchem VE Accelerator.

Certificates/approvals

CE according EN 13813 (when used as part of complete system)

Environment and Health

Follow the appropriate Occupational Health and Safety Guidelines applicable to the location where the application is undertaken.

For more information, please refer to the safety datasheets for the individual components.

Technical Information

Appearance	Transparent liquid
Density at +23°C (EN ISO 1183)	1.0 kg/dm ³
Solids content	~ 100%

Technical Characteristics (liquid state)



Construction

Europe



Packaging

The Flowchem VE Curing Agent is supplied in the following pack size:

in plastic bottles of 1 kg •

Storage

Store in dry area, in unopened, original containers in temperatures +5 °C to +25 °C. Protected from freezing, out of direct sunlight, moisture or contaminant ingress.

Shelf-life

9 months from manufacture day when stored correctly in the original, unopened packaging as supplied.

Usage Guidelines

Application conditions of the Flowchem VE systems

Ambient temperature range:	+5°C - +30°C
Substrate temperature range:	+5°C - +30°C
Ambient relative humidity:	< 95 %
Substrate relative humidity	<4.5 % (Tramex scale or 75% RH BS8203)

Application

Flowchem VE Accelerator shall added to and mixed with the Flowchem VE Resin before the Flowchem VE Curing Agent added.

Fillers must be added after Flowchem VE Accelerator and Flowchem VE Curing Agent mixed in the Flowchem VE Resin.

Coverage

2% of the weight of the Flowchem VE Resin up to an application temperature of 30°C. For temperatures higher than 30°C, please take contact with our Technical Department.

Cleaning

Clean using Flowchem VE Equipment Cleaner.



Construction

Europe



Technical Service Contact Tremco CPG "Country"

Guarantee

Tremco CPG "Country" warrants all goods to be free from defects and will replace materials proven to be defective but makes no warranty as to appearance of colour. The information and recommendations herein are believed by Tremco CPG "Country" to be accurate and reliable.

