

NUDURA 12" (305mm)  
STANDARD FORM UNIT

BRICK VENEER c/w  
1" (25mm) AIR  
SPACE AND BRICK  
TIES

FORM PANELS c/w  
INSERT WEBS-CUT  
TO SUIT FLOOR  
CONNECTION-ADDITIONAL  
FORM SUPPORT AS  
REQUIRED

WET SET FIELD  
DOWELS FIELD BENT  
INTO SLAB AS  
SPECIFIED

THROUGH WALL  
FLASHING AS PER  
CODE OR AS  
SPECIFIED

NUDURA 12" (305mm)  
SITE ASSEMBLED BRICK  
LEDGE FORM UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC  
PARGE COAT

NUDURA WATERPROOF  
MEMBRANE

HORIZ/VERT  
REINFORCEMENT AS PER  
CODE OR AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

STEEL DECK SUPPORT  
WELDING ANCHOR  
INSERT

COMPOSITE STEEL  
DECK- SLAB AND  
REINFORCEMENT AS  
SPECIFIED

INTERIOR INSULATION  
TO BE DISCONTINUOUS  
AT FLOOR LINES

OWSJ

MINIMUM  $\frac{1}{32}$ " (0.8mm) x 2  
 $\frac{1}{2}$ " (63.5mm) GALVANIZED  
STEEL CHANNEL CAP TO  
PROVIDE THERMAL BARRIER  
PROTECTION

WET SET DOWELS TO  
MATCH VERTICAL  
REINFORCEMENT  
BETWEEN POURS OR  
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM  
BOARD

**DISCLAIMER NOTICE:**  
SPECIFIC INFORMATION  
REQUIRED FOR COMPLIANCE  
WITH LOCAL CODES IS THE  
RESPONSIBILITY OF THE  
DESIGNER



**NUDURA**

**INTEGRATED BUILDING TECHNOLOGY**

*Building Value.*

NUDURA 12" (305mm) FORM UNIT  
COMPOSITE STEEL DECK-SLAB  
STEEL JOISTS ON SIDE WALL  
BRICK VENEER FINISH

REV. NO.  
003 KS

REV. DATE:  
MARCH 2010

DRAWN BY:  
T. VAN CLIEAF

DWG NO.

D12C05

SCALE:  
1 : 8