

RW141

TREMCLIP

KEY BENEFITS SUMMARY

- No mechanical fixing required
- Aids in the protection of buildings from lightning strikes
- Reliable attachment of lightning conductor tapes
- Self-adhesive & heat applied versions

PRODUCT INFORMATION

Description

RW141 is a self-adhesive or heat applied lightning conductor clip that has an integral membrane pad for no penetrative securement.

TremClip SA is a semi rigid PVC plastic disk with a self-adhesive backing.
TremClip HA is a heat applied SBS reinforced bitumen membrane pad.

Usage / Purpose

RW141 is designed for securing lightning conductor tapes up to 25mm wide and 5mm thick.

Packaging

250 units per box

Sizes

TremClip SA: 70mm diameter

TremClip HA: 100mm x 100mm SBS pad

Availability

Direct from Tremco CPG UK Limited (see bottom of leaflet for address and telephone details).

Application

- Clips should be secured at a frequency the coincides with the specialist lightning conductor contractor's design or 500 mm centres.
- Heat applied clips: Compatible with reinforced bitumen membranes only and typically applied by hot air gun or gas torch (if safe to do so). Heat the exposed bitumen surface of the pad until the bitumen begins to flow and press in place ensuring a visible bead of bitumen is exuded from all sides.
- Self-adhesive clips: Compatible with liquid applied membranes only. Prepare the bonding area with an appropriate cleaner before application and allow to dry. Peel the release film away from the clip and firmly press in place with even pressure around the entire circumference of the clip.

Please Note

- Heat applied clips have SBS reinforced bitumen membrane base 100 mm x 100 mm.
- Self-adhesive clips have circular rigid plastic base 50 mm in diameter.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.