

NUDURA 10" (254mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WET SET DOWELS TO
MATCH VERTICAL
REINFORCEMENT
BETWEEN POURS OR
AS SPECIFIED

V-CLIP WALL PANEL
ANCHOR

FORM PANELS c/w
INSERT WEB-CUT TO SUIT
FLOOR
CONNECTION-ADDITIONAL
FORM SUPPORT AS
REQUIRED

THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

NUDURA 10" (254mm)
SITE ASSEMBLED
BRICK LEDGE FORM UNIT

$\frac{3}{16}$ " (5mm) ACRYLIC PARGE
COAT

NUDURA WATERPROOF
MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

FINISHED CONCRETE
TOPPING

HOLLOW CORE
PRECAST SLAB

FINISH AS SPECIFIED

DOWELS BENT AND
GROUTED INTO HOLLOW
CORE PRECAST PANELS
AS SPECIFIED

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 10" (254mm)
BRICK LEDGE FORM UNIT
HOLLOW CORE PRECAST SLAB
EXTERIOR SIDE WALL DETAIL
BRICK VENEER FINISH

REV. NO.
003 KS

REV. DATE:
FEB 2010

DRAWN BY:
T. VAN CLIEAF

DWG NO.

D10A06

SCALE:
1 : 8