

SAFETY DATA SHEET

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: RW551 AlphaGuard PUMA Topcoat Coloured

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Coatings

Uses advised against: Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Importer/Supplier/Distributor Information

Alteco Technik GmbH

Raiffeisenstrasse 16

D-27239 Twistringen

Germany

Telephone: +49 424392950

Fax: +49 4243929589

Contact person: MSDS_Alteco@tremcocpg.com

National Supplier

Tremco CPG UK Limited

Coupland Road

WN2 4HT Hindley Green, WIGAN

UK

Telephone: +44 1942251400

Fax: +44 1942251410

Contact person: www.tremcocpg.eu, uk.info@tremcocpg.com

1.4 Emergency telephone number: 111 / 0300 020 0155

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

The product has been classified according to the legislation in force.

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Physical Hazards

Flammable liquids

Category 2

H225: Highly flammable liquid and vapour.

Health Hazards

Skin irritation

Category 2

H315: Causes skin irritation.

RW551 AlphaGuard PUMA Topcoat Coloured

Skin sensitiser	Category 1	H317: May cause an allergic skin reaction.
Specific Target Organ Toxicity - Single Exposure	Category 3	H335: May cause respiratory irritation.

Environmental hazards

Chronic hazards to the aquatic environment	Category 3	H412: Harmful to aquatic life with long lasting effects.
--	------------	--

2.2 Label elements



Signal Words:

Danger

Hazard Statement(s):

H225: Highly flammable liquid and vapour.
H315: Causes skin irritation.
H317: May cause an allergic skin reaction.
H335: May cause respiratory irritation.
H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention:

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243: Take action to prevent static discharges.
P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P273: Avoid release to the environment.
P280: Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P403+P235: Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label: :

Contains
methyl methacrylate
2-ethylhexyl acrylate
2,2'-ethylenedioxydiethyl dimethacrylate
2-(benzotriazol-2-yl)-4-methylphenol
2-(N,4-dimethylanilino)ethanol

RW551 AlphaGuard PUMA Topcoat Coloured

2.3 Other hazards

PBT/vPvB data

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Endocrine disrupting properties-Toxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties-Ecotoxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical name	Concentration	CAS-No.	EC No.	REACH Registration No.	M-Factor:	Notes
methyl methacrylate	20 - <50%	80-62-6	201-297-1	01-2119452498-28-XXXX;	No data available.	#
2-ethylhexyl acrylate	10 - <25%	103-11-7	203-080-7	01-2119453158-37-XXXX;	No data available.	
2,2'-ethylenedioxy diethyl dimethacrylate	1 - <5%	109-16-0	203-652-6	01-2119969287-21-XXXX;	No data available.	
2-(benzotriazol-2-yl)-4-methylphenol	0,25 - <1%	2440-22-4	219-470-5	01-2119583811-34-xxxx;	No data available.	
2-(N,4-dimethylanilin o)ethanol	0,1 - <1%	2842-44-6	220-638-5	01-2120827830-56-XXXX;	No data available.	

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

This substance has workplace exposure limit(s).

This substance is listed as SVHC.

Classification

Chemical name	Classification	Notes
methyl methacrylate	Classification: Flam. Liq.: 2: H225; Skin Irrit.: 2: H315; STOT SE: 3: H335; Skin Sens.: 1: H317	Note D

RW551 AlphaGuard PUMA Topcoat Coloured

	Acute toxicity, oral: LD 50: 7.900 mg/kg Acute toxicity, inhalation: LC 50: 29,8 mg/l Acute toxicity, dermal: LD 50: > 5.000 mg/kg	
2-ethylhexyl acrylate	Classification: STOT SE: 3: H335; Skin Sens.: 1: H317; Skin Irrit.: 2: H315; Aquatic Chronic: 3: H412 Acute toxicity, oral: LD 50: 4.435 mg/kg Acute toxicity, dermal: LD 50: > 12.000 mg/kg	Note D
2,2'-ethylenedioxydiethyl dimethacrylate	Classification: Skin Sens.: 1B: H317 Acute toxicity, dermal: LD 50: > 2.000 mg/kg	None.
2-(benzotriazol-2-yl)-4-methylphenol	Classification: Skin Sens.: 1B: H317; Aquatic Chronic: 1: H410 Acute toxicity, inhalation: LC 50: 590 mg/m ³ Acute toxicity, dermal: LD 50: > 2.000 mg/kg	None.
2-(N,4-dimethylanilino)ethanol	Classification: Skin Sens.: 1: H317; Eye Irrit.: 2: H319; Aquatic Chronic: 2: H411 Acute toxicity, oral: LD 50: 2.000 mg/kg	None.

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

Move out of dangerous area. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Get medical attention if symptoms persist. Remove contaminated clothing and shoes.

Inhalation:

If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, trained personnel should give oxygen. Get medical attention immediately. Place unconscious person on his/her side in the recovery position and ensure breathing can take place.

Skin Contact:

Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or rash occurs: Get medical advice/attention.

Eye contact:

Immediately rinse with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.

RW551 AlphaGuard PUMA Topcoat Coloured

Ingestion: If swallowed, rinse mouth with water (only if the person is conscious). Do not give victim anything to drink if he is unconscious. DO NOT induce vomiting. Get medical attention immediately.

Personal Protection for First-aid Responders: No data available.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms: Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

Hazards: No data available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment: No data available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media: Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

5.2 Special hazards arising from the substance or mixture:

Highly flammable liquid and vapour. Containers can burst violently when heated, due to excess pressure build-up. Vapours are flammable and heavier than air. Vapours may travel across the ground and reach remote ignition sources, causing a flashback fire danger. Flammable or explosive mixtures with air may be formed. In case of fire, toxic gases may be formed. Carbon monoxide. Carbon dioxide. Organic compounds.

5.3 Advice for firefighters

Special fire-fighting procedures: Water spray should be used to cool containers. Evacuate area. Dyke and collect extinguishing water. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for fire-fighters: Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

SECTION 6: Accidental release measures

RW551 AlphaGuard PUMA Topcoat Coloured

- | | |
|---|---|
| 6.1 Personal precautions, protective equipment and emergency procedures: | Use personal protective equipment. See Section 8 of the SDS for Personal Protective Equipment. |
| 6.1.1 For non-emergency personnel: | In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Eliminate all sources of ignition. Provide adequate ventilation. Avoid contact with eyes, skin, and clothing. Avoid breathing vapours. |
| 6.1.2 For emergency responders: | See Section 8 of the SDS for Personal Protective Equipment. |
| 6.2 Environmental precautions: | Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer. Environmental manager must be informed of all major spillages. |
| 6.3 Methods and material for containment and cleaning up: | Take precautionary measures against static discharges. Use explosion proof electric equipment. Dam and absorb spillages with sand, earth or other non-combustible material. Transfer to a container for disposal. Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal. |
| 6.4 Reference to other sections: | For waste disposal, see section 13. |

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- | | |
|---------------------------------|---|
| Technical Measures: | No data available. |
| Local/Total ventilation: | No data available. |
| Safe handling advice: | Wear appropriate personal protective equipment. Do not breathe vapour. Avoid contact with eyes, skin, and clothing. Provide adequate ventilation. Use only in well-ventilated areas. Vapours are flammable and heavier than air. Vapours may travel across the ground and reach remote ignition sources, causing a flashback fire danger. Open drum carefully as content may be under pressure. Solvent vapours may form explosive mixtures with air. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Ground and bond container and receiving equipment. Do not eat, drink or smoke when using the product. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product. Take off contaminated clothing and wash it before reuse. Private clothes and working clothes |

RW551 AlphaGuard PUMA Topcoat Coloured

should be kept separately.

Contact avoidance measures: No data available.

7.2 Conditions for safe storage, including any incompatibilities

Safe storage conditions: Never fill containers more than 80 % because aerial oxygen is necessary for stabilising. Store in closed original container at temperatures between 5°C and 30°C. Store in a cool and well-ventilated place. Store in a dry place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Protect from sunlight. Store away from: Oxidising agents. Peroxides Polymerisation initiators. Acids. Bases. Rust. Activated carbon.

Safe packaging materials: No data available.

7.3 Specific end use(s): No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Chemical name	Type	Form of exposure	Exposure Limit Values		Source
methyl methacrylate	TWA		50 ppm	208 mg/m ³	EH40 WEL (2007)
	STEL 15 minutes		100 ppm	416 mg/m ³	EH40 WEL (01 2020)

Please refer to the latest edition of the appropriate source text and consult an industrial hygienist or similar professional, or local agencies, for further information.

Biological Limit Values

No biological exposure limits noted for the ingredient(s).

DNEL-Values

Remarks: DNEL-Values

Critical component	Type	Route of Exposure	Health Warnings	Remarks
methyl methacrylate	Workers	Inhalation	Local, long-term; 208 mg/m ³	Repeated dose toxicity
	General population	Inhalation	Local, long-term; 104 mg/m ³	Repeated dose toxicity
	Workers	Dermal	Local, long-term; 1,5 mg/cm ²	Skin Sensitisation
	General population	Dermal	Local, long-term; 1,5 mg/cm ²	Skin Sensitisation
	General population	Inhalation	Local, short-term; 208 mg/m ³	Repeated dose toxicity
	Workers	Eyes	Local effect;	No hazard identified
	General population	Eyes	Local effect;	No hazard identified

RW551 AlphaGuard PUMA Topcoat Coloured

	General population	Oral	Systemic, long-term; 8,2 mg/kg	Repeated dose toxicity
	Workers	Inhalation	Local, short-term; 416 mg/m3	Repeated dose toxicity
	Workers	Dermal	Systemic, long-term; 13,67 mg/kg	Repeated dose toxicity
	General population	Dermal	Systemic, long-term; 8,2 mg/kg	Repeated dose toxicity
	Workers	Inhalation	Systemic, long-term; 348,4 mg/m3	Repeated dose toxicity
	General population	Dermal	Local, short-term; 1,5 mg/cm2	Skin Sensitisation
	General population	Inhalation	Systemic, long-term; 74,3 mg/m3	Repeated dose toxicity
	Workers	Dermal	Local, short-term; 1,5 mg/cm2	Skin Sensitisation
2-ethylhexyl acrylate	General population	Dermal	Systemic, long-term; 2,34 mg/kg	Repeated dose toxicity
	Workers	Inhalation	Local, short-term; 38 mg/m3	irritation respiratory tract
	General population	Oral	Systemic, long-term; 0,23 mg/kg	Repeated dose toxicity
	Workers	Dermal	Systemic, long-term; 6,5 mg/kg	Repeated dose toxicity
2,2'-ethylenedioxydiethyl dimethacrylate	General population	Inhalation	Systemic, long-term; 14,5 mg/m3	Repeated dose toxicity
	Workers	Inhalation	Systemic, long-term; 48,5 mg/m3	Repeated dose toxicity
	General population	Eyes	Local effect;	No hazard identified
	Workers	Eyes	Local effect;	No hazard identified
	Workers	Dermal	Systemic, long-term; 13,9 mg/kg	Repeated dose toxicity
	General population	Oral	Systemic, long-term; 8,33 mg/kg	Repeated dose toxicity
	General population	Dermal	Systemic, long-term; 8,33 mg/kg	Repeated dose toxicity
2-(benzotriazol-2-yl)-4-methylphenol	Workers	Inhalation	Systemic, short-term; 1 mg/m3	Acute toxicity
	Workers	Eyes	Local effect;	No hazard identified
	General population	Eyes	Local effect;	No hazard identified
	Workers	Dermal	Systemic, long-term; 2,5 mg/kg	Repeated dose toxicity
	General population	Dermal	Systemic, long-term; 1,2 mg/kg	Repeated dose toxicity

PNEC-Values

Remarks: PNEC-Values

Critical component	Environmental compartment	PNEC-Values	Remarks
methyl methacrylate	Aquatic (marine water)	0,094 mg/l	
	Sediment (marine water)	1,02 mg/kg	
	Sediment (freshwater)	10,2 mg/kg	
	Sewage treatment plant	10 mg/l	
	Soil	1,48 mg/kg	Soil
2-ethylhexyl acrylate	Aquatic (freshwater)	0,94 mg/l	
	Soil	1 mg/kg	
	Sediment (marine water)	0,0126 mg/kg	
	Aquatic (freshwater)	2,72 µg/l	
	Sewage treatment plant	2,3 mg/l	
	Aquatic (marine water)	0,272 µg/l	
	Sediment (freshwater)	0,126 mg/kg	

RW551 AlphaGuard PUMA Topcoat Coloured

2,2'-ethylenedioxydiethyl dimethacrylate	Sewage treatment plant	1,7 mg/l	
	Aquatic (freshwater)	0,016 mg/l	
	Aquatic (marine water)	0,002 mg/l	
	Sediment (freshwater)	0,185 mg/kg	
	Sediment (marine water)	0,018 mg/kg	
	Soil	0,027 mg/kg	
2-(benzotriazol-2-yl)-4-methylphenol	Soil	100 mg/kg	
	Sediment (marine water)	0,014 mg/kg	
	Sewage treatment plant	1 mg/l	
	Aquatic (freshwater)	0 mg/l	
	Aquatic (marine water)	0 mg/l	
	Sediment (freshwater)	0,136 mg/kg	

8.2 Exposure controls

Appropriate Engineering Controls:

Observe good industrial hygiene practices. Observe occupational exposure limits and minimise the risk of inhalation of vapours and mist. Adequate ventilation should be provided so that exposure limits are not exceeded. Mechanical ventilation or local exhaust ventilation may be required. Use explosion-proof ventilation equipment.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection:

Wear safety glasses with side shields (or goggles). Provide easy access to water supply and eye wash facilities.

Hand Protection:

Material: Butyl rubber.
Break-through time: > 60 min
Glove thickness: >= 0,7 mm
Additional Information: Chemical resistant gloves The most suitable glove must be chosen in consultation with the gloves supplier, who can inform about the breakthrough time of the glove material. Wear suitable gloves tested to EN374. Gloves should be replaced regularly and if there is any sign of damage to the glove material.
Material: Polyvinyl alcohol (PVA).

Skin and Body Protection:

Wear suitable protective clothing. Chemical resistant clothing Flame retardant antistatic protective clothing.

Respiratory Protection:

In case of insufficient ventilation, wear suitable respiratory equipment. It is recommended to use respiratory equipment with combination filter, type A2/P2. If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Self-contained breathing apparatus.

RW551 AlphaGuard PUMA Topcoat Coloured

Hygiene measures:

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned. Do not eat, drink or smoke when using the product. Take off contaminated clothing and wash it before reuse. Private clothes and working clothes should be kept separately.

Environmental Controls:

Do not release into the environment. Do not discharge into drains, water courses or onto the ground.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	liquid
Form:	No data available.
Colour:	Various
Odour:	acrylic-like Strong pungent
Odour Threshold:	0,05 ppm
Freezing point:	-48 °C Methyl methacrylate
Boiling Point:	101 °C Methyl methacrylate
Flammability:	No data available.

Upper/lower limit on flammability or explosive limits

Explosive limit - upper:	12,5 %(V) Methyl methacrylate
Explosive limit - lower:	2,1 %(V) Methyl methacrylate

Flash Point:	10 °C
Auto-ignition temperature:	No data available.
Decomposition Temperature:	No data available.
pH:	Not applicable.

Viscosity

Dynamic viscosity:	No data available.
Kinematic viscosity:	No data available.
Flow Time:	No data available.

Solubility(ies)

Solubility in Water:	Insoluble in water
-----------------------------	--------------------

RW551 AlphaGuard PUMA Topcoat Coloured

Solubility (other):	No data available.
Dissolution Rate:	No data available.
Partition coefficient (n-octanol/water):	1,38 Methyl methacrylate
Dispersion Stability:	No data available.
Vapour pressure:	37 hPa(20 °C) Methyl methacrylate
Relative density:	No data available.
Density:	1,00 - 1,04 g/cm ³
Bulk density:	No data available.
Relative vapour density:	No data available.

9.2 Other information

VOC content:	< 500 g/l 2004/42/CE & UK SI 2012/1715/IIA(j)(500)
---------------------	---

SECTION 10: Stability and reactivity

10.1 Reactivity:	Material is stable under normal conditions.
10.2 Chemical stability:	Highly flammable liquid and vapour. Flammable or explosive mixtures with air may be formed.
10.3 Possibility of hazardous reactions:	Polymerisation occurs when exposed to white light, ultraviolet light or heat. Polymerisation is a highly exothermic reaction and may generate sufficient heat to cause thermal decomposition and/or rupture containers.
10.4 Conditions to avoid:	Keep away from heat/sparks/open flames. - No smoking. Protect from sunlight.
10.5 Incompatible Materials:	Avoid radical-forming starting agents, peroxides and reactive metals. Amines. Heavy metals Oxidising agents. Reducing Agents. Acids. Bases.
10.6 Hazardous decomposition products:	Carbon monoxide. Carbon dioxide. Organic compounds.

SECTION 11: Toxicological information

RW551 AlphaGuard PUMA Topcoat Coloured

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (list all possible routes of exposure)

Oral

Product: Based on available data, the classification criteria are not met.

Components:

methyl methacrylate	LD 50, Rat, 7.900 mg/kg, 2 = reliable with restrictions, non-guideline study, Weight of evidence.
2-ethylhexyl acrylate	LD 50, Rat, 4.435 mg/kg, 2 = reliable with restrictions, Key study
2-(N,4-dimethylanilino)ethanol	LD 50, Rat, 2.000 mg/kg, 1 = reliable without restrictions, Key study

Dermal

Product: Based on available data, the classification criteria are not met.

Components:

methyl methacrylate	LD 50, Rabbit, > 5.000 mg/kg, 2 = reliable with restrictions, according to specific guideline, Experimental result, Key study
2-ethylhexyl acrylate	LD 50, Rat, > 12.000 mg/kg, 2 = reliable with restrictions, Experimental result, Not specified LD 50, Rabbit, 7.522 mg/kg, 2 = reliable with restrictions
2,2'-ethylenedioxydiethyl dimethacrylate	LD 50, Mouse, > 2.000 mg/kg, 2 = reliable with restrictions, Experimental result, Key study

RW551 AlphaGuard PUMA Topcoat Coloured

2-(benzotriazol-2-yl)-4-methylphenol LD 50, Rat, > 2.000 mg/kg, 2 = reliable with restrictions, Experimental result, Key study

Inhalation

Product: ATEmix, 73,75 mg/l, Dust and mist, Based on available data, the classification criteria are not met.

Components:

methyl methacrylate LC 50, Rat, 4 h, 29,8 mg/l, Vapour, 2 = reliable with restrictions, Vapour, Key study

2-(benzotriazol-2-yl)-4-methylphenol LC 50, Rat, 4 h, 590 mg/m³, Aerosol, No, 2 = reliable with restrictions, Aerosol

Repeated dose toxicity

Product: Based on available data, the classification criteria are not met.

Components:

methyl methacrylate NOAEL Rat, Male, Oral, 14 d, > 200 mg/kg, Oral Experimental result, Other

NOAEL Rat, Female, Male, Oral, 104 Weeks, >= 124,1 mg/kg, Oral Experimental result, Supporting study

NOAEL Hamster, Female, Male, Inhalation, 1,64 mg/l, Inhalation Experimental result, Other

NOAEL Rat, Female, Male, Oral, 104 Weeks, >= 164 mg/kg, Oral Experimental result, Supporting study

LOAEL Rat, Male, Oral, 14 d, > 200 mg/kg, Oral Experimental result, Other

2-ethylhexyl acrylate LOAEL Rat, Female, Male, Inhalation, 0,226 mg/l, Inhalation Experimental result, Key study

NOAEL Rat, Female, Male, Inhalation, 0,226 mg/l, Inhalation

RW551 AlphaGuard PUMA Topcoat Coloured

Experimental result, Key study

2,2'-ethylenedioxydiethyl dimethacrylate NOAEL Rat, Female, Male, Oral, 5 - 6 Weeks, 1.000 mg/kg, Oral
Experimental result, Key study

2-(benzotriazol-2-yl)-4-methylphenol NOAEL Rat, Female, Male, Oral, 104 Weeks, > 47 mg/kg, Oral
Experimental result, Key study

Skin Corrosion/Irritation

Product: Causes skin irritation.

Components:

2-ethylhexyl acrylate Irritating, in vivo, Rabbit, 24 - 72 h, Experimental result, Key study

Serious Eye Damage/Eye Irritation

Product: Based on available data, the classification criteria are not met.

Components:

2-ethylhexyl acrylate Not irritant, in vivo, Rabbit, 24 - 72 hrs, EU

2,2'-ethylenedioxydiethyl dimethacrylate Not irritant, in vivo, Rabbit, 24 - 72 hrs, CLP (1272/2008)

2-(benzotriazol-2-yl)-4-methylphenol Not Classified, in vivo, Rabbit, 7 d, EU

Respiratory or Skin Sensitisation

Product: May cause an allergic skin reaction.

Components:

RW551 AlphaGuard PUMA Topcoat Coloured

methyl methacrylate Skin sensitisation:, in vivo, Mouse, Sensitising

2-ethylhexyl acrylate Skin sensitisation:, in vivo, Mouse, Sensitising

2,2'-ethylenedioxydiethyl
dimethacrylate Skin sensitisation:, in vivo, Guinea pig, Sensitising
Skin sensitisation:, in vivo, Mouse, Sensitising

2-(benzotriazol-2-yl)-4-
methylphenol Skin sensitisation:, in vivo, Mouse, Sensitising
Skin sensitisation:, in vivo, Guinea pig, Sensitising

Carcinogenicity

Product: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity

In vitro

Product: Based on available data, the classification criteria are not met.

In vivo

Product: Based on available data, the classification criteria are not met.

Reproductive toxicity

Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure

RW551 AlphaGuard PUMA Topcoat Coloured

Product: May cause respiratory irritation.

Specific Target Organ Toxicity - Repeated Exposure

Product: Based on available data, the classification criteria are not met.

Aspiration Hazard

Product: Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Other information

Product: No data available.

SECTION 12: Ecological information

General information: Contains a substance which causes risk of hazardous effects to the environment.

12.1 Toxicity:

Acute hazards to the aquatic environment:

Fish

Product: Not classified based on available data.

Components:

methyl methacrylate LC 50, Oncorhynchus mykiss, 96 h, > 79 mg/lflow-through
2-ethylhexyl acrylate LC 50, Cyprinodon variegatus, 96 h, 1,1 mg/lflow-through, Experimental result, Key study

RW551 AlphaGuard PUMA Topcoat Coloured

	LC 50, Leuciscus idus, 96 h, 56,2 mg/lStatic
	LC 0, Cyprinodon variegatus, 96 h, < 0,89 mg/lflow-through
	LC 0, Oncorhynchus mykiss, 96 h, 2,8 mg/lflow-through
	LC 100, Cyprinodon variegatus, 96 h, 3,5 mg/lflow-through
2,2'-ethylenedioxydiethyl dimethacrylate	LC 50, Danio rerio, 96 h, 16,4 mg/lsemi-static, Experimental result, Key study
	LC 50, Danio rerio, 24 h, 23,1 mg/lsemi-static
2-(benzotriazol-2-yl)-4-methylphenol	NOAEL, Oncorhynchus mykiss, 96 h, 0,17 mg/lsemi-static, Experimental result, Key study
	LC 50, Oncorhynchus mykiss, 96 h, > 0,17 mg/lsemi-static
	LC 100, Danio rerio, 96 h, > 100 mg/lStatic
	LC 50, Danio rerio, 96 h, > 100 mg/lStatic
	LC 0, Danio rerio, 96 h, > 100 mg/lStatic

Aquatic Invertebrates

Product:

Not classified based on available data.

Components:

methyl methacrylate	EC 50, Daphnia magna, 48 h, 69 mg/lflow-through, Experimental result, Key study
2-ethylhexyl acrylate	EC 50, Daphnia magna, 48 h, 1,3 mg/lStatic, experimental result Experimental result, Key study NOAEL, Daphnia magna, 48 h, 0,88 mg/lflow-through, experimental result Experimental result, Key study EC 50, Daphnia magna, 24 h, > 10 mg/lStatic, Experimental result, Other LC 0, Americamysis bahia, 96 h, 0,99 mg/lflow-through, Experimental result, Other EC 100, Daphnia magna, 48 h, 2,8 mg/lStatic, Experimental result, Key study
2-(benzotriazol-2-yl)-4-methylphenol	EC 50, Daphnia magna, 24 h, > 1.000 mg/lStatic, experimental result Experimental result, Key study EC 100, Daphnia magna, 24 h, > 1.000 mg/lStatic, Experimental result, Key study EC 50, Daphnia magna, 24 h, > 1.000 mg/lStatic, Experimental result, Key study
2-(N,4-dimethylanilino)ethanol	LC 50, Daphnia magna, 48 h, 7,03 mg/lStatic, Experimental result, Key study

Toxicity to aquatic plants

Product:

Not classified based on available data.

Toxicity to microorganisms

Product:

Not classified based on available data.

Chronic hazards to the aquatic environment:

Fish

Product:

Not classified based on available data.

Components:

methyl methacrylate	NOEL, Danio rerio, 9,4 mg/l, flow-through, experimental result LC 50, Danio rerio, 33,7 mg/l, flow-through, experimental result
---------------------	--

RW551 AlphaGuard PUMA Topcoat Coloured

Aquatic Invertebrates

Product:

Not classified based on available data.

Components:

methyl methacrylate	NOEC, Daphnia magna, 37 mg/l, flow-through, experimental result Experimental result, Key study EC 50, Daphnia magna, 49 mg/l, flow-through, experimental result Experimental result, Key study
2-ethylhexyl acrylate	EC 10, Daphnia magna, 0,91 mg/l, semi-static, experimental result Experimental result, Key study EC 20, Daphnia magna, 1,5 mg/l, semi-static, experimental result Experimental result, Key study EC 50, Daphnia magna, > 2,8 mg/l, semi-static, experimental result Experimental result, Key study EC 20, Daphnia magna, 1,2 mg/l, semi-static, experimental result Experimental result, Key study EC 10, Daphnia magna, 0,85 mg/l, semi-static, experimental result Experimental result, Key study
2,2'-ethylenedioxydiethyl dimethacrylate	LOAEL, Daphnia magna, 100 mg/l, semi-static, experimental result Experimental result, Key study EC 50, Daphnia magna, 51,9 mg/l, semi-static, experimental result Experimental result, Key study EC 10, Daphnia magna, 30,2 mg/l, semi-static, experimental result Experimental result, Key study EC 50, Daphnia magna, 51,9 mg/l, semi-static, experimental result Experimental result, Key study
2-(benzotriazol-2-yl)-4-methylphenol	LOAEL, Daphnia magna, 0,041 mg/l, semi-static, experimental result Experimental result, Key study EC 50, Daphnia magna, 0,015 mg/l, semi-static, experimental result Experimental result, Key study EC 50, Daphnia magna, 0,015 mg/l, semi-static, experimental result Experimental result, Key study

Toxicity to microorganisms

Product:

Not classified based on available data.

12.2 Persistence and degradability

Biodegradation

Product:

Not classified based on available data.

Components:

methyl methacrylate	94 %, 14 d, Detected in water. Experimental result, Key study
2-ethylhexyl acrylate	30 %, 20 d, Detected in water. Experimental result, Other 40 %, 20 d, Detected in water. Experimental result, Other 70 - 80 %, 15 d, Detected in water. Experimental result, Key study 30 - 40 %, 20 d, Detected in water. Experimental result, Other 50 - 60 %, 14 d, Detected in water. Experimental result, Supporting study
2,2'-ethylenedioxydiethyl dimethacrylate	61 %, 17 d, Detected in water. Experimental result, Key study 85 %, 28 d, Detected in water. Experimental result, Key study
2-(benzotriazol-2-yl)-4-methylphenol	> 0 %, 28 d, Detected in water. Experimental result, Key study 2 %, 28 d, Detected in water. Experimental result, Key study

RW551 AlphaGuard PUMA Topcoat Coloured

2-(N,4-dimethylanilino)ethanol 22,7 %, 28 d, Detected in water. Experimental result, Key study

12.3 Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: Not classified based on available data.

Components:

methyl methacrylate	2 - 6,59, Aquatic sediment estimated by calculation
2-ethylhexyl acrylate	233, Aquatic sediment QSAR, Weight of evidence
2,2'-ethylenedioxydiethyl dimethacrylate	16, Aquatic sediment Not specified, Other
2-(benzotriazol-2-yl)-4-methylphenol	Cyprinus carpio, 548 - 895, Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study Cyprinus carpio, 44 - 220, Aquatic sediment Experimental result, Weight of Evidence study Cyprinus carpio, 196 - 802, Aquatic sediment Read-across from supporting substance (structural analogue or surrogate), Weight of Evidence study Cyprinus carpio, 123 - 494, Aquatic sediment Experimental result, Weight of Evidence study Cyprinus carpio, 130 - 295, Aquatic sediment Experimental result, Weight of Evidence study

Partition Coefficient n-octanol / water (log Kow)

Product: 1,38, 20 °C, Methyl methacrylate

12.4 Mobility in soil:

Product Not classified based on available data.

12.5 Results of PBT and vPvB assessment:

Product This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects:

Other hazards

Product: Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

RW551 AlphaGuard PUMA Topcoat Coloured

General information:

This material and/or its container must be disposed of as hazardous waste. Dispose of waste and residues in accordance with local authority requirements.

Disposal methods:

Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Contaminated Packaging:

Since emptied containers retain product residue, follow label warnings even after container is emptied. Do not puncture or incinerate even when empty. Dispose of this material and its container to hazardous or special waste collection point.

European Waste Codes

Unused product:

08 01 11*: waste paint and varnish containing organic solvents or other dangerous substances

Contaminated Packaging:

15 01 10*: packaging containing residues of or contaminated by dangerous substances

SECTION 14: Transport information

ADR

14.1 UN number or ID number:	UN 1866
14.2 UN proper shipping name:	RESIN SOLUTION
14.3 Transport hazard class(es)	
Class:	3
Label(s):	3
Classification Code:	F1
Hazard No. (ADR):	33
Tunnel restriction code:	(D/E)
14.4 Packing group:	II
Limited quantity	005 L
Excepted quantity	E2
14.5 Environmental hazards	
Environmentally Hazardous:	No
14.6 Special precautions for user:	None.

IMDG

14.1 UN number or ID number:	UN 1866
14.2 UN proper shipping name:	RESIN SOLUTION
14.3 Transport hazard class(es)	
Class:	3
Label(s):	3
EmS No.:	F-E, S-E
14.4 Packing group:	II
Limited quantity	005 L

RW551 AlphaGuard PUMA Topcoat Coloured

Excepted quantity	E2
14.5 Environmental hazards	
Marine pollutant:	No
14.6 Special precautions for user:	None.

IATA

14.1 UN number or ID number:	UN 1866
14.2 UN proper shipping name:	RESIN SOLUTION
14.3 Transport hazard class(es)	
Class:	3
Label(s):	3
14.4 Packing group:	II
Passenger and cargo aircraft :	353
Limited quantity	None.
Excepted quantity	E2
14.5 Environmental hazards	
Environmentally Hazardous:	No
14.6 Special precautions for user:	None.
Passenger and cargo aircraft:	Allowed. 353
Cargo aircraft only :	Allowed. 364

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

UK. REACH, Annex XIV, Substances Subject to Authorization (Authorization List), as amended: None present or none present in regulated quantities.

UK. UK REACH Candidate List of substances of very high concern (SVHCs) for Authorisation: None present or none present in regulated quantities.

UK. Great Britain Assimilated Regulation (EU) 2019/1021 on Persistent Organic Pollutants, as amended: None present or none present in regulated quantities.

Regulation 2024/590/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: None present or none present in regulated quantities.

Regulation 2024/590/EC on substances that deplete the ozone layer, Annex II, New Substances: None present or none present in regulated quantities.

UK EXP1: UK. GB PIC List, Regulation (EU) 649/2012 as amended by EU Exit Regulations S.I. 2019/720 and S.I. 2020/1567, as amended: None present or none present in regulated quantities.

UK EXP2: UK. GB PIC List, Regulation (EU) 649/2012 as amended by EU Exit Regulations S.I. 2019/720 and S.I. 2020/1567, as amended: None present or none present in regulated quantities.

RW551 AlphaGuard PUMA Topcoat Coloured

UK EXP3: UK. GB PIC List, Regulation (EU) 649/2012 as amended by EU Exit Regulations S.I. 2019/720 and S.I. 2020/1567, as amended: None present or none present in regulated quantities.

UK BAN: UK. GB PIC List, Regulation (EU) 649/2012 as amended by EU Exit Regulations S.I. 2019/720 and S.I. 2020/1567, as amended: None present or none present in regulated quantities.

UK REACH List of restrictions (Annex 17):

Chemical name	CAS-No.	Number on list
methyl methacrylate	80-62-6	40, 3

Control of Major Accident Hazards Regulations 2015 (COMAH):

Classification	Lower-tier Requirements	Upper-tier Requirements
P5c. Flammable liquids	5.000 t	50.000 t

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

15.2 Chemical safety assessment: No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Date of first report version: 06.06.2025

Revision Date: 08.10.2025

Version #: 3.2

Abbreviations and acronyms:

EH40 WEL: UK. EH40 Workplace Exposure Limits (WELs)
EH40 WEL / STEL: Short Term Exposure Limit (STEL)
EH40 WEL / TWA: Time Weighted Average (TWA)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR -

RW551 AlphaGuard PUMA Topcoat Coloured

Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Notes:

Note D	Certain substances which are susceptible to spontaneous polymerisation or decomposition are generally placed on the market in a stabilised form. It is in this form that they are listed in Part 3. However, such substances are sometimes placed on the market in a non-stabilised form. In this case, the supplier must state on the label the name of the substance followed by the words 'non-stabilised'.
--------	--

Key literature references and sources for data: No data available.

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567

Classification	Classification procedure
Flammable liquids, Category 2	On basis of test data
Skin irritation, Category 2	Calculation method
Skin sensitiser, Category 1	On basis of test data
Specific Target Organ Toxicity - Single Exposure, Category 3	Calculation method
Chronic hazards to the aquatic environment, Category 3	On basis of test data

Wording of the statements in section 3

RW551 AlphaGuard PUMA Topcoat Coloured

H225	Highly flammable liquid and vapour.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Training information: No data available.

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.