

Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: illbruck FM330

· MSDS code: A-I-FM330

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Sealant

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Tremco CPG Netherlands B.V. Vlietskade 1032, 4241 WC Arkel T: +31 (0) 183568000, F: +31 (0) 183568100 msds@cpg-europe.com

· Further information obtainable from:

Tremco CPG UK Ltd Coupland Road, Hindley Green, Wigan, WN2 4HT T: +44 (0) 1942251400, F: +44 (0) 1942251410 www.cpg-europe.com, info.uk@cpg-europe.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 1)

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Contains:

methylenediphenyl diisocyanate

- · Hazard statements
- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H317 May cause an allergic skin reaction.
- H351 Suspected of causing cancer.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- · Precautionary statements
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Do not pierce or burn, even after use.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.
- P284 In case of inadequate ventilation wear respiratory protection.
- P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- Supplemental information:
- EUH204 Contains isocyanates. May produce an allergic reaction.
- As from 24 August 2023 adequate training is required before industrial or professional use.
- · feica.eu/PUinfo:





- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · **vPvB:** Not applicable.
- Determination of endocrine-disrupting properties

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

|List I

illbruck

Safety data sheet acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 2)

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Active substance with propellant

Dangerous components:		
CAS: 26447-40-5 EINECS: 247-714-0 Reg.nr.: 01-2119457015-45-xxxx	methylenediphenyl diisocyanate Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Skin Irrit. 2; H315: $C \ge 5$ % Eye Irrit. 2; H319: $C \ge 5$ % Resp. Sens. 1; H334: $C \ge 0.1$ % STOT SE 3; H335: $C \ge 5$ %	30-<50%
CAS: 9082-00-2	Ethoxylated/propoxylated glycerol Acute Tox. 4, H302	10-<20%
CAS: 25791-96-2 NLP: 500-044-5	Glycerol, propoxylated Acute Tox. 4, H302	10-<20%
CAS: 1244733-77-4 EC number: 807-935-0 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302; Aquatic Chronic 3, H412	10-<20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	5-<10%
CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1A, H220; Press. Gas (Comp.), H280	1-<5%
CAS: 556-67-2 EINECS: 209-136-7 Reg.nr.: 01-2119529238-36-xxxx	Octamethylcyclotetrasiloxane (D4) Flam. Liq. 3, H226; Repr. 2, H361f; Aquatic Chronic 1, H410 (M=10) PBT; vPvB	<0.1%

- · EU SVHC see Section 15
- · GB SVHC see Section 15
- · Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

(Contd. on page 4)

illbruck

Safety data sheet acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 3)

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Carbon monoxide (CO)

Carbon dioxide (CO2)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- · **Protective equipment:** Wear self-contained respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

00

(Contd. on page 5)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 4)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Store away from water.
- · Further information about storage conditions:

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:		
CAS: 115-10-6 dimethyl ether		
WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm		
PNECs		
CAS: 26447 40 F mothylogodinhogyl diiggayanete		

CAS: 26447-40-5 methylenediphenyl diisocyanate

	1 mg/L (sewage treatment plant)
	1 mg/L (soil)
	10 mg/L (sporadic release)
	0.1 mg/L (salt water)
PNEC	mg/kg dwt (sediment (salt water)) (exposure not expected)
	mg/kg dwt (sediment (fresh water)) (exposure not expected)

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

PNEC 0.64 mg/L (fresh water) 0.064 mg/L (marine)

PNEC 1 mg/L (fresh water)

(Contd. on page 6)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

	(Contd. of page 5)
PNEC	1.7 mg/kg dwt (soil)
	1.34 mg/kg dwt (sediment (salt water))
CAS: 1	15-10-6 dimethyl ether
PNEC	0.155 mg/L (fresh water)
	160 mg/L (sewage treatment plant)
	1.549 mg/L (intermittent release)
	0.016 mg/L (salt water)
PNEC	0.045 mg/kg (soil)
	0.069 mg/kg (sediment (salt water))

Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Hand protection



Protective gloves

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

(Contd. on page 7)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 6)

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection



Tightly sealed goggles

Body protection:



Protective work clothing

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Aerosol

· Colour: According to product specification

Odour: Characteristic

· Odour threshold: Not determined.

· **Melting point/freezing point:** Not applicable, as aerosol.

Undetermined.

· Flammability Not applicable.

Lower and upper explosion limit

• **Lower:** 1.8 Vol % (CAS: 75-28-5 isobutane)

• **Upper:** 18.6 Vol % (CAS: 115-10-6 dimethyl ether)

· Flash point: -97 °C

Ignition temperature: 235 °C (CAS: 115-10-6 dimethyl ether)

• **Decomposition temperature:** Not determined.

· **pH** Mixture reacts violently with water.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

Solubility

· water: Immiscible / difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 0 hPa

Density and/or relative density

Density at 20 °C: 0.99 g/cm³
 Relative density Not determined.
 Vapour density Not determined.

(Contd. on page 8)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 7)

• 9.2 Other information

· Appearance:

· Form: Aerosol

Important information on protection of health

and environment, and on safety.

· **Auto-ignition temperature:** Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

Solvent content:

 ⋅ VOC (EU)
 152.7 g/l

 ⋅ VOC (EC)
 15.43 %

· Evaporation rate Not applicable.

Information with regard to physical hazard

classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised

container: May burst if heated.

 Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void Pyrophoric solids Void · Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable

gases in contact with water Void
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 9)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 8)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
 Harmful if inhaled.

· I D/I C50 values relevant for classific

· LD/LC50 values relevant for classification:			
CAS: 2644	CAS: 26447-40-5 methylenediphenyl diisocyanate		
Oral	LD50	>2,000 mg/kg (rat)	
Dermal	LD50	>9,400 mg/kg (rabbit)	
Inhalative	LC50/1 h	1.5 mg/L (rat)	
CAS: 9082	2-00-2 Eth	oxylated/propoxylated glycerol	
Oral	LD50	>500 mg/kg (rat)	
Dermal	LD50	>2,000 mg/kg (rabbit)	
CAS: 2579	91-96-2 GI	ycerol, propoxylated	
Oral	LD50	1,999 mg/kg (rat)	
CAS: 1244	4733-77-4	tris(2-chloro-1-methylethyl)phosphate	
Oral	LD50	632 mg/kg (rat)	
CAS: 556-	-67-2 Octa	methylcyclotetrasiloxane (D4)	
Oral	LD50	4,800 mg/kg (rat)	
		1,700 mg/kg (mouse)	
Dermal	LD50	2,400 mg/kg (rat)	
Inhalative	LC50/4 h	12.1 mg/L (rat)	

Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity

Suspected of causing cancer.

- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 10)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 9)

- 11.2 Information on other hazards
- Endocrine disrupting properties

CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate

List II

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: CAS: 26447-40-5 methylenediphenyl diisocyanate LC50/96 h (static) >1,000 mg/L (brachydanio rerio) (OESO 203) EC50/24 h (static) >1,000 mg/L (daphnia magna) (OESO 202) EC50/72 h (static) >1,640 mg/L (scenedesmus subspicatus) (OESO 201) CAS: 9082-00-2 Ethoxylated/propoxylated glycerol >100 mg/L (brachydanio rerio) LC50/48 h >100 mg/L (daphnia magna) EC50/48 h >1,000 mg/L (scenedesmus capricornutum) EC50/72 h CAS: 1244733-77-4 tris(2-chloro-1-methylethyl)phosphate 51 mg/L (pimephales promelas) LC50/96 h EC50/48 h 131 mg/L (daphnia magna) EC50/96 h 131 mg/L (daphnia magna)
 - 12.2 Persistence and degradability No further relevant information available.
 - Other information: The product is not easily biodegradable.
 - 12.3 Bioaccumulative potential No further relevant information available.
 - · 12.4 Mobility in soil No further relevant information available.
 - · 12.5 Results of PBT and vPvB assessment
 - · PBT: Not applicable.
 - · **vPvB:** Not applicable.
 - 12.6 Endocrine disrupting properties

For information on endocrine disrupting properties see section 11.

· 12.7 Other adverse effects

· Ecotoxical effects:		
CAS: 26447	-40-5 methylenediphenyl diisocyanate	
LC50/14 d	>1,000 mg/kg (eisenia foetida) (OESO 207)	
NOEC/21 d	>10 mg/L (daphnia magna) (OESO 202)	
NOEC/14 d	>1,000 mg/kg (avea sativa) (OESO 208)	
	>1,000 mg/kg (lactuca sativa) (OESO 208)	

Other information:

This product contains no substances in Annex I to Directive EC 1005/2009 concerning ozone depleting substances

GE



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 10)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue		
16 05 05	gases in pressure containers other than those mentioned in 16 05 04	
15 01 04	metallic packaging	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP6	Acute Toxicity	
HP7	Carcinogenic	
HP13	Sensitising	

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

 14.1 UN number or ID number 	. 14	I UN	number	or ID	number
---	------	------	--------	-------	--------

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

ADR 1950 AEROSOLS 1950 AEROSOLS

· IMDG AEROSOLS

· IATA AEROSOLS, flammable

· 14.3 Transport hazard class(es)

· ADR



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases.

(Contd. on page 12)



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

	(Contd. of page 1
Label	2.1
· 14.4 Packing group · ADR, IMDG, IATA	Void
· 14.5 Environmental hazards: · Marine pollutant:	No
· 14.6 Special precautions for user · Hazard identification number (Kemler code) · EMS Number: · Stowage Code · Segregation Code	Warning: Gases. F-D,S-U SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS Category C, Clear of living quarters. SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
 14.7 Maritime transport in bulk according to instruments 	Not applicable.
Transport/Additional information:	
· ADR · Limited quantities (LQ) · Excepted quantities (EQ) · Transport category	1L Code: E0 Not permitted as Excepted Quantity
Tunnel restriction code	D D
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2.1



Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

(Contd. of page 12)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) "GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

- · Directive 2012/18/EU
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 56, 70
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

 Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

- National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- Other regulations, limitations and prohibitive regulations No further relevant information available.
- · Substances of very high concern (SVHC) according to EU REACH, Article 57 Not applicable.
- · Substances of very high concern (SVHC) according to UK REACH Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 14)



(Contd. of page 13)

Safety data sheet acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 30.01.2023 Version number 7 (replaces version 6) Revision: 30.01.2023

Trade name: illbruck FM330

H226	Flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H361f	Suspected of damaging fertility.
H373	May cause damage to organs through prolonged or repeated exposure.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH204	Contains isocyanates. May produce an allergic reaction.

Department issuing SDS:

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols - Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3