

RW160, RW161 & RW162

TREMTRIM

KEY BENEFITS SUMMARY



- Effective waterproofing termination
- Robust GRP construction
- Bespoke colour options

PRODUCT INFORMATION

Description

RW160, RW161 and RW162 is a prefabricated GRP edge trim that is specifically designed for multiple flat roof waterproofing types.

Usage / Purpose

RW160, RW161 & RW162 trims are compatible with various Tremco reinforced bitumen membrane and liquid applied membrane systems to effectively terminate the specified waterproofing systems at the perimeter edge within a water-check or water-shed configuration.

Packaging

Units are banded. Quantity and design subject to project.

Availability

Direct from Tremco CPG UK Limited (see bottom of leaflet for address and telephone details).

Application Instructions

Mechanically fix TremTrim GRP edge trims to roof perimeters at approx. 200-300 mm centres (subject to wind load calculations) using substrate specific fasteners. Clouts nails are not recommended.

At the end of each trim joint, install strengthening cleats and ensure the trims are hooked into position. Position trims so that a slight gap is maintained between the vertical leg of the trim and external façade avoiding any type of capillary action.

Before applying waterproofing membranes directly to the trim, ensure the bonding area is clean and prepared with a system specific primer as stated within the project specific specification.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

RW160, RW161 & RW162

TREMTRIM



TECHNICAL DATA

| Characteristic | Data |
|----------------|--|
| Material | Glass fibre reinforced polyester |
| Length | 2500mm |
| Face | 53mm or 75mm |
| Type | Standard or dual |
| Compatibility | AlphaGuard liquid and POWERply RBM systems |

