

Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: illbruck AT105

· MSDS code: T-I-AT105

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture Priming

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

msds@tremco-illbruck.com

#### · Further information obtainable from:

tremco illbruck Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.tremco-illbruck.co.uk, uk.info@tremco-illbruck.com

#### 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), 01 809 2166 (ROI), or otherwise to contact a doctor.

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Repr. 2 H361d Suspected of damaging the unborn child.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms







GHS02 GHS07 GHS08

Signal word Danger

(Contd. on page 2)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 1)

#### · Contains:

tetraethyl silicate

toluene butanone

titanium tetrakis(2-ethylhexanolate)

#### Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H361d Suspected of damaging the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

#### **Precautionary statements**

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

#### Supplemental information:

Restricted to professional users.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 78-10-4 tetraethyl silicate  EINECS: 201-083-8 Flam. Liq. 3, H226; Acute Tox. 4, H332; Eye Irrit. 2, H319;  STOT SE 3, H335	30-<50%	
CAS: 78-93-3 butanone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 Reg.nr.: 01-2119457290-43-xxxx	20-<30%	
CAS: 1070-10-6 titanium tetrakis(2-ethylhexanolate)  EINECS: 213-969-1 Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335  Reg.nr.: 01-2119968572-27-xxxx	20-<30%	
CAS: 108-88-3 toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Reg.nr.: 01-2119471310-51-xxxx Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336	5-<10%	

(Contd. on page 3)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 2)

- · SVHC -
- Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

- · 4.1 Description of first aid measures
- General information: Take affected persons out into the fresh air.
- · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Remove from the skin using a cloth or paper. Then clean with water and soap.

If skin irritation continues, consult a doctor.

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information Cool endangered receptacles with water spray.

#### **SECTION 6: Accidental release measures**

· 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 3)

#### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Fumes can combine with air to form an explosive mixture.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· 7.3 Specific end use(s) No further relevant information available.

### **SECTION 8: Exposure controls/personal protection**

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters

· Ingre	· Ingredients with limit values that require monitoring at the workplace:	
CAS:	78-10-4 tetraethyl silicate	
OEL	Short-term value: 340 mg/m³, 40 ppm Long-term value: 170 mg/m³, 20 ppm	
WEL	Long-term value: 44 mg/m³, 5 ppm	
CAS:	78-93-3 butanone	
WEL	Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV	
CAS:	108-88-3 toluene	
WEL	Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm Sk	
	(Contd. on page 5)	

(Contd. on page 5)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 4)

#### · DNELs

· Long term effects		
CAS: 78-93-3 butanone		
Oral	consumer	31 mg/kg (human)
Dermal	industrial	1,116 mg/kg (human)
	consumer	412 mg/kg (human)
Inhalative	industrial	600 mg/m3 (human)
	consumer	106 mg/m3 (human)

#### · PNECs

#### **CAS: 78-93-3 butanone**

PNEC 55.8 mg/L (fresh water)

709 mg/L (sewage treatment plant) 55.8 mg/L (sporadic release)

55.8 mg/L (salt water)

PNEC 22.5 mg/kg (soil)

284.7 mg/kg (sediment (salt water)) 284.7 mg/kg (sediment (fresh water))

#### · Ingredients with biological limit values:

#### **CAS: 78-93-3 butanone**

BMGV 70 µmol/L

Medium: urine

Sampling time: post shift

Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Pregnant women should strictly avoid inhalation or skin contact.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Filter AX

(Contd. on page 6)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 5)

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

Protection of hands:



Protective gloves

Solvent resistant gloves

· Material of gloves

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Fluid
Colour: Yellowish
Odour: Like ketone
Odour threshold: Not determined.

pH-value: Not determined.Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 79 °C

· Flash point: -1 °C

(Contd. on page 7)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

	(Contd. of page 6)
· Flammability (solid, gas):	Not applicable.
· Ignition temperature:	514 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits: Lower: Upper:	1.3 Vol % 23.0 Vol %
· Vapour pressure at 20 °C:	105 hPa
· Density at 20 °C:	0.89 g/cm³
· Solubility in / Miscibility with water:	Immiscible / difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Solvent content: VOC (EU) VOC (EC) · 9.2 Other information	309.2 g/l 34.74 % No further relevant information available.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: None if stored according to specifications.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
CAS: 78-10-4 tetraethyl silicate		
Oral	LD50	6,270 mg/kg (rat)
Dermal	LD50	5,878 mg/kg (rabbit)
	•	/0

(Contd. on page 8)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

		(Contd. of page 7)	
CAS: 78-9	CAS: 78-93-3 butanone		
Oral	LD50	3,300 mg/kg (rat)	
Dermal	LD50	5,000 mg/kg (rabbit)	
Inhalative	LC50/4 h	34 mg/L (rat)	
CAS: 108-	CAS: 108-88-3 toluene		
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/L (mouse)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Additional toxicological information: Repeated exposure may cause skin dryness or cracking.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

### **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:			
CAS: 78-93-3 butanone			
LC0/96 h 2,993 mg/L (pimephales p	promelas)		
EC50/48 h 308 mg/L (daphnia magna)			

- 12.2 Persistence and degradability No further relevant information available.
- · Other information: The product is easily biodegradable.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 9)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 8)

- · **vPvB:** Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

Disposal must be made according to official regulations.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 04 99	9 wastes not otherwise specified	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP10	HP10 Toxic for reproduction	

- Uncleaned packaging:
- · Recommendation:

Empty packages totally (without drops or grains, cleaned with a spatula). Under observation of the relevant local respectively national regulations re-use or recycling is preferred.

SECTION 14: Transport information	
· 14.1 UN-Number · ADR, IMDG, IATA	UN1993
14.2 UN proper shipping name	
ADR	1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), TETRAETHYL SILICATE) 1993 FLAMMABLE LIQUID, N.O.S. (METHYL ETHYL
· IMDG, IATA	KETONE, TETRAETHYL SILICATE) FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), TETRAETHYL
	SILICATE)

(Contd. on page 10)

- GB -



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 9) · 14.3 Transport hazard class(es) · ADR · Class 3 (F1) Flammable liquids. · Label · IMDG, IATA · Class 3 Flammable liquids. · Label · 14.4 Packing group · ADR, IMDG, IATA Ш · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Flammable liquids. · Hazard identification number (Kemler code): 33 · EMS Number: F-E,S-E Stowage Category В · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable. · Transport/Additional information: · ADR · Limited quantities (LQ) 1L Excepted quantities (EQ) Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml Transport category · Tunnel restriction code D/E · IMDG · Limited quantities (LQ) 1L

(Contd. on page 11)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

	(Contd. of page 10)
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHYL METHYL KETONE (METHYL ETHYL KETONE), TETRAETHYL SILICATE), 3, II

### **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture "CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) 2001/118/EC as regards the list of wastes

2008/98/EC on waste

- Directive 2012/18/EU
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.

(Contd. on page 12)



Printing date 03.04.2020 Version number 17 Revision: 15.10.2019

Trade name: illbruck AT105

(Contd. of page 11)

H373 May cause damage to organs through prolonged or repeated exposure.

#### Department issuing SDS:

Prepared and verified in accordance with "REACH" Regulation (EC) No 1907/2006, Annex II, Part A, 0.2.3.

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - inhalation – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

\* \* Data compared to the previous version altered.

GB