

POWERply SA

SELF-ADHESIVE FLAT ROOF SYSTEM

POWERply SA is a styrene-butadiene-styrene (SBS) that is installed through self-adhesion. It combines pre-engineered components and an established installation process, to deliver a proven durable solution. It can turn your older but still functional roof into a long-lasting, highly efficient weatherproofing system by overlaying.

The system can waterproof over existing flat roof build-ups and structural roof decks. It can also be used as a full system build up for either roof replacement or new build construction projects. Alongside it being a full roof solution, it can be used solely for combustible detailing, compatible with other systems.




Suitability

For built environment sectors across public and private including housing, education, healthcare, government buildings and commercial.

System Features

- High-performance integrated system
- Time-tested
- Flame-free installation
- Independently certified to Broof(t4) classification (BS EN 13501-5)
- Full roof or detailing system solution
- System durability in excess of 30 years**
- Uninsulated and warm roof applications available
- Compliant offering to the NFRC's Safe2Torch initiative



Warm roof application

NUMBER	PRODUCT TITLE	WEIGHT
1	Prepared Substrate	N/A
2	TremStik Spray Primer	Nominal
3	POWERply AVCL SA	3.7kg/m ²
4	TremStik PU Adhesive	Nominal
5	TremTherm Insulation	4.48kg/m ² (140mm PIR)***
6	TremStik Spray-on Primer	Nominal
7	POWERply Underlay SA	3.7kg/m ²
8	TremStik Spray Primer	Nominal
9	POWERply Capping SA	6kg/m ²



NBS



Tremco CPG UK Limited - A Company approved to:



POWERply SA

SELF-ADHESIVE FLAT ROOFING SYSTEM



System Compliance and Accreditations

ECO CREDENTIALS



UK manufacturer

Tremco CPG is an international construction product manufacturer, including factories in the UK.



Carbon footprint commitment

Manufacturing process in accordance with ISO 14064-1:2018 (Greenhouse gases Part 1).



Green roofs

POWERply is green roof and roof garden accredited with the inclusion of a root barrier.

RESILIENCE



Fire safety

Independently certified by the BBA to Broof(t4) classification (BS EN 13501-5). PIR & Mineral wool 25mm to 500mm fire test compliance.



Damage resistance

'Resistance to damage' rating of R4 (the highest level of acceptance) under MOAT 31.



Durability

System durability in excess of 30 years**.



Fit for purpose

POWERply systems comply with BS 6229:2018 and guidance outlined within NHBC technical requirements for flat roofs and balconies.



Zero falls

Independently certified by the BBA for zero-falls for roofs with falls between 0 and 1:80.

WARRANTY



Warranty

Once the system is installed and checked by our team the building owner will acquire a warranty of up to 25 years*.



Planned preventative maintenance

We offer warranty extensions with our maintenance packages. This is managed through by our expert Aftercare Team.

THE TREMCO DIFFERENCE

Single Source Solution

We are not only a UK manufacturer, we pride ourselves on offering a single source solution for roofing.

Whether new build or refurbishment, we design the roof/s, we install the chosen system via our network of Trusted Partners, monitor the install throughout, and a warranty is then issued.

Once completed our aftercare team is here to help in the unlikely event that you have problems with your new roof. They will also be the point of contact for roof maintenance. We offer a range of PPM (planned preventative maintenance) programmes to support building life cycle costing, as part of an estate's asset management plan.

A well structured maintenance plan can avoid costly reactive repairs and efficiently identify defects that could be detrimental to the long-term performance of the building. This due-diligence will provide added peace of mind to occupants and stakeholders alike.



*Warranties of up to 25 years are available depending on the system build-up components.

**System durability currently under assessment via the BBA.

***Data represents a typical build-up specification compliant to Part L Regulations.

For more information such as installation and product component data, view our Technical Data Sheets.