



**Safety Data Sheet**  
**according to Regulation (EC)**  
**No. 2015/830**

**SECTION 1: Identification of the Substance/Mixture and the Company/Undertaking**

<b>1.1</b>	<b>Product Identifier</b>	10840908	<b>Revision Date:</b>	25/03/2021
	<b>Product Name:</b>	CARBOGUARD E-19 PRIMER PART B	<b>Supersedes Date:</b>	16/02/2021
			<b>Version Number:</b>	2
	<b>UFI Code:</b>	X4D0-N0W3-500T-3RFJ		
<b>1.2</b>	<b>Relevant identified uses of the substance or mixture and uses advised against</b>	Hardener for 2 components coatings - Industrial use. Advised against: Please see Technical Data Sheet.		
	<b>Product to be mixed with:</b>	CARBOGUARD E-19 PRIMER/LT PART A		
	<b>Mixing ratio by volume Part A/ Part B:</b>	2:1		
<b>1.3</b>	<b>Details of the supplier of the safety data sheet</b>			
	<b>Importer:</b>	None		
	<b>Manufacturer:</b>	Carboline Norge AS Postboks 593 3412 Lierstranda Norway		
		Regulatory / Technical Information: +47 32 85 73 00 +47 32 85 74 00		
	<b>Datasheet Produced by:</b>	Chen, Shi - hms@carboline.com		
<b>1.4</b>	<b>Emergency telephone number:</b>	CHEMTREC +1 703 5273887 (Outside US)		

## SECTION 2: Hazard Identification

### 2.1 Classification of the substance or mixture

#### Classification according to Classification, Labeling & Packaging Regulation (EC) 1272/2008

Acute Toxicity, Dermal, category 4  
 Acute Toxicity, Inhalation, category 4  
 Hazardous to the aquatic environment, Chronic, category 2  
 Serious Eye Damage, category 1  
 Flammable Liquid, category 3  
 STOT, repeated exposure, category 2  
 STOT, single exposure, category 3, RTI  
 Skin Irritation, category 2  
 Skin Sensitizer, category 1

#### HAZARD STATEMENTS

Flammable Liquid, category 3	H226
Acute Toxicity, Dermal, category 4	H312
Skin Irritation, category 2	H315
Skin Sensitizer, category 1	H317
Serious Eye Damage, category 1	H318
Acute Toxicity, Inhalation, category 4	H332
STOT, single exposure, category 3, RTI	H335
STOT, repeated exposure, category 2	H373
Hazardous to the aquatic environment, Chronic, category 2	H411

### 2.2 Label elements

#### Symbol(s) of Product



#### Signal Word

Danger

#### Named Chemicals on Label

2-methylpropan-1-ol, ethylbenzene, Triethylenetetramine, xylene, fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids

#### HAZARD STATEMENTS

Flammable Liquid, category 3	H226	Flammable liquid and vapour.
Acute Toxicity, Dermal, category 4	H312	Harmful in contact with skin.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Serious Eye Damage, category 1	H318	Causes serious eye damage.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

**PRECAUTION PHRASES**

P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention
P333+313	If skin irritation or rash occurs: Get medical advice/attention.

**ADDITIONAL INFORMATION**

ADD-04	Due to the viscosity, this product does not present an aspiration hazard.
--------	---

**2.3 Other hazards**

No Information

**Results of PBT and vPvB assessment:**

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

**SECTION 3: Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>EINEC No.</u>	<u>Name According to EEC</u>	<u>%</u>
68082-29-1	500-191-5	fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids	25 - <50
1330-20-7	215-535-7	xylene	25 - <50
78-83-1	201-148-0	2-methylpropan-1-ol	2.5 - <10
100-41-4	202-849-4	ethylbenzene	2.5 - <10
64742-48-9	265-150-3	Naphtha (petroleum), hydrotreated heavy	1.0 - <2.5
112-24-3	203-950-6	Triethylenetetramine	0.1 - <1.0
108-88-3	203-625-9	toluene	0.1 - <1.0

<u>CAS-No.</u>	<u>REACH Reg No.</u>	<u>CLP Symbols</u>	<u>CLP Hazard Statements</u>	<u>M-Factors</u>
68082-29-1		GHS05-GHS07-GHS09	H315-317-318-411	
1330-20-7	01-2119488216-32	GHS02-GHS07-GHS08	H226-304-312-315-319-332-335-373	
78-83-1	01-2119484609-23	GHS02-GHS05-GHS07	H226-315-318-335-336	
100-41-4	01-2119489370-35	GHS02-GHS07-GHS08	H225-304-332-373-412	
64742-48-9	01-2119457273-39	GHS02-GHS08	H226-304	
112-24-3		GHS05-GHS07	H302-312-314-317-412	
108-88-3	01-2119471310-51	GHS02-GHS07-GHS08	H225-304-315-336-361D-373-412	

**Additional Information:** The text for CLP Hazard Statements shown above (if any) is given in Section 16.

**SECTION 4: First-aid Measures****4.1 Description of First Aid Measures**

**GENERAL NOTES:** Show this safety data sheet to the doctor in attendance.

**AFTER INHALATION:** Move to fresh air. Give oxygen or artificial respiration if needed. When risk of unconsciousness, place and transport the victim in secured recovery position. Provide fresh air, rest and warmth. Call a physician immediately.

**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. Do not use solvent or thinners to clean skin.

**AFTER EYE CONTACT:** Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

**AFTER INGESTION:** Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously: Keep head below hips to prevent aspiration of stomach vomit into lungs. Provide fresh air, rest and warmth.

**Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

May cause sensitization by skin contact. Danger of serious damage to health by prolonged exposure. Harmful by inhalation and in contact with skin. Irritating to respiratory system and skin. Vapours may cause drowsiness and dizziness. Causes serious eye damage.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treat symptomatically.

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

When symptoms persist or in all cases of doubt seek medical advice.

## **SECTION 5: Fire-fighting Measures**

**5.1 Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above. Do not use a solid water stream as it may scatter and spread fire.

**5.2 Special hazards arising from the substance or mixture**

Heating or fire conditions liberates toxic gas. Flash back possible over considerable distance. As the product contains combustible organic components, fire will produce dense black smoke containing hazardous products of combustion (see section 10). Vapours may form explosive mixtures with air. Solvent vapours are heavier than air and may spread along floors and ignite.

**5.3 Advice for firefighters**

Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Keep containers and surroundings cool with water spray.

## **SECTION 6: Accidental Release Measures**

**6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

**6.2 Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

**6.3 Methods and material for containment and cleaning up**

Do not let product enter drains. Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents.

**6.4 Reference to other sections**

Please refer to EU disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

## **SECTION 7: Handling and Storage**

**7.1 Precautions for safe handling**

Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. Provide sufficient air exchange and/or exhaust in work rooms. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Open drum carefully as content may be under pressure. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used.

Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

**CONDITIONS TO AVOID:** Avoid heat, sparks, flames and other ignition sources.

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Keep container closed. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Store in upright position only. Storage of flammable liquids. Store away from: oxidising materials, acids, and alkalis.

## 7.3 Specific end use(s)

The mixing and application to be in accordance with the technical data sheets.

# SECTION 8: Exposure Controls/Personal Protection

## 8.1 Control parameters

### Ingredients with Occupational Exposure Limits (EU)

<u>Name</u>	<u>CAS-No.</u>	<u>LTEL ppm</u>	<u>STEL ppm</u>	<u>STEL mg/m3</u>	<u>LTEL mg/m3</u>
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids	68082-29-1				
xylene	1330-20-7	50	100	442	221
2-methylpropan-1-ol	78-83-1				
ethylbenzene	100-41-4	100	200	884	442
Naphtha (petroleum), hydrotreated heavy	64742-48-9				
Triethylenetetramine	112-24-3				
toluene	108-88-3	50	100	384	192

<u>Name</u>	<u>CAS-No.</u>	<u>OEL Note</u>
fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids	68082-29-1	
xylene	1330-20-7	Can be absorbed through the skin.
2-methylpropan-1-ol	78-83-1	Can be absorbed through the skin.
ethylbenzene	100-41-4	Can be absorbed through the skin.
Naphtha (petroleum), hydrotreated heavy	64742-48-9	
Triethylenetetramine	112-24-3	
toluene	108-88-3	Can be absorbed through the skin.

**FURTHER ADVICE:** Refer to the regulatory exposure limits for the workforce enforced in each country. Some components may not have been classified under the EU CLP Regulation. Annotations: Carc = Capable of causing cancer and/or heritable genetic damage, Sen = Capable of causing occupational asthma, Sk = Can be absorbed through the skin.

## 8.2 Exposure controls

### Personal Protection

**RESPIRATORY PROTECTION:** Use compressed air or fresh air breathing apparatus in closed compartments. Wear respiratory protection with combination filter (dust and gas filter, EN 14387:2004+A1:2008) during spraying operations: Gas filter type A2 (organic substances). Dust filter P3 (for fine dust).

**EYE PROTECTION:** Face-shield. Safety glasses with side-shields conforming to EN166.

**HAND PROTECTION:** Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Use chemical resistant gloves and lotions and barrier creams to prevent drying of the skin. Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber. Viton®. Recommended glove material for mixed product: Protective gloves complying with EN 374: Butyl rubber. Nitril rubber.

**OTHER PROTECTIVE EQUIPMENT:** Ensure that eyewash stations and safety showers are close to the workstation location.

**ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

#### Chemical Name:

fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids

**EC No.:**

500-191-5

**CAS-No.:**

68082-29-1

#### DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							0.56 mg/kg bw/day
Inhalation				3.9 mg/m <sup>3</sup>				0.97 mg/m <sup>3</sup>
Dermal				1.1 mg/kg bw/day				0.56 mg/kg bw/day

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.004 mg/L
Fresh water sediments	434.02 mg/kg
Marine water	
Marine sediments	43.4 mg/kg
Food chain	
Microorganisms in sewage treatment	3.84 mg/L
soil (agricultural)	86.78 mg/kg
Air	

#### Chemical Name:

xylene

**EC No.:**

215-535-7

**CAS-No.:**

1330-20-7

#### DNELs - Derived no effect level

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required				174 mg/m <sup>3</sup>	174 mg/m <sup>3</sup>		1.6 mg/kg bw/day
Inhalation	289 mg/m <sup>3</sup>	289 mg/m <sup>3</sup>		77 mg/m <sup>3</sup>				14.8 mg/m <sup>3</sup>
Dermal				180 mg/kg bw/day				108 mg/kg bw/day

#### PNEC's - Predicted no effect concentration

Environmental protection target	PNEC
Fresh water	0.327 mg/L
Fresh water sediments	12.46 mg/kg
Marine water	0.327 mg/L
Marine sediments	12.46 mg/kg
Food chain	
Microorganisms in sewage treatment	6.58 mg/L
soil (agricultural)	2.31 mg/kg
Air	

**Chemical Name:**

2-methylpropan-1-ol

**EC No.:**

201-148-0

**CAS-No.:**

78-83-1

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required						55 mg/m3	25 mg/kg
Inhalation			310 mg/m3					
Dermal								

**PNEC's - Predicted no effect concentration**

PNEC

Environmental protection target	
Fresh water	0,4 mg/l
Fresh water sediments	1,52 mg/kg
Marine water	0,04 mg/l
Marine sediments	0,152 mg/kg
Food chain	
Microorganisms in sewage treatment	10 mg/l
soil (agricultural)	0,0699 mg/kg
Air	

**Chemical Name:**

Naphtha (petroleum), hydrotreated heavy

**EC No.:**

265-150-3

**CAS-No.:**

64742-48-9

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required							300 mg/kg
Inhalation				300 mg/kg				900 mg/m3
Dermal								300 mg/kg

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	
Fresh water sediments	
Marine water	
Marine sediments	
Food chain	
Microorganisms in sewage treatment	
soil (agricultural)	
Air	

**Chemical Name:**

toluene

**EC No.:**

203-625-9

**CAS-No.:**

108-88-3

**DNELs - Derived no effect level**

Route of Exposure	Workers				Consumers			
	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic	Acute effect local	Acute effects systemic	Chronic effects local	Chronic effects systemic
Oral	Not required				226 mg/m3	226 mg/m3	56.5 mg/m3	8.13 mg/kg bw/day
Inhalation	384 mg/m3	384 mg/m3	192 mg/m3	192 mg/m3				56.5 mg/m3
Dermal				384 mg/kg bw/day				226 mg/kg bw/day

**PNEC's - Predicted no effect concentration**

Environmental protection target	PNEC
Fresh water	0.68 mg/L
Fresh water sediments	16.39 mg/kg
Marine water	0.68 mg/L
Marine sediments	16.39 mg/kg
Food chain	
Microorganisms in sewage treatment	13.61 mg/L
soil (agricultural)	2.89 mg/kg
Air	

**SECTION 9: Physical and Chemical Properties****9.1 Information on basic physical and chemical properties**

<b>Appearance:</b>	Colourless
<b>Physical State</b>	Liquid
<b>Odor</b>	Solvent
<b>Odor threshold</b>	Not determined
<b>pH</b>	Not determined
<b>Melting point / freezing point (°C)</b>	Not determined
<b>Boiling point/range (°C)</b>	106 - 144
<b>Flash Point, (°C)</b>	26°C
<b>Evaporation rate</b>	Not determined
<b>Flammability (solid, gas)</b>	Not determined
<b>Upper/lower flammability or explosive limits</b>	1.0 - 10.9
<b>Vapour Pressure, mmHg</b>	Not determined
<b>Vapour density</b>	>1 (air = 1)
<b>Relative density</b>	0.86 - 0.96
<b>Solubility in / Miscibility with water</b>	Negligible
<b>Partition coefficient: n-octanol/water</b>	Not determined
<b>Auto-ignition temperature (°C)</b>	400
<b>Decomposition temperature (°C)</b>	Not determined
<b>Viscosity</b>	440 cSt



**Explosive properties** Not determined

**Oxidising properties** Not determined

## 9.2 Other information

**VOC Content g/l:** 513

**Grams of VOC per liter of coating product as applied per ISO 11890-1 and/or ISO 11890-2.**

**Specific Gravity (g/cm3)** 0.91

## SECTION 10: Stability and Reactivity

### 10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

No reactivity hazards known under normal storage and use conditions.

### 10.4 Conditions to avoid

Avoid heat, sparks, flames and other ignition sources.

### 10.5 Incompatible materials

Keep away from strong oxidising agents and strongly acid or alkaline materials.

### 10.6 Hazardous decomposition products

In case of fire or hot work operations, hazardous decomposition products may be formed such as: Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), aliphatic amines, aldehydes.

## SECTION 11: Toxicological Information

### 11.1 Information on toxicological effects

#### Acute Toxicity:

**Oral LD50:** No information available on the product itself as the product is not tested.

**Inhalation LC50:** No information available on the product itself as the product is not tested.

**Irritation:** No information available.

**Corrosivity:** Causes serious eye damage.

**Sensitization:** May cause an allergic skin reaction.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

**STOT-single exposure:** Vapour/spray mist may irritate respiratory system and lungs.

**STOT-repeated exposure:** Central nervous system depression.

**Aspiration hazard:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested.  
Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>	<u>Gas LC50</u>	<u>Dust/Mist LC50</u>
68082-29-1	fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids	>2000 mg/kg (oral-rat)	No information	No information	No information	No information
1330-20-7	xylene	>2000 mg/kg (oral-rat)	1100 mg/kg (ATE dermal-rabbit)	11 mg/L (ATE inh/vapour)	4500 ppmV (ATE inh - Gas)	1.5 mg/L (ATE inh/dust/mist)
78-83-1	2-methylpropan-1-ol	2830 - 3350 mg/kg (oral-rat)	> 2000 mg/kg (dermal - rabbit)	> 20 mg/L (Inhalation, rat, 6h)	No information	No information
100-41-4	ethylbenzene	3500 mg/kg rat, oral	5510 mg/kg, rabbit	4000 ppm, rat, 4h	10000 ppm	1.5 mg/L
64742-48-9	Naphtha (petroleum), hydrotreated heavy	>5000 mg/Kg (Oral-rat)	>3000 mg/Kg (Dermal-rabbit)	No information	No information	No information
112-24-3	Triethylenetetramine	1716 mg/kg (oral, rat M-F)	1465 mg/kg (dermal, rabbit, M-F)	No information	No information	No information
108-88-3	toluene	5580 mg/kg (oral, rat)	>5000 mg/kg (dermal, rabbit)	28.1 mg/L (4hrs, rat, inhal., vapor)	No information	No information

#### Additional Information:

This product may contain Ethyl Benzene, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. Corrosive - causes irreversible eye damage. Chronic exposure causes drying effect on the skin and eczema. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Gas or vapour is harmful on prolonged exposure or in high concentrations. Irritant of eyes and mucous membranes. CNS depressant. Inhalation is the main hazard in industrial use. The solvent vapours can be harmful and cause headaches, nausea, and intoxication. Acts as a defatting agent on skin. Chronic exposure has been associated with various neurotoxic effects including permanent brain damage. Inhalation of vapour or mist can cause headache, nausea, irritation of nose, throat, and lungs.

## SECTION 12: Ecological Information

### 12.1 Toxicity:

EC50 48hr (Daphnia):	No information
IC50 72hr (Algae):	No information
LC50 96hr (fish):	No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB assessment: The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information

<u>CAS-No.</u>	<u>Name According to EEC</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
68082-29-1	fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids	7.07 mg/L (Daphnia magna)	4.34 mg/L (Pseudokirchneriella supracitata)	7.07 mg/L (zebra fish)

1330-20-7	xylene	165 mg/L (Daphnia magna 24h)	3 - 5 mg/L (Selenastrum sp.)	2 - 11 mg/L (Roccus saxatilis), 8.2 mg/L (Salmo gairdneri), 13.5 mg/L (Lepomis macrochirus), 21.0 mg/L (Pimephales promelas)
78-83-1	2-methylpropan-1-ol	1100 mg/L (Daphnia magna)	1799 mg/L (Scenedesmus subspicatus)	1430 mg/L (Pimephales promelas)
100-41-4	ethylbenzene	1.37 mg/L	No information	32 mg/L (Bluegill)
112-24-3	Triethylenetetramine	31.1 mg/L (Daphnia, EC50, static)	No information	330 mg/L (fish, LC50, static)
108-88-3	toluene	3.78 mg/L (Ceriodaphnia dubia)	10 mg/L OECD Guideline 201 (Algae, Growth Inhibition Test)	5.5 mg/L (Oncorhynchus kisutch)

### SECTION 13: Disposal Considerations

- 13.1 WASTE TREATMENT METHODS:** Do not burn, or use a cutting torch on, the empty drum. According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Empty containers should be taken to an approved waste handling site for recycling or disposal. Rags/wiping cloths and the like, moistened with flammable liquids, must be discarded into designated fireproof buckets. Dispose of waste material at an approved (hazardous) waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems.

**European Waste Code:** 08 01 11\*

**Packaging Waste Code:** 15 01 10\*

### SECTION 14: Transport Information

14.1	UN number	UN1263
14.2	UN proper shipping name	PAINT
	Technical name	Not applicable
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	III
14.5	Environmental hazards	Marine pollutant: Yes (fatty acids, c18-unsatd., dimers, polymers with tall-oil fatty acids)
14.6	Special precautions for user	Not applicable
	EmS-No.:	F-E, S-E
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

### SECTION 15: Regulatory Information

- 15.1 Safety, health and environmental regulations/legislation for the substance or mixture:**

**National Regulations:**

<b>Denmark Product Registration Number:</b>	Not available
<b>Danish MAL Code:</b>	5 - 5
<b>Danish MAL Code - Mixture:</b>	5 - 5
<b>Sweden Product Registration Number:</b>	Not available
<b>Norway Product Registration Number:</b>	P-31564
<b>WGK Class:</b>	

**Covered by Directive 2012/18/EC (Seveso III):** P5c, E2

**Restrictions to product or to substances according to Annex XVII, Regulation (CE) 1907/2006:** Entry 48

#### Annex XIV - Authorisation List:

CAS-No.      Name According to EEC

Not Applicable

#### SVHC - Substances of very high concern (Candidate List):

CAS-No.      Name According to EEC

Not Applicable

#### 15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

### SECTION 16: Other Information

#### Text for CLP Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H361D	Suspected of damaging the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

#### Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet the new EU CLP requirements. There have been both formatting and content changes based on the CLP classification (if applicable), please review each section of the SDS for specific changes. .

#### List of References

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark  
 ESIS (The European Chemical Substances Information System), provided by the European Commission  
 Joint Research Centre in Ispra, Italy  
 Annex VI of the EU Council Directive 67/548/EEC  
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC  
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

## Acronym &amp; Abbreviation Key

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.