



# FR230 Intucompound Fire Mortar Performance Data

**Nullifire**  
Smart Protection

## Performance examples of FR230 Penetration Seals in Rigid Floors 150 mm thick (min.)

Installation	Service	Ancillary Product	Classification
Top Side	Blank Seal	-	EI240
Top Side	100 mm Cable Bundle	FB750 Intubatt	EI240
Top Side	Cable	-	EI240
Top Side	Cable Ladder	-	EI240
Top Side	Cable Tray	-	EI240
Top Side	Combustible Pipe Ø160	FP302 Intustrap	EI240
Top Side	Composite Multilayer Pipe Ø90	FP302 Intustrap	EI240
Top Side	Insulated Non-Combustible Pipe Ø14	FP160 Intusleeve	EI240

## Performance examples of FR230 Penetration Seals in Rigid Walls 100 mm thick (min.)

Installation	Service	Ancillary Product	Classification
Full Width	Cable	-	EI240
Full Width	Cable Ladder	-	EI240
Full Width	Insulated Non-Combustible Pipe Ø15	FP302 Intustrap	EI240
Full Width	Insulated Non-Combustible Pipe Ø170	FI140 Intuflex	EI180

## Performance examples of FR230 Linear Joint Seals in Rigid Walls 150 mm thick (min.)

Installation	Installation	Seal Depth (mm)	Classification		
			Integrity & Insulation	Application & Usage	Gap Width Range
AAC-AAC	Fire Side	50	EI120	T – X – F	W 5-50