

Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: TREMCO RW413 B
- · MSDS code: W-T-RW413B
- \cdot 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Priming
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@cpg-europe.com

· Further information obtainable from:

Tremco CPG UK Ltd

Coupland Road, Hindley Green, Wigan, WN2 4HT

T: +44 (0) 1942251400, F: +44 (0) 1942251410

www.cpg-europe.com, info.uk@cpg-europe.com

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 1)

Hazard pictograms











GHS02 GHS05 GHS07 GHS08 GHS09

· Signal word Danger

· Contains:

Fatty acids, C18-unsaturated, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

xylene

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

Wear protective gloves/protective clothing/eye protection/face protection. P280

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403+P235 Store in a well-ventilated place. Keep cool.

Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with non-hazardous additions.

(Contd. on page 3)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

	(Con	td. of page 2)	
· Dangerous components:			
CAS: 68082-29-1 NLP: 500-191-5	Fatty acids, C18-unsaturated, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1B, H317	50-<75%	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-xxxx	xylene Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	20-<30%	
CAS: 90-72-2 EINECS: 202-013-9	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2, H319	5-<10%	
CAS: 100-41-4 EINECS: 202-849-4	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332	1-<5%	
CAS: 108-88-3 EINECS: 203-625-9	toluene Flam. Liq. 2, H225; Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Chronic 3, H412	0.1-<1%	

[•] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out of danger area and lay down.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- · Information for doctor: No further relevant information available.
- · 4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes, respiratory system and skin.

Risk of serious damage to eyes.

May cause an allergic skin reaction.

Coughing

Nausea

· **Hazards** No further relevant information available.

(Contd. on page 4)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 3)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour.

Formation of toxic gases is possible during heating or in case of fire.

Carbon dioxide (CO2)

Carbon monoxide (CO)

Nitrogen oxides (NOx)

Under certain fire conditions, traces of other toxic gases cannot be excluded.

- 5.3 Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

· Additional information

Cool endangered receptacles with water spray.

Do not allow water to get inside the containers.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear protective equipment. Keep unprotected persons away.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste according to Section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

The usual precautionary measures are to be adhered to when handling chemicals.

Ensure good ventilation/exhaustion at the workplace.

Use only in well-ventilated areas.

(Contd. on page 5)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 4)

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

- · Information about fire and explosion protection: Flammable liquid and vapour.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store only in unopened original receptacles.
- · Information about storage in one common storage facility: Protect from heat and direct sunlight.
- Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Storage temperature: +5°C to +25°C

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk: BMGV

CAS: 100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

CAS: 108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm

Long-term value: 191 mg/m³, 50 ppm

Sk

Ingredients with biological limit values:

CAS: 1330-20-7 xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

Additional information:

The lists valid during the making were used as basis.

HSE EH40/2005 Workplace Exposure Limits (as amended)

- · 8.2 Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Do not eat, drink, smoke or sniff while working.

(Contd. on page 6)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 5)

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not breathe vapour/spray.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Short term filter device:

Filter ABEK2/P3

Ensure good ventilation/exhaustion at the workplace.

Take note of emission threshold.

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Butyl rubber, BR

PVA gloves

Impervious gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

Body protection:



Protective work clothing

– GE

(Contd. on page 7)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 6)

SECTION 9: Physical and ch	emical properties	
9.1 Information on basic physical General Information	l and chemical properties	
Appearance:		
Form:	Liquid	
Colour:	Clear	
Odour:	Characteristic	
pH-value:		
Initial boiling point and boiling	range: 37 °C	
Flash point:	27 °C	
Ignition temperature:	>340 °C	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	e properties: Product is not explosive. However, formation of explosive vapour mixtures are possible.	
Explosion limits:		
Lower:	1.0 Vol %	
Upper:	7.1 Vol %	
Density at 20 °C:	0.91 g/cm³	
Solubility in / Miscibility with		
water:	Insoluble.	
Viscosity:		
Kinematic at 40 °C:	>20.5 mm²/s	
9.2 Other information No further relevant information available.		

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions

Reacts with water.

Reacts with acids, alkalis and oxidising agents.

- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide and carbon dioxide

(Contd. on page 8)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

Nitrogen oxides (NOx)

(Contd. of page 7)

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
CAS: 1330	CAS: 1330-20-7 xylene		
Dermal	ATE	1,100 mg/kg (unknown)	
CAS: 90-7	CAS: 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol		
Oral	LD50	2,169 mg/kg (rat)	
	NOAEL	15 mg/kg (rat)	
CAS: 100-41-4 ethylbenzene			
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	17,800 mg/kg (rabbit)	
CAS: 108-88-3 toluene			
Oral	LD50	5,000 mg/kg (rat)	
Dermal	LD50	12,124 mg/kg (rabbit)	
Inhalative	LC50/4 h	5,320 mg/L (mouse)	

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information: Irritating to eyes, respiratory system and skin.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

May cause respiratory irritation.

- · STOT-repeated exposure
- May cause damage to organs through prolonged or repeated exposure.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability Not easily biodegradable

(Contd. on page 9)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 8)

- 12.3 Bioaccumulative potential Low potential for bioaccumulation.
- 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- Additional ecological information:
- · General notes:

Toxic for aquatic organisms

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage

- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Disposal must be made according to official regulations.

· European	European waste catalogue	
08 01 11*	1* waste paint and varnish containing organic solvents or other hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP6	Acute Toxicity	
HP13	Sensitising	
HP14	Ecotoxic	

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning. Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

· 14.1	UN-Numb	er
--------	----------------	----

· ADR, IMDG, IATA UN1263

· 14.2 UN proper shipping name

· ADR 1263 PAINT, ENVIRONMENTALLY HAZARDOUS

· IMDG PAINT, MARINE POLLUTANT

(Contd. on page 10)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B		
	(Contd. of page 9)	
· IATA	PAINT	
· 14.3 Transport hazard class(es)		
· ADR		
¥2		
· Class	3 (F1) Flammable liquids.	
· Label	3	
· IMDG		
Class	3 Flammable liquids.	
· Label	3	
IATA		
Class	3 Flammable liquids.	
· Label	3	
· 14.4 Packing group · ADR, IMDG, IATA	III	
· 14.5 Environmental hazards:	Product contains environmentally hazardous substances: Fatty acids, C18-unsaturated, dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	
· Marine pollutant:	Symbol (fish and tree)	
· Special marking (ADR):	Symbol (fish and tree)	
· 14.6 Special precautions for user · Hazard identification number (Kemler code):	Warning: Flammable liquids. 30	
EMS Number:	F-E,S-E	
Stowage Category	A -, <u>-=</u>	
· 14.7 Transport in bulk according to Annex II o Marpol and the IBC Code	f Not applicable.	

(Contd. on page 11)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 10)

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3
· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 1263 PAINT, 3, III, ENVIRONMENTALLY

HAZARDOUS

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015) "GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 48
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

(Contd. on page 12)



Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

(Contd. of page 11)

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

CAS: 108-88-3 toluene

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

CAS: 108-88-3 toluene

3

- · National regulations:
- · Information about limitation of use: Employment restrictions concerning juveniles must be observed.
- · Other regulations, limitations and prohibitive regulations No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

Department issuing SDS:

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 13)



(Contd. of page 12)

Printing date 25.08.2022 Version number 1 Revision: 25.08.2022

Trade name: TREMCO RW413 B

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation – Category 1 Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

- GB