

DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

TREMCO
Lasting Performance

No. CS375 – 20170912

- 1. Unique identification code of the product-type:** CS375
- 2. Intended use/es:** Cement screed material for use internally in buildings – EN 13813:2002
- 3. Manufacturer:** TREMCO CPG UK Limited, Coupland Road, Hindley Green, Wigan, WN2 4HT
- 5. System/s of AVCP:** System 4 (for internal uses)
- 6a. Harmonised standard:** EN 13813:2002 (CT-C35-F9)-AR2

Notified body/ies: Not relevant

7. Declared performance/s:

EN 13813:2002 (Cement screed material for use internally in buildings (wearing surfaces))

| Essential Characteristic | Performance | Harmonised Technical Specification |
|---------------------------------|-------------|------------------------------------|
| Release of corrosive substances | CT | EN 13813:2002 |
| Compressive strength | C35 | EN 13813:2002 |
| Flexural strength | F9 | EN 13813:2002 |
| Wear Resistance | AR2 | EN 13813:2002 |
| Reaction to fire | BFL-s1 | EN 13813:2002 |
| Water Permeability | NPD | EN 13813:2002 |

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

M. Liptrot, Operations Director

At Wigan on 1 July 2020



Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

DECLARATION OF PERFORMANCE

ACCORDING TO ANNEX III OF THE REGULATION (EU) N° 305/2011

TREMCO

| CE | |
|---|-------------|
| tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 17 CS375 – 20170912 tremco-europe.com/CS375/ | |
| EN 13813:2002 Cement screed material for use internally in buildings (non-wearing surfaces) | |
| Essential Characteristic | Performance |
| Release of corrosive substances | CT |
| Compressive strength | C35 |
| Flexural strength | F9 |
| Wear Resistance | AR2 |
| Reaction to Fire | BFL –s1 |
| Water Permeability | NPD |