

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### · 1.1 Product identifier

· Trade name: illbruck AT200

· MSDS code: T-I-AT200

#### · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· **Application of the substance / the mixture** Cleaning agent / Cleaner

#### · 1.3 Details of the supplier of the safety data sheet

##### · Manufacturer/Supplier:

Tremco CPG Germany GmbH  
Zweigniederlassung Traunreut  
Traunring 65, D - 83301 Traunreut  
Tel: +49 (0) 8669 34100, Fax: +49 (0) 8669 9784  
msds@cpg-europe.com

##### · Further information obtainable from:

Tremco CPG UK Ltd  
Coupland Road, Hindley Green, Wigan, WN2 4HT  
T: +44 (0) 1942251400, F: +44 (0) 1942251410  
www.cpg-europe.com, info.uk@cpg-europe.com

#### · 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 1942251400. At all other times it is recommended to call NHS 111 (England/Wales/Scotland), your local GP/pharmacist (NI), 01 809 2166 (ROI), or otherwise to contact a doctor.

### SECTION 2: Hazards identification

#### · 2.1 Classification of the substance or mixture

##### · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

#### · 2.2 Label elements

##### · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

##### · Hazard pictograms



GHS02 GHS07

##### · Signal word Danger

(Contd. on page 2)

GB

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 1)

- **Contains:**

acetone

- **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- **Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.

P261 Avoid breathing vapours.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

- **Supplemental information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

### SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**

- **Description:** Solvent mixture

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2219471330-49-xxxx	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336, EUH066	75-<100%
CAS: 1330-20-7 EC number: 918-167-1 Reg.nr.: 01-2119488216-32-xxxx	xylene (mix) Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	5-<10%
CAS: 100-41-4 EINECS: 202-849-4 Reg.nr.: 01-2119489370-35-xxxx	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332	1-<5%

- **SVHC -**

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

GB

(Contd. on page 3)

# Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 2)

## SECTION 4: First aid measures

### · 4.1 Description of first aid measures

#### · General information:

Take affected persons out of danger area and lay down.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

#### · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:** Do not induce vomiting; call for medical help immediately.

· **Information for doctor:** No further relevant information available.

### · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· **Hazards** No further relevant information available.

### · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

### · 5.1 Extinguishing media

#### · Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** Water with full jet

· **5.2 Special hazards arising from the substance or mixture** No further relevant information available.

### · 5.3 Advice for firefighters

· **Protective equipment:** Wear self-contained respiratory protective device.

· **Additional information** Cool endangered receptacles with water spray.

## SECTION 6: Accidental release measures

### · 6.1 Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation.

Wear protective equipment. Keep unprotected persons away.

### · 6.2 Environmental precautions:

Prevent from spreading (e.g. by damming-in or oil barriers).

Keep contaminated washing water and dispose of appropriately.

Do not allow to enter sewers/ surface or ground water.

### · 6.3 Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of the material collected according to regulations.

(Contd. on page 4)

GB

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 3)

**6.4 Reference to other sections**

- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

**SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
  - Keep ignition sources away - Do not smoke.
  - Fumes can combine with air to form an explosive mixture.
  - Protect against electrostatic charges.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
  - Store in cool, dry conditions in well sealed receptacles.
  - Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Ingredients with limit values that require monitoring at the workplace:****CAS: 67-64-1 acetone**

WEL	Short-term value: 3620 mg/m <sup>3</sup> , 1500 ppm Long-term value: 1210 mg/m <sup>3</sup> , 500 ppm
-----	--

**CAS: 1330-20-7 xylene (mix)**

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

**CAS: 100-41-4 ethylbenzene**

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

**PNECs****CAS: 67-64-1 acetone**

PNEC	100 mg/L (sewage treatment plant) 10.6 mg/L (sediment (fresh water)) 1.06 mg/L (salt water)
PNEC	29.5 mg/kg (soil)

(Contd. on page 5)

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 4)

	3.04 mg/kg (sediment (salt water))
	30.4 mg/kg (sediment (fresh water))

· **Ingredients with biological limit values:**

**CAS: 1330-20-7 xylene (mix)**

BMGV	650 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**

· **Appropriate engineering controls** No further data; see item 7.

· **Individual protection measures, such as personal protective equipment**

· **General protective and hygienic measures:**

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Do not eat, drink, smoke or sniff while working.

Avoid contact with the eyes and skin.

Do not inhale gases / fumes / aerosols.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Not necessary if room is well-ventilated.

Filter AX

For further guidance,

please refer to HSE HSG53 "Respiratory Protective Equipment at work - A Practical Guide".

· **Hand protection**



Protective gloves

Solvent resistant gloves

· **Material of gloves**

Butyl rubber, BR

Recommended thickness of the material:  $\geq 0.5$  mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

Trade name: illbruck AT200

(Contd. of page 5)

- **Eye/face protection**



Tightly sealed goggles

- **Body protection:**



Protective work clothing

### SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

· <b>Physical state</b>	Fluid
· <b>Colour:</b>	Colourless
· <b>Odour:</b>	Like ketone
· <b>Odour threshold:</b>	Not determined.
· <b>Melting point/freezing point:</b>	Undetermined.
· <b>Boiling point or initial boiling point and boiling range</b>	56 °C
· <b>Flammability</b>	Highly flammable.
· <b>Lower and upper explosion limit</b>	
· <b>Lower:</b>	1.1 Vol % (CAS: 1330-20-7 xylene (mix))
· <b>Upper:</b>	13 Vol % (CAS: 67-64-1 acetone)
· <b>Flash point:</b>	-18 °C
· <b>Ignition temperature:</b>	465 °C
· <b>Decomposition temperature:</b>	Not determined.
· <b>pH</b>	Mixture is non-polar/aprotic.
· <b>Viscosity:</b>	
· <b>Kinematic viscosity</b>	Not determined.
· <b>Solubility</b>	
· <b>water:</b>	Fully miscible.
· <b>Partition coefficient n-octanol/water (log value)</b>	Not determined.
· <b>Vapour pressure at 20 °C:</b>	233 hPa (CAS: 67-64-1 acetone)
· <b>Density and/or relative density</b>	
· <b>Density at 20 °C:</b>	0.8 g/cm <sup>3</sup>
· <b>Relative density</b>	Not determined.
· <b>Vapour density</b>	Not determined.

(Contd. on page 7)

GB

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 6)

**· 9.2 Other information****· Appearance:****· Form:** Fluid**· Important information on protection of health and environment, and on safety.****· Auto-ignition temperature:** Product is not selfigniting.**· Explosive properties:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.**· Solvent content:****· Organic solvents:** 100.0 %**· VOC (EU)** 100.00 %

800.0 g/l

**· VOC (EC)** 100.00 %**· Evaporation rate** Not determined.**· Information with regard to physical hazard classes****· Explosives** Void**· Flammable gases** Void**· Aerosols** Void**· Oxidising gases** Void**· Gases under pressure** Void**· Flammable liquids** Highly flammable liquid and vapour.**· Flammable solids** Void**· Self-reactive substances and mixtures** Void**· Pyrophoric liquids** Void**· Pyrophoric solids** Void**· Self-heating substances and mixtures** Void**· Substances and mixtures, which emit flammable gases in contact with water** Void**· Oxidising liquids** Void**· Oxidising solids** Void**· Organic peroxides** Void**· Corrosive to metals** Void**· Desensitised explosives** Void**SECTION 10: Stability and reactivity****· 10.1 Reactivity** No further relevant information available.**· 10.2 Chemical stability****· Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**· 10.3 Possibility of hazardous reactions** No dangerous reactions known.**· 10.4 Conditions to avoid** No further relevant information available.

(Contd. on page 8)

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

Trade name: illbruck AT200

(Contd. of page 7)

- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** None if stored according to specifications.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

#### · LD/LC50 values relevant for classification:

##### CAS: 67-64-1 acetone

Oral	LD50	5,800 mg/kg (rat) (OECD 401)
Dermal	LD50	20,000 mg/kg (rabbit) (OECD 402)
Inhalative	LC0/4 h	16,000 ppm (rat)
	LC50/4 h	76 mg/L (rat)

##### CAS: 1330-20-7 xylene (mix)

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	27.6 mg/L (rat)

##### CAS: 100-41-4 ethylbenzene

Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation**  
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**  
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** Repeated exposure may cause skin dryness or cracking.
- **11.2 Information on other hazards**

#### · Endocrine disrupting properties

None of the ingredients is listed.

GB

(Contd. on page 9)

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

Trade name: illbruck AT200

(Contd. of page 8)

### SECTION 12: Ecological information

#### · 12.1 Toxicity

##### · Aquatic toxicity:

##### CAS: 67-64-1 acetone

LC50/96 h	5,540 mg/L (oncorhynchus mykiss)
	7,500 mg/L (leuciscus idus)
EC50/48 h	6,100 mg/L (daphnia magna)
IC50/8 d	7,500 mg/L (scenedesmus quadricauda)

##### CAS: 1330-20-7 xylene (mix)

LC50/96 h	3.77 mg/L (fish)
EC50/48 h	7.4 mg/L (daphnia magna)
EC50/72 h	10 mg/L (skeletonema costatum)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**  
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **General notes:**  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.

### SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

##### · European waste catalogue

08 04 99	wastes not otherwise specified
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

(Contd. on page 10)

GB

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

Trade name: illbruck AT200

(Contd. of page 9)

- **Uncleaned packaging:**

- **Recommendation:**

Empty packages totally (without drops or grains, cleaned with a spatula). Under observation of the relevant local respectively national regulations re-use or recycling is preferred.

### SECTION 14: Transport information

- **14.1 UN number or ID number**

- **ADR, IMDG, IATA** UN1993

- **14.2 UN proper shipping name**

- **ADR** 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE)  
1993 ENTZÜNDBARER FLÜSSIGER STOFF,  
N.A.G. (ACETON)
- **IMDG, IATA** FLAMMABLE LIQUID, N.O.S. (ACETONE)

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 3 (F1) Flammable liquids.

- **Label** 3

- **IMDG, IATA**



- **Class** 3 Flammable liquids.

- **Label** 3

- **14.4 Packing group**

- **ADR, IMDG, IATA** II

- **14.5 Environmental hazards:**

- **Marine pollutant:** No

- **14.6 Special precautions for user**

Warning: Flammable liquids.

- **Hazard identification number (Kemler code):** 33

- **EMS Number:** F-E,S-E

- **Stowage Category** B

- **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

(Contd. on page 11)

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 10)

**· Transport/Additional information:****· ADR****· Limited quantities (LQ)**

1L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· Transport category**

2

**· Tunnel restriction code**

D/E

**· IMDG****· Limited quantities (LQ)**

1L

**· Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

**· UN "Model Regulation":**UN 1993 FLAMMABLE LIQUID, N.O.S.  
(ACETONE), 3, II**SECTION 15: Regulatory information****· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

HSE EH40/2005 Workplace Exposure Limits (as amended)

Guidance on the classification and assessment of waste | Technical Guidance WM3 (1st edition 2015)

"GB- CLP" UK SI 2019 No. 720 The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019

"UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

**· Directive 2012/18/EU****· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5.000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50.000 t**· REGULATION (EC) No 1907/2006 ANNEX XVII** Conditions of restriction: 3**· DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II**

None of the ingredients is listed.

**· REGULATION (EU) 2019/1148****· Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))**

None of the ingredients is listed.

**· Annex II - REPORTABLE EXPLOSIVES PRECURSORS**

CAS: 67-64-1 | acetone

(Contd. on page 12)

GB

## Safety data sheet

acc. (EC) 1907/2006, as amended by UK SI 2019/758

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 11)

· <b>Regulation (EC) No 273/2004 on drug precursors</b>		
CAS: 67-64-1	acetone	3

· <b>Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors</b>		
CAS: 67-64-1	acetone	3

- **National regulations:**

- **Other regulations, limitations and prohibitive regulations** No further relevant information available.

- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

- **Department issuing SDS:**

Prepared and verified in accordance with Annex II, Part A, 0.2.3. of "UK- REACH" UK SI 2019 No. 758 The UK REACH etc. (Amendment etc.) (EU Exit) Regulations 2019

- **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 13)

**Safety data sheet**  
**acc. (EC) 1907/2006, as amended by UK SI 2019/758**

Printing date 01.12.2022

Version number 20 (replaces version 19)

Revision: 01.12.2022

**Trade name: illbruck AT200**

(Contd. of page 12)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

GB