

SF550

GUN GRADE FLEXIBLE WOOD ADHESIVE

PRODUCT INFORMATION

Description

A high strength, flexible, single component advanced polymer adhesive for surface bonding most wood flooring. Packed in a handy 600 ml sausage for edge work or general usage.

Usage/Purpose

For bonding most types of wood flooring including wood blocks, wood mosaic panels, engineered, laminated and solid wood plank/strip flooring.

Use over most common substrates, sand/cement screeds, concrete, calcium sulphate screeds, stone, metal, timber and epoxy membranes.

For other surfaces please consult Technical Services for suitability.

Compatible with most underfloor heating systems. Consult Technical Services for confirmation.

Colour

Buff / brown

Packaging

Available in boxes of 12 x 600 ml foil sausages.

Standards

All aspects of the installation must be in accordance with the requirements of BS 8204, BS 8203 (Installation of Resilient Floor Coverings) or BS 5325 (Installation of Textile Floor Coverings) and supplementary specifications.

Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Preparation

- All phases of installation should comply with BS 8201, BS 8203, CP 102 and / or other local installation standards and codes of practice.

SUBFLOOR

- Ensure the subfloor is flat, clean, sound and dry and free from contaminants that may hinder adhesion, this includes paint, varnish, polish, old adhesive residues and plaster spots.
- Existing wooden subfloors must have an intact base DPM.
- The subfloor should be tested in accordance with British Standards, using a properly calibrated and insulated hygrometer.
- A reading of 75% RH or less confirms that the subfloor is satisfactorily dry. Where this has not been attained, it is necessary to apply a TREMCO surface membrane to suppress residual moisture. For further information contact Technical Services.
- Ensure the timber is acclimatised in accordance to the manufacturer's instructions in the environment in which it is to be laid.
- Always allow an expansion gap around any perimeters or columns to allow for natural movement of the wood when bonded.

SMOOTHING COMPOUNDS

- Mechanically remove all surface treatments on concrete bases.
- Repair any deep indentations in the subfloor with TREMCO SX400 Cementitious Repair Mortar.
- Lightly abrade calcium sulphate to remove any surface laitance. Always prime before applying a suitable TREMCO smoothing compound to calcium sulphate screeds.
- Apply a suitable TREMCO smoothing compound at a minimum thickness of 3 mm.
- See relevant technical data sheet for full information.

EXISTING FLOOR COVERINGS

- Not recommended for use over existing floor coverings.



KEY BENEFITS SUMMARY

- Strong and flexible
- Permanently elastic bond
- Solvent free and moisture free
- Compatible with most underfloor heating systems

Priming

- Ensure substrate is suitable for the adhesive before application. Very porous substrates can be primed with CS150 Acrylic Primer. Contact Tremco CPG UK Limited Customer Services for details.

Application

- Cut off tip of sausage and place into suitable cartridge. Cut off top of nozzle flat to leave an 8 mm opening. Cut a 'V' shaped profile down into nozzle to a depth of approximately approx 10 mm. Fix nozzle and place cartridge containing sausage in sealant gun.
- Hold gun at 90° to floor and extrude out a triangular shaped bead, approx 8 mm wide and 10 mm high at approximately 250 mm centres at right angles to the length of the plank.
- Press firmly or gently tap the wood into the adhesive to ensure good overall contact. Where necessary use heavy objects to hold the wood firmly in place during curing time.
- The bonded wood will be suitable to take foot traffic 6 to 8 hours after application. It should be left for 48 hours before sanding or varnishing takes place.

Cleaning

Use water immediately after use.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Availability

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details), or via local and national distributors.

TECHNICAL DATA

PROPERTY	RESULT
Composition	SF550 Gun Grade Flexible Wood Adhesive is formulated from advanced polymer technology
Open Time/Workability (at +20°C)	Approximately 20 minutes
Application Temperature Range	+4°C to +30°C
Service Temperature	-20°C to +60°C
Coverage	One 600 ml sausage will bond approximately 2 m ² of flooring when applied as directed
Storage	Store in dry conditions between +5°C and +25°C
Shelf Life	12 months from manufacturing date, when stored as recommended in original unopened containers

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee/Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

Tremco CPG UK Limited Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



Tremco CPG UK Limited - A Company approved to: