



Lasting Performance

Contract Flooring Solutions

High Performance Products
for the Flooring Professional

Damp Proof
Membranes

Floor Smoothing
Compounds

Flooring
Adhesives



For more than 75 years, TREMCO has been the UK's preferred choice for flooring solutions. Providing UK flooring specialists with fully compatible systems, we pride ourselves on remaining innovative and ecological.

Tremco flooring products are high-quality solutions suitable for new installs or refurbishments projects for all types of floor coverings. Recognising the need for peace of mind, Tremco offers more than just products. Our specialised flooring team are on hand to talk you through your technical enquiries, choosing the right Tremco system for you, or simply just directing you to one of our approved distributors across the UK.

Tremco stands for lasting performance and is a brand of Tremco Construction Products Group, a European manufacturer and service provider of high-quality building materials. Leaders in product areas such as epoxy damp proof membranes, single coat membranes and pressure sensitive flooring adhesives, our products will help you achieve the results you are looking for.

Contents

Damp Proof Membranes	4-6
Primers	7-9
Smoothing Compounds	10-13
Adhesives	14-17
Tapes	17
Technical Services	18-19
Accessories	20-21
Tremco CPG brands	22-23



Damp Proof Membranes

The Founder of Damp Proof Membranes

The installation of a liquid damp proof membrane is a vital stage of any construction project, with Tremco being the founder of Damp Proof Membranes in the market, we know what your projects require.

What does a DPM do?

A surface DPM, which bonds to the surface of the concrete, minimises moisture vapour transmission. It, therefore, prevents moisture build-up beneath vinyl or other floor coverings. To choose the most suitable and cost-effective DPM for any application, it is essential to determine the relative humidity and the moisture vapour transmission rate of the substrate and floor covering.

ES100 One Coat Universal DPM is the market-leading epoxy damp proof membrane in the UK and a single coat accommodates up to 97% relative humidity (RH).

Epoxy Based



ES100

ONE COAT UNIVERSAL DPM

ES100 is a two-part, epoxy-based damp proof membrane. ES100 has been developed specifically for residual moisture in concrete and sand/cement subfloors and provides a guaranteed surface damp proof membrane with a single coat liquid application. ES100 can also be used on calcium sulphate screeds without underfloor heating in a single coat application up to 87% RH.

- Accommodates up to 97% RH
- Solvent-free
- Suitable with underfloor heating
- Cost-effective, single coat application reducing time on site

Coverage: Up to 24m² per 10kg unit and up to 60m² per 25kg unit

ES200

FAST CURING UNIVERSAL DPM



ES200 is a solvent free, two-part, epoxy-based damp proof membrane which achieves emicode EC1 status. Developed specifically for suppressing residual moisture in concrete and sand/cement subfloors and it guarantees a surface damp proof membrane with a single coat liquid application.

- Accommodates up to 97% RH
- Very cost-effective single coat application reducing time on site
- Suitable with underfloor heating
- Cures in half the time of conventional epoxy-based surface damp proof membrane

Coverage: Up to 15m² per 6kg unit



ES600

MOISTURE VAPOUR SUPPRESSANT

ES600 is a ready for use, one-part, water-based moisture vapour suppressant. This surface moisture vapour suppressant has been developed to suppress residual construction moisture in cementitious subfloors including power-floated concrete and sand/cement screeds.

- Rapid drying – approximately 1 hour to 20°C
- Easy to apply, primerless application and single component, no mixing required
- Suitable for heated concrete and sand-cement screeds (provided the surface temperature does not exceed 27°C in accordance with BS 8203 and BS 5325)
- Water-based, low VOC compliant

Coverage: Up to 16m² per 5kg unit for 2 coats



ES500

SHEET MEMBRANE

ES500 is a specially coated fibreglass underlay and acts as a continuous barrier substrate, is moisture resistant to damp with resin peduncles on the underside. Can be installed onto sand cement screeds and concrete with a structural DPM included in the construction up to a moisture content of 97% RH (99.9% theoretically).

- No VOC's
- Reduced weight per square metre for easier handling
- Suitable for heated concrete and sand-cement screeds (provided the surface temperature does not exceed 27°C in accordance with BS 8203 and BS 5325)
- Cuts down installation time as it can be installed over damp and contaminated substrates

Coverage: Per role 40m²



CS100

EPOXY PRIMER FOR NON-POROUS SUBSTRATES

CS100 is a two-part, water-based epoxy primer designed to prime TREMCO surface damp proof membranes and other non-porous surfaces, prior to the application of a smoothing compound. Specifically formulated for interior use on smooth or dense surfaces such as – power-floated concrete, precast concrete, terrazzo, glazed ceramic tiles or hard flooring grade asphalt.

- Excellent adhesion to a wide range of substrates
- Easy to apply
- Improves substrate chemical resistance
- Solvent-free

Coverage: Approx. 100m² per kg unit



CS150

ACRYLIC PRIMER

A universal primer for porous substrates, typically used prior to the application of smoothing compounds. CS150 removes the adverse effects of suction from the substrate including pin-holing and premature drying of the screed, helping prevent the loss of flow characteristics

- Easy to apply
- Helps to prevent pin-holing
- Helps maintain the flow characteristics of the screed

Coverage: Approx. 40m² per 5 litre unit or 200m² per 25 litre unit



CS175

EPOXY PRIMER FOR POROUS SUBSTRATES

A two-part, water-based epoxy primer that provides a breathable seal for calcium sulphate screeds, prior to the installation of cementitious substrates, brick, and blockwork. CS175 is also suitable for use as a primer on concrete prior to the application of floor coatings.

- Excellent coverage
- Low viscosity
- Consolidates weak surfaces
- Floor coverings may be applied directly when using a suitable adhesive

Coverage: Approx. 75m² per 7.5kg unit



CS190

GRITTY PRIMER

CS190 Gritty Primer is a ready-mixed, ready to use rapid drying primer that can be used on both, absorbent and non-absorbent substrates. CS190 provides a textured surface that gives an excellent bonding surface for self-levelling/smoothing compounds, and screeds. It is suitable for use on a wide range of substrates, including existing ceramic, porcelain and natural stone tiles, existing vinyl flooring, flooring grade asphalt and bitumen, epoxy DPMS, plaster, metal, fibreglass, concrete, sand/cement screed, timber substrates and underfloor heating systems.

- Provides an excellent key and extra grip surface
- Rapid drying – in as little as 15 minutes
- Ready-mixed and ready to use, apply straight from the resealable tub
- Significantly improves adhesion and bond strength of tile adhesives and smoothing compounds

Coverage: Approx. 45–65m² depending on porosity of the substrate and ambient temperature



Floor Smoothing Compounds

Advanced Technology Systems

Tremco continues to develop smoothing compounds using the latest technology, including new shrinkage control systems, new flow systems and low emission polymers. We pride ourselves in the continuous research and development of our products - and have many more innovations on the way. The range of smoothing compounds include:

Two-Part Latex Underlayments

General-purpose, high performance, and damp tolerant grades.

Water-Mixed Underlayments

Hand or pump applied for heavy-duty applications. Repair Compounds – patch repair and feather edge repair compounds for specialist applications.

Specialist Floor Screeds

We offer a fibre-filled pumpable underlayment for flexing subfloors or difficult substrates.

Water Based

SX100

RENOVATION SCREED

A fibre reinforced, cementitious self-levelling flooring compound for interior application, prior to the installation of floor coverings which works over a range of problem substrates including concrete, sand/cement, steel, wood, ceramic tile, quarry tile, plywood, and old vinyl tiles. SX100 has excellent flow and smoothing properties. With an application range of 5mm–50mm, it can be applied by hand or suitable pump. With compressive strengths of more than 30 N/mm², it can also be used in heavy-duty applications.

- Fast application and minimum downtime
- Contains special fibres to give excellent crack resistance
- Suitable for laying over existing floor finishes such as tiles and flooring grade mastic asphalt
- Suitable with underfloor heating systems (minimum cover of 25mm over pipes)

Coverage: Approx. 5m² per 25kg unit at 3mm



SX200

SELF-LEVELLING SMOOTHING COMPOUND

A fast drying self levelling, pump applied underlayment, for levelling of concrete floors before the installation of floor coverings. Provides good resistance to impact, point loading and abrasion. SX200 has an ultimate compressive strength of 33 N/mm² and is ideally suited to floors in public buildings such as schools, hospitals airports and shops.

- Fast setting and drying - walk on after 2-4 hours under suitable conditions
- Rapid installation - 2000 m² per day for 7mm thickness, under suitable conditions
- Protein free - will not harbour bacteria

Coverage: An average thickness of 3mm will provide a typical coverage rate of 5 m² per mix





SX300^{NA}

HIGH PERFORMANCE LATEX UNDERLAYMENT

A two-part general purpose smoothing underlayment. SX300NA is specifically designed for the preparation and smoothing of interior subfloors prior to the application of a liquid applied damp proof membrane and receiving a floor covering. With a compressive strength of 21.9 N/mm² SX300NA has a walk on time of 2-4 hours and 8-12 hours for application of DPM, floor covering or loading.

- Water resistant: can be used for pre-smoothing
- Excellent adhesion to a wide range of common flooring substrates and self priming on most surfaces
- Short setting and cure time, facilitating fast track programs and minimising disruption
- Low odour and protein free

Coverage: Approx. 5m² per unit at 3mm

SX302

MOISTURE TOLERANT LATEX UNDERLAYMENT



A general-purpose latex underlayment with a high degree of moisture tolerance for use prior to the application of a liquid applied damp proof membrane. Also, for use on dry floors, minimised adhesive residues or on top of primed damp proof membranes prior to the installation of floor coverings. SX302 has a compressive strength of 25 N/mm² and can be laid in thicknesses of 1–10mm.

- May accept foot traffic after approximately 90 minutes
- Moisture tolerant for use under surface damp proof membranes
- Easy to mix and apply, a smooth surface is produced
- Extremely low odour with no unpleasant ammonia smell

Coverage: Approx. 5m² per unit at 3mm



SX500

RAPID DRYING SMOOTHING COMPOUND

SX500 is a fast drying, smoothing compound for interior applications. It is moisture tolerant, has a 40% recycled content and can be applied in thicknesses of 2–15mm. SX500 has a compressive strength of 30 N/mm². The product will accept foot traffic from as little as 30 minutes and some floor coverings from 90 minutes. With a 10-minute working time, SX500 is ideally suited to applications that require a same day turnaround.

- Accepts both textile and resilient floor coverings in as little as 90 minutes
- OPC free, low odour product with 40% recycled content
- Moisture tolerant
- Suitable for use with underfloor heating

Coverage: Approx. 5m² per unit at 3mm

SX600^{NA}

RAPID SET SMOOTHING COMPOUND - NO AMMONIA



SX600^{NA} is a protein free, moisture tolerant smoothing underlayment that can be used over old adhesive residue in interior applications. Additionally, there is no need to prime if being applied to a TREMCO DPM. The product has a walk on time of 2 hours and can receive floor coverings after 4 hours. SX600NA has been designed for levelling uneven subfloors and is well suited to areas that require low odour products. It can be used under a DPM or over underfloor heating systems.

- Suitable for use over most adhesive residues
- Moisture tolerant – can be used under a DPM
- Suitable for use over underfloor heating systems
- Walk on after 2 hours, install floor coverings after 4 hours

Coverage: Approx. 5m² per unit at 3mm

Flooring Adhesives

High Performance Flooring Adhesives

Here at Tremco we offer a range of suitable adhesives to meet the pressing requirements of the market. Our range stems from Carpet Adhesives through to more specialist contact adhesives.



SF105

HIGH PERFORMANCE ACRYLIC ADHESIVE



SF105 is a thixotropic water-borne floor covering adhesive. It has been specially developed for linoleum and vinyl floor coverings, particularly the highly plasticised types. It is approved for use with PVC backed carpets. The adhesive has excellent grab characteristics and high achievable coverage rates.

- Strong initial tack and permanent bond
- Non-flammable
- Approved by major manufacturers (more information available upon request)
- Approved for practically all vinyl (PVC) floor coverings

Coverage: Up to 67m² per 15 kg unit using a 1.5 x 5mm notched trowel

SF108

PRESSURE SENSITIVE ACRYLIC ADHESIVE



A pressure sensitive adhesive for rubber and vinyl floor and wall coverings. Compatible with a wide range of vinyls including the highly plasticised types. This adhesive has amazing coverage of over 100m² per 15 litre unit when bonding PVC and smooth backed rubber floor coverings. SF108 can be used for dry bonding PVC floor coverings directly to our range of TREMCO epoxy damp proof membranes.

- Faster application, quicker installation
- Meets existing low VOC requirements
- Permanent tack
- Guaranteed no serration marks

Coverage: Up to 110m² per 15 litre unit using a 1.5 x 5mm notched trowel



SF110

CARPET ADHESIVE

An acrylic based multi-purpose adhesive which has good bond strength and a long open time, is easy to trowel and is non-staining. SF110 is suitable for hessian, ActionBac®, felt, rubber gel, & latex backed carpets with a 24 hour final set. It is not suitable for use with urethane backed carpets.

- Good initial grab
- Very low VOC
- Long open time
- Clean to use and non-staining
- Suitable for a wide range of carpets

Coverage: Up to 45 m² per 15 kg bucket

SF115

CONTACT ADHESIVE



A one part, solvent based, modified elastomer contact adhesive for use with rubber and PVC. Typical uses include bonding rubber tiles and sheet floor coverings, vinyl, and cork to horizontal or vertical surfaces, rubber nosings and covings, or PVC nosings and covings. TREMCO SF115 has excellent resistance to plasticiser migration from PVC floor coverings and covers up to 3m² of bonded area per litre.

- Extra strong bond
- Extended working life
- Fast drying but long “open time”
- Suitable for a wide range of floor coverings

Coverage: Up to 30m² per face per 5 litre or 15m² of bonded area



SF200

CARPET TILE TACKIFIER

A single component, waterborne liquid adhesive, which dries to a clear permanently tacky film. This product has been developed for the installation of Hexphalte/Bitumen backed carpet tiles, some grades of PVC backed carpet tiles, thermoplastic hot melt backed tiles, and underfelts. This liquid adhesive can be used to bond the floor coverings to concrete, sand/cement and is particularly suited for bonding carpet tiles to non-porous surfaces e.g. raised access flooring.

- Solvent-free
- Non-flammable
- Meets existing low VOC requirements
- Can be used on impervious surfaces

Coverage: Up to 135m² per 15 kg unit



TF448

HIGH PERFORMANCE CCS TAPE

TF448 is a tear resistant, very aggressive-grab double sided bonding tape. TF448 has been specially developed for the bonding of skirtings, capping and cove formers used in the installation of commercial floor coverings. Bonds to almost all construction materials.

- Strong initial tack and permanent bond
- Low toxicity
- No waste
- Speeds up installations

Available in a range of sizes:

25mm x 50m (10 rolls/box)
50mm x 50m (5 rolls/box)
85mm x 50m (3 rolls/box)

Technical Services

When installing flooring products, it is advisable to select a manufacturer where the support, training and technical expertise is second to none. As a brand of Tremco CPG UK, we offer customers an unrivalled level of technical support from initial product training to on-site technical assistance.

All Tremco CPG customers are provided with product training to ensure confidence in using our products to achieve optimum installation results. Our technical services team are on hand to help with:

- Moisture tests
- Installation advice
- Ongoing project support

And much more. To get in contact email flooringhelp@cpg-europe.com or call **+44 (0) 1942 251 400**.

Did You Know?

As a part of Tremco CPG UK, our product offering to contract flooring extends further than just flooring products, we offer a range of accessories to support.



AA292

CLEANING CLOTHS

AA292 Cleaning Cloths are made from spun bond fabrics fibre cloth with water, ethyl alcohol, glycerin and perfume soaked. They have been developed to be highly effective to remove wet and semi-cured adhesives, sealants and expanding foams, for use on hands, tools, and surfaces.

- Antibacterial
- Easily removes latex paint, adhesives, caulk, grease, oil, fingerprints, food stains and paint smears
- Convenient to transport on and off site




GS360

MULTI PURPOSE SILICONE

GS360 is suitable for a wide range of sealing applications, such as: perimeter sealing of door and window frames, sealing and draught proofing of glass and metal assemblies, general construction joints throughout the building.

- Bonds to many common construction materials
- Rapid curing and permanently flexible
- Excellent external weathering properties





Tremco CPG UK manufactures high performance building materials in order to solve the complex challenges faced by today's construction industry. It is the home for multiple European construction product brands, including illbruck, Flowcrete, Nullifire, Tremco, Vandex and Dryvit. With over 1,400 employees across Europe, we are committed to shaping a world where buildings and structures save energy, last longer and exceed sustainability benchmarks.

From joint sealing, bonding and insulation through to passive fire protection, flooring, waterproofing and roofing solutions – the product brands housed within Tremco CPG cover a wide array of different construction needs. Combined with the wealth of expertise, services and support we provide a truly unique offer – to make our customers more successful time after time.

Tremco CPG is part of RPM International Inc. – one of the world's leading construction products companies for both the industrial and consumer segments.

Tremco CPG's Core Values



Collaboration



Honesty & Integrity



Respect



Engagement



Sustainable

Delivering World-Class Construction Product Solutions.

The product brands housed within Tremco CPG cover a wide array of different construction needs and provide a wealth of complex services, support and systems that are rarely found together under one roof.



Window Insulation, Façade Construction, Exterior Insulation & EIFS, Structural & Inplant Glazing



Intumescent Coatings, Fire Stopping



Seamless Resin Flooring, Subfloor Preparation, Car Parking Structures



Civil Engineering, Potable & Waste Water Industry, Balconies, Terraces, Basements & Foundations



Liquid Applied Systems, Felt Systems, Vegetated Roofing

Tremco CPG's leading construction products brands...



Tremco CPG UK Limited
Coupland Road
Hindley Green
Wigan WN2 4HT UK

+44 (0) 1942 251400
hello@tremcocpg.com



www.tremco-europe.com



hello@tremcocpg.com



[@TremcoUK](https://www.facebook.com/TremcoUK)



[/company/tremcoUK](https://www.linkedin.com/company/tremcoUK)