

## **DECLARATION OF PERFORMANCE**

according Annex III of the regulation (EU) N° 305/2011 as it has effect in the United Kingdom in respect of Great Britain.

*ME060-20220420*

### **1. Unique identification code of the product-type:**

*ME060*

### **2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):**

*ME060*, batch number: see packaging of the product

### **3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

*Vapour Control Layer EN 13984:2013 – Type B*

### **4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):**

*Tremco CPG Germany GmbH  
Werner-Haepf-Straße 1  
D-92439 Bodenwöhr*

### **5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

*Not relevant*

### **6. System or systems of assessment and verification of constancy of performance of the construction product:**

*AVCP 3*

### **7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

- LGAI Technological Center, S. A. (Applus+), notified body number 0370  
- TSUS (notified body number 1301)

carried out the determination of the product type on the basis of type-testing (based on sampling carried out by the manufacturer), type calculation, tabulated values or descriptive documentation of the product.

### **8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

*not relevant*

## 9. Declared performance

Essential characteristics in accordance with EN 13984:2013 table ZA 1

Essential characteristics	Performance	Harmonised technical specification
REACTION TO FIRE (EN 13501-1)	A1	EN 13984:2013
WATER TIGHTNESS AND AIR TIGHTNESS		
Water Vapour diffusion Sd value (EN 1931)	> 2000 m > 10,000 MNs/g	EN 13984:2013
After ageing (EN 1296/ EN 1931)	complies	EN 13984:2013
TENSILE PROPERTIES		
Tensile strength (EN 12311-2) MD (longitudinal) CD (transversal)	> 960 N/50 mm > 960 N/50 mm	EN 13984:2013
Elongation at break (EN 12311-2) MD (longitudinal) CD (transversal)	< 6 % < 6 %	EN 13984:2013
Tear resistance (EN 12310-1) MD (longitudinal) CD (transversal)	150 N 150 N	EN 13984:2013
Other, information in accordance with EN 13984 is provided in the current technical data sheet.		EN 13984:2013

## 10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.  
Signed for and on behalf of the manufacturer by:

Walter Geyer, General Manager  
(name and function)



Bodenwöhr, 29,07,2024  
(place and date of issue)

(signature)

### Annex:

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according to Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

<b>CE</b>	0370 1301	<b>UK CA</b>
<p><i>Tremco CPG Germany GmbH</i>  <i>Werner-Haepf-Str. 1,</i>  <i>D-92439 Bodenwöhr</i></p> <p><b>22</b>  ME060-20220420</p>		
<p><b>EN 13984:2013 type B</b>  <i>Vapour Control Layer</i></p>		
<b>REACTION TO FIRE</b>		A1
<b>WATER TIGHTNESS and AIR TIGHTNESS</b>		
- water vapour permeability (EN 1931)		> 2000 m
- after ageing		Passed
<b>TENSILE PROPERTIES</b>		
- tensile strength MD/CD (EN 12311-2)		960 / 960 N/50mm
- elongation at break MD/CD (EN 12311-2)		< 6 % / < 6 %
- tear resistance MD/CD (EN 12310-1)		150 / 150 N