Technical Data Sheet

RW416 ALPHAGUARD BIOWASH

KEY BENEFITS SUMMARY

- Water based
- Neutralises mould and bacterial growth
- Easy to apply

PRODUCT INFORMATION

Description

RW416 is a single part, water based biocidal treatment.

Usage/Purpose

RW416 has been developed to neutralise bacterial growth prior to the application of AlphaGuard BIO systems.

Please Note

RW416 must be stored and transported in closed original cans.

Colour Clear

orour

Packaging 5kg can

Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Application

- Clean roof by pressure wash or similar to remove all visible growth.
- Apply by sheep skin roller at the required coverage rate.
- Allow to dry and remove any residue.

Health & Safety Precautions

Safety data sheet must be read and understood before use. Highly flammable - keep away from open flames and other ignition sources.

Availability

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details), or via local and national distributors.

TREMCO

Lasting Performance

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee/Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and and deemed accurate at the time of issue.

Tremco CPG UK Limited Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Composition	Water based
Drying time	1-2 hours
Viscocity (DIN 53019 at 20°C)	< 1mPa:s
Flash Point (ISO 1516)	+11.5°C
Storage	Store in shaded dry conditions between +5°C and +20°C
Shelf Life	12 months when stored as recommended in original unopened containers





Tremco CPG UK Limited Coupland Road, Hindley Green Wigan WN2 4HT +44 (0) 1942 251400 roofing.uk@tremcocpg.com



1

www.tremco-europe.com