

CI/SfB	(31)	Zt4
CAW P10		
Uniclass L675:P91		

Description

Open cell flexible polyurethane foam material with acrylate polymer impregnation.

Colour

Anthracite

Packaging

Supplied on rolls, pre-compressed, with single-sided self-adhesive to aid initial location.

Dimensions

Item No	Item Description	Mtrs per roll	Mtrs per box	Box Qty
TP610301667	illbruckTP610 10/1-2 Anthr	12.50	137.50	11
TP610301671	illbruckTP610 10/2-4 Anthr	10.00	110.00	11
TP610301679	illbruckTP610 15/3-6 Anthr	8.00	56.00	7
TP610301691	illbruckTP610 15/4-10 Anthr	5.60	39.20	7
TP610301681	illbruckTP610 20/3-6 Anthr	8.00	40.00	5
TP610301701	illbruckTP610 20/5-12 Anthr	4.30	21.50	5
TP610313282	illbruckTP610 25/5-12 Anthr	4.30	17.20	4
TP610398720	illbruckTP610 25/7-16 Anthr	3.30	13.20	4
TP610399128	illbruckTP610 30/9-20 Anthr	2.60	7.80	3
TP610315682	illbruckTP610 40/7-16 Anthr	3.30	23.10	7

Other dimensions on request

Tolerance according to DIN 7715 P3

Technical Information

Property	Test Method	Result
Building Material Class	DIN4102	B1 (flame retardant), P-NDS04-218
Water Vapour Diffusion, sd Value		< 0.5m
Air Permeability	EN 1026	$a \leq 0.1 \text{ m}^3/[\text{h} \cdot \text{m} \cdot (\text{daPa})\text{n}]$
Weathering	DIN 18 542	meets the requirements
Classification	DIN 18 542	BG1
Resistance to Water Penetration	EN 1027	Requirements are fulfilled up to 600 Pa
Compatibility with Conventional Building Materials	DIN 18 542	Meets the requirements
Service Temperature		-30°C to +90°C
Storage		Store in dry, shaded conditions between +1°C and + 20°C
Shelf Life		9 months when stored in cool, dry conditions in original unopened containers

Tools

Tape measure, cutting shears or knife and a flat bladed tool are required for installation.

Application

- Remove any contamination or mortar residue from the reveal. Any areas where significant undulations or damage is present should be repaired locally using an appropriate mortar. Check presence and condition of DPM and ensure cavities are filled/closed prior to fitting the new window.



TP610

illmod Compri

Usage / Purpose

TP610 illmod Compri is an impregnated foam tape which can be used for weather tight sealing of perimeter joints around windows and doors. In order to provide thermal insulation within the perimeter joint and maintain the energy rating of the window, it is recommended to also use FM330 Pro Foam Airseal. The use of this system will maintain the energy rating or U-value of the installed window and prevent thermal bridging through the perimeter gap. TP610 is available in a range of widths and thicknesses.

Key Benefits

- Maintains the energy rating or U-value of the installed window when used in conjunction with FM330
- Driving rain tightness to 600 Pa
- Meets CWCT test for site water tightness (TN41)
- Breathable
- All weather installation
- UV-resistant

- Install the window into the opening.
- Assuming internal plaster finish is to be undisturbed, apply FM330 Pro Foam Airseal to provide thermal insulation using the illbruck gun into the perimeter gap from the external side to a depth of approximately 50% of the frame thickness (e.g. 35 mm deep for a 70 mm frame) and allow to cure. Do not apply too much foam (allowing for post-expansion) so that there is insufficient space for application of the TP610 tape. (If access to the inside of the joint is possible due to removal of internal finishes, apply the FM330 foam from the inside after application of the TP610 and following full expansion).
- Select tape size from the table above. The joint width must be within the variation of the tape size (thickness) selected. It is advisable to select the tape size based on the nominal joint width being in the middle of the range (e.g. for a nominal 5 mm joint width, select size 15/3 – 6).
- Cut off the wedge shaped start of the roll and apply the tape to the outer edge of the window frame in the perimeter joint, recessed back from the external frame face by 1–2mm, applying a separate length for each side to be sealed, bonding with the aid of the self-adhesive. Allow an extra 20mm/m when cutting the tape length to allow for potential shrinkage - the dimension should be based on the opening size, not frame dimension. Make tight butt joints at the corners and at connections between separate lengths. Pay particular attention to the corner joints (See Fig. 1). Normally the TP610 is applied to the head and two sides to allow for insertion of packers under the cill.
- Any unintended small gaps at joints should be sealed with FS125 low modulus neutral cure silicone or SP525 hybrid sealant (black).
- FM330 Pro Foam Airseal should then be applied under the cill. Once this is cured, the ends of the window cill and the gap between the underside of the cill and structural opening should be sealed with a suitable sealant (e.g. FS125 or SP525) against the external reveal. Ensure that window cill end caps protrude for the full frame depth rather than just the projecting part of the cill.
- If the window is installed into a 'check reveal', apply the TP610 to the external face of the window frame, positioned to achieve a 2- 3 mm set-back behind the external opening. The TP610 is normally applied immediately prior to installing the window.




Fig 1:
Tape installation to perimeter joints



Fig 2:
TP610 and FM330 installed joints

Note

- High temperatures accelerate tape expansion, while low temperatures delay this. At ambient temperatures above 20°C, the tape should be stored in a cool place on the construction site away from direct sunlight. A small fridge is ideal for this.
- Remaining rolls in opened boxes should be maintained in a horizontal state and weighed down to prevent lateral expansion (telescoping) of the rolls. Whilst it is unnecessary to seal over the external face of the tape, the exposed edge can be plastered or painted over. The compatibility of sealants must be tested. In some cases, white sealants can be incompatible. The tape must not come into contact with chemicals containing solvents or aggressive chemicals.
- During application, the tape must not be exposed to weather and allowed to partially recover and lose compression, followed by re-compression as staining issues may occur.

Health & Safety Precautions

Safety data sheet must be read and understood before use.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in

accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.



Tremco CPG UK Limited
 Coupland Road
 Hindley Green, Wigan WN2 4HT
 United Kingdom
 T: +44 1942 251400
 F: +44 1942 251410

info.uk@tremcocpg.com
 www.tremcocpg.eu

