

## Technical Data Sheet

# TP654

## illmod TRIO 1050

08-05-2025 / V 1

### Description

TP654 is an impregnated, pre-compressed multi-functional window sealing tape based on 2 new technologies:

1. A 3-layer foam structure: the grey foam is an airtight closed cell foam which provides a 100% secure airtight connection to the window frame and the wall. The black foam has a slow recovery time which allows a successful installation.
2. An airtight layer is inserted inside the tape, connecting the grey foam and the black foam from the top to the bottom. Combined, these 2 technologies provide a high performance sealing level with a driving rain resistance up to 600Pa, a level more than double the requirements.



### Features and Benefits

- High raintight and airtight performance level
- Easy application: the tape can be installed either way around due to its variable Sd value.
- Secure airtight installation on the window frame and the wall due to its 3-layer foam structure
- Suitable for joints between 6 - 25 mm wide using only two sizes of TP654

### Please Note

- The compatibility of sealants, other than illbruck, must be tested.
- The tape must not come into contact with chemicals containing solvents or corrosive substances.
- High temperatures accelerate tape expansion, while low temperatures delay this.

### Guarantee / Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge. No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct. Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

### Health And Safety Precautions

Safety data sheet must be read and understood before use.

### Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Technical Data Sheet

**TP654**

**illmod TRI0 1050**

## Certification

