

ROOF SHEATHING AS
SPECIFIED

ENGINEERED TRUSSES

2x6" (38x140mm)
SILL PLATE ANCHORED TO
CONCRETE AS PER CODE

SOFFIT/FASCIA AS
PER CODE

CEILING TECHNOLOGY ANGULAR
CUT AT EDGE AND SEALED TO
WALL WITH NUDURA SPRAY FOAM

RIGID PANEL ($\frac{1}{2}$ " (13mm)
GYPSUM BOARD)

NUDURA 6" (152mm)
STANDARD FORM UNIT

HORZ/VERT
REINFORCEMENT AS
PER CODE

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

$\frac{1}{2}$ " (13mm)
GYPSUM BOARD

2 LAYERS OF NUDURA
CEILING TECHNOLOGY OR
STANDARD ATTIC
INSULATION AS PER CODE

6 MIL (0.15 mm)
POLYETHYLENE VAPOR BARRIER
(CONTINUOUS) LAPPED AND
SEALED TO NUDURA FORM

1x4 (28mmx89mm) FURRING
STRIP (FACTORY EMBEDDED)
(16" (400mm) c/c)

6x6 (152mmx152mm)
AIR SHIELD MEMBRANE

$\frac{1}{2}$ " (13mm) GYPSUM
BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
NUDURA CEILING TECHNOLOGY
BRICK VENEER FINISH
ROOF RAFTERS

REV. NO.
007 KS

REV. DATE:
MARCH 2012

DRAWN BY:
J. NEILON

DWG NO.

F6B02

SCALE:
1 : 8