

RW593

ALPHAGUARD PUMA CLEANER



KEY BENEFITS SUMMARY

- Cleaner for tools & equipment
- Degreaser for substrates prior to bonding

PRODUCT INFORMATION

Description

RW593 is a clear colourless single part cleaning agent.

Usage/Purpose

RW593 is an excellent agent for the cleaning of application tools used in the installation of AlphaGuard PUMA coatings.

RW593 can also be used to prepare previously installed soiled liquid coatings

Please Note

RW593 must be stored and transported in closed original cans.

Colour

Clear

Packaging

RW593 is supplied in 5 or 10kg cans.

Protective Equipment

USE IN WELL VENTILATED CONDITIONS and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

Application

- Generally it is advisable to apply the cleaner as soon as possible before skinning or curing has started to occur.
- Apply with a soft clean cloth or paper wipe.
- Remove with a second soft clean dry cloth or paper wipe.

Health & Safety Precautions

Safety data sheet must be read and understood before use. Highly flammable - keep away from open flames and other ignition sources.

Empty containers that have fully cured product residues can be considered as non-hazardous waste. Uncured product must be disposed of responsibly in accordance with local or national health and safety regulations. Please refer to the specific Tremco safety data sheet for further guidance.

Availability

Direct from Tremco CPG UK Limited (see back of leaflet for address and telephone details), or via local and national distributors.

Technical Service

Tremco CPG UK Limited has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

Guarantee/Warranty

Tremco CPG UK Limited products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with Tremco CPG UK Limited written instructions and (b) in any application recommended by Tremco CPG UK Limited, but which is proved to be defective, will be replaced free of charge

Tremco CPG UK Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

TECHNICAL DATA

PROPERTY	RESULT
Composition	RW593 is a clear, colourless liquid base on methyl methacrylate.
Density (ISO 2811 at 20°C)	0.94 g/cm ³
Viscosity (DIN 53019 at 20°C)	< 1mPa:s
Flash Point (ISO 1516)	+11.5°C
Storage	Store in shaded dry conditions between +15°C and +20°C
Shelf Life	12 months when stored as recommended in original unopened containers



Tremco CPG UK Limited
 Coupland Road, Hindley Green
 Wigan WN2 4HT
 +44 (0) 1942 251400
 roofing.uk@tremcocpg.com

Find Us @



www.tremco-europe.com

