

NUDURA 6" (152mm)
STANDARD FORM UNIT

BRICK VENEER c/w
1" (25mm) AIR
SPACE AND BRICK
TIES

WEEP HOLES AND
THROUGH WALL
FLASHING AS PER
CODE OR AS
SPECIFIED

STEEL LINTEL c/w
CONTINUOUS
CAULKING AT FRAME

BRICK VENEER
BEYOND

THRESHOLD

EXTERIOR CONCRETE
SLAB AND SLOPE AS
PER CODE

NUDURA 6"
(152mm) BRICK
LEDGE FORM UNIT
BEYOND

NUDURA
WATERPROOF MEMBRANE

HORIZ/VERT
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

1/2" (13mm) GYPSUM
BOARD

LINTEL
REINFORCEMENT AS
PER CODE OR AS
SPECIFIED

STEEL DOOR FRAME
c/w CAST IN
ANCHORS

STEEL DOOR

FLOOR FINISH
AS SPECIFIED

BLOCKING BETWEEN
JOISTS

FLOOR
JOISTS/TRUSSES
AS SPECIFIED

PROPRIETARY
EMBEDDED JOIST
ANCHORAGE SYSTEM
OR EQUIVALENT

1/2" (13mm)
GYPSUM BOARD

DISCLAIMER NOTICE:
SPECIFIC INFORMATION
REQUIRED FOR COMPLIANCE
WITH LOCAL CODES IS THE
RESPONSIBILITY OF THE
DESIGNER



NUDURA

INTEGRATED BUILDING TECHNOLOGY

Building Value.

NUDURA 6" (152mm) FORM UNIT
DOOR HEAD/SILL DETAIL
BRICK VENEER FINISH
WOOD ROUGH BUCK

REV. NO.
004 KS

DATE:
SEPT 2010

DRAWN BY:
J. NEILON

DWG NO.

E6E01

SCALE:
1 : 8